










SP series miniature sealed momentary pushbutton switches (p.c. and panel mt.) (cont.).

MODEL NO.	CKT.	FIG.
SP35P000000	SPDT	A
SP45P000000	DPDT	A
SP35Y000000	SPDT	B
SP45Y000000	DPDT	B
SP35W000000	SPDT	C
SP45W000000	DPDT	C
SP35WW000000	SPDT	D
SP45WW000000	DPDT	D
SP35S000077	SPDT	E
SP35P000077	SPDT	F





18000 series miniature snap action momentary pushbutton switches (panel mt.)

Contact rating 1 amp at 120 VAC or 30 VDC. Operating temp. range -30° C to 65° C. Glass filled polyamide actuator. Nickel plated brass bushing. Gold plated silver contacts. Silver plated brass terminals. Diallyl phthalate case. Tin plated steel bracket. Epoxy term. seal. Mounting hardware included. S.P. body size .275" w x .519" h x .472" d. D.P. body size .472" w x .519" h x .472" d. Mounts in .255" hole (except snap-in models). Snap-in models have black bezel & cap & mount in .492" x .590" panel cutout.

MOD. NO.	CKT.	FIG.	MODEL NUMBER	CKT.	FIG.
18535AD	SPDT	A	18245AD	DPDT	B
18545AD	DPDT	A	18835AD+U912+U1202	SPDT	C
18235AD	SPDT	B	18845AD+U912+U1202	DPDT	C




18000 series miniature snap action momentary pushbutton switches (p.c. mt.)

Contact rating 100 mA at 30 VDC. Operating temp. range -30° C to 65° C. Glass filled polyamide actuator. Nickel plated brass bushing. Gold plated brass contacts and terminals. Diallyl phthalate case. Tin plated steel bracket. Epoxy term. seal. S.P. body size .275" w x .519" h x .472" d. D.P. body size .472" w x .519" h x .472" d. Snap-in models have black bezel & cap & mount in .492" x .590" panel cutout.

MOD. NO.	CKT.	FIG.	MODEL NUMBER	CKT.	FIG.
18235YCD3	SPDT	A	18235YCD2X624	SPDT	C
18245YCD3	DPDT	A	18245YCD2X624	DPDT	C
18235WCD3	SPDT	B	18835CDX662	SPDT	D
18245WCD3	DPDT	B	18845CDX662	DPDT	D




8000 series miniature momentary or alternate action pushbutton switches (p.c. and panel mt.)

Contact ratings: Model no's with 'A' - 6 amps at 125 VAC, 3 amps at 250 VAC or 4 amps at 30 VDC (gold plated silver contacts). Model no's with 'CD' - 0.4 VA at 20 V. (gold plated brass contacts & terms.). Operating temp. range -40° C to 85° C. Nickel plated brass actuator & bushing. Diallyl phthalate case. Stainless steel housing. Epoxy term. seal. S.P. body size .275" w x .519" h x .767" d. D.P. body size .472" w x .519" h x .767" d. Mounts in .255" panel hole. Models with UL recognition available on request (silver contacts only).

SINGLE POLE- DOUBLE THROW			DOUBLE POLE- DOUBLE THROW		
MODEL NO.	ACTION	FIG.	MODEL NO.	ACTION	FIG.
8632AB	On Mom	A	8642AB	On Mom	A
8636AB	On On	A	8646AB	On On	A
8432AB	On Mom	B	8442AB	On Mom	B
8436AB	On On	B	8446AB	On On	B
8432WCDB	On Mom	C	8442WCDB	On Mom	C
8436WCDB	On On	C	8446WCDB	On On	C

4700 & 4800 series alternate action pushbutton switches (panel mt.)

SPST, SPDT, DPST & DPDT models. Contact ratings: 6 amps at 125 VAC or 3 amps at 250 VAC (silver contacts). Operating temp. range -20° C to 65° C. Polyamide actuator. Nickel plated brass bushing. Diallyl phthalate case. Epoxy term. seal. S.P. body size .472" w x .748" h x .550" d. D.P. body size .649" w x .826" h x .590" d. Mounts in .480" panel hole. 1 hex nut and one insulating knurled nut supplied. Color of knurled nut supplied in same color as actuator (specify below). Models ending with **UU** are UL, CSA & VDE recognized. Models not ending with **UU** are VDE recognized.

SINGLE POLE			DOUBLE POLE		
MODEL NO.	ACTION	FIG.	MODEL NO.	ACTION	FIG.
4731A02UU	On Off	A	4741A02UU	On Off	A
4736A02UU	On On	A	4746A02UU	On On	A
A4831A02	On Off	B	4841A02	On Off	B
4836A02	On On	B	4846A02	On On	B
47318A02UU	On Off	C			
47368A02UU	On On	C			

Note: Above models have black actuator and black knurled nut.
To specify a different color selection, replace the '02' in model number with the following color code:

Color	Code
Blue	01
Green	03
Yellow	05
Red	06
White	07/1
Orange	09