

CA SERIES SNAP-IN ILLUMINATED POWER ROCKER SWITCHES



A

B

Rating: 15 Amps at 125 V AC or 28 V DC; 10 Amps at 250 V AC; 1/4 HP at 125 V AC or 250 V AC (UL/CSA). **Lamp:** 125 V neon. **Mounting Hole:** SP 1.102" (28,00) x .420" (10,67). DP 1.102" (28,00) x .866" (22,00).

C&K Part No.	No. Poles	Switch Function	Actuator Color	Housing Color	Fig.
CA04J137207Q	SPST	Off/On	Red	Black	A
CA04J137107Q	SPST	Off/On	Red	White	A
CA24J137207Q	DPST	Off/On	Red	Black	B
CA24J137107Q	DPST	Off/On	Red	White	B

D SERIES MINIATURE POWER ROCKER SWITCHES



C

D

E

Rating: D10X and D20X Models: 4 Amps at 125 V AC, 2 Amps at 250 V AC (UL/CSA); 4(2) Amps at 125 V AC, 2(1) Amps at 250 V AC, T85 (VDE). D50X & D60X Models: 10 Amps at 125 V AC, 5 Amps at 250 V AC (UL/CSA); 10(6) Amps at 125 V AC, 5(3) Amps at 250 V AC, T85 (VDE). **Terminals:** 187" x .031" (4,75 x 0,79) quick connect or right angle PC with .277" (7,04) spacing.

C&K Part No. Rating at 125, 250 V AC	No. Poles	Switch Function	Fig.
D101J12S215PQF	SPDT	On-None-On	C
D102J12S215PQF	SPST	On-None-On	C
D103J12S215PQF	SPDT	On-Off-On	C
D105J12S215PQF	SPDT	Mom-Off-Mom	C
D108J12S215PQF	SPDT	On-None-Mom	C
D501J12S215PQF	SPDT	On-None-On	C
D502J12S215PQF	SPST	On-None-On	C
D503J12S215PQF	SPDT	On-Off-On	C
D508J12S215PQF	SPDT	On-None-Mom	C
D201J12S215PQF	DPDT	On-None-On	D
D203J12S215PQF	DPDT	On-Off-On	D
D601J12S215PQF	DPDT	On-None-On	D
D603J12S215PQF	DPDT	On-Off-On	D
D101J12S2APQF	SPDT	On-None-On	E
D103J12S2APQF	SPDT	On-Off-On	E

DF SERIES POWER ROCKER SWITCHES



F

G

Rating: 16 Amps at 125 V AC (UL/CSA); 16(2)/250-T100, TUV. **Actuator:** Nylon, black, white or gray, with on-off markings. **Housing:** Nylon, black. **Movable Contacts:** Fine silver, silver plated. **Mounting Hole:** If panel thickness is 0.048" to 0.078", mounting hole is 1.030" x 0.490" to 0.495".

C&K Part No.	No. Poles	Actuator Color	Fig.
DF62J12S215QF	DPST	Black	F
DF62J12S2APQF	DPST	Black	G

7000 SERIES SNAP-IN ROCKER SWITCHES



Rating: 5 Amps at 120 V AC or 28 V DC; 2 Amps at 250 V AC. Epoxy seal. **Mounting Hole:** .500" (12,70) x .600" (15,24).

C&K Part No.	No. Poles	Switch Function
7101J51ZQE22	SPDT	On-None-On
7103J51ZQE22	SPDT	On-Off-On
7105J51ZQE22	SPDT	Mom-Off-Mom
7107J51ZQE22	SPDT	On-Off-Mom
7108J51ZQE22	SPDT	On-None-Mom
7201J51ZQE22	DPDT	On-None-On
7203J51ZQE22	DPDT	On-Off-On
7205J51ZQE22	DPDT	Mom-Off-Mom
7207J51ZQE22	DPDT	On-Off-Mom
7208J51ZQE22	DPDT	On-None-Mom

7000 SERIES PANEL-MOUNTED ROCKER SWITCHES



Rating: 5 Amps at 120 V AC or 28 V DC; 2 Amps at 250 V AC. Epoxy seal. **Mounting Hole:** .937" (23,80). .707" (17,96) x .418" (10,62).

C&K Part No.	No. Poles	Switch Function
7101J1ZQE2	SPDT	On-None-On
7103J1ZQE2	SPDT	On-Off-On
7105J1ZQE2	SPDT	Mom-Off-Mom
7107J1ZQE2	SPDT	On-Off-Mom
7201J1ZQE2	DPDT	On-None-On
7203J1ZQE2	DPDT	On-Off-On
7205J1ZQE2	DPDT	Mom-Off-Mom
7207J1ZQE2	DPDT	On-Off-Mom

E SERIES SEALED ROCKER SWITCHES



Rating: 0.4 VA max. at 20 V AC or DC max. Epoxy seal, PC mount, spacing: .185" (4,70) typ. **Switch Support:** Brass or steel, tin plated.

C&K Part No.	No. Poles	Switch Function
E101J1V3BE2	SPDT	On-None-On
E103J1V3BE2	SPDT	On-Off-On
E105J1V3BE2	SPDT	Mom-Off-Mom
E107J1V3BE2	SPDT	On-Off-Mom
E201J1V3BE2	DPDT	On-None-On
E203J1V3BE2	DPDT	On-Off-On
E301J1V3BE2	3PDT	On-None-On
E303J1V3BE2	3PDT	On-Off-On

E SERIES PC-MOUNTED SEALED ROCKER AND LEVER HANDLE SWITCHES



H

I

Internal o-ring seal. **Rating:** 0.4 VA max. at 20 V AC or DC max. Epoxy seal. Terminal spacing: .185" (4,70) typ.

C&K Part No.	No. Poles	Switch Function	Fig.
E101J1ABE2	SPDT	On-None-On	H
E103J1ABE2	SPDT	On-Off-On	H
E105J1ABE2	SPDT	Mom-Off-Mom	H
E107J1ABE2	SPDT	On-Off-Mom	H
E201J1ABE2	DPDT	On-None-On	H
E101J1AV2BE2	SPDT	On-None-On	I
E103J1AV2BE2	SPDT	On-Off-On	I
E105J1AV2BE2	SPDT	Mom-Off-Mom	I