


Basic Switches Standard

BZ/BA Series

2
SWITCHES
&
KNOBS

TYPICAL DIMENSIONS (For reference only)

BZ Type




ROLLER LEVER ORDER GUIDE

Catalog Listing	Recommended For	Electrical Data and UL Codes	O.F. newtons ounces	O.T. min. mm inches	D.T. mm inches	O.P.* mm inches
BZ-2RW822	1.05 inch (26,7 mm) steel roller lever application. Solder terminal.	15 Amps L96	1,67 6	2,39 .094	0,08-0,51 .003-.020	30,17 1.118
BZ-2RW822-A2	1.05 inch (26,7 mm) steel roller lever applications	15 Amps L96	1,67 6	2,39 .094	0,08-0,51 .003-.020	30,17 1.188
BZ-2RW8225551-A2	As above with dustproof and splash resistant seal	15 Amps L96	1,67 6	2,39 .094	0,08-0,51 .003-.020	30,17 1.188
BA-2RV22-A2	Up to 20 ampere load handling	20 Amps L23	1,67 6	0,76 .030	1,14 .045 max.	29,77 1.172
BE-2RV22-A4	Up to 25 ampere load handling	25 Amps —	1,67 6	0,76 .030	1,14 .045 max.	29,77 1.172

Except where stated * ±0,38 mm
±.015 in.

BZ/BA Type




ROLLER LEVER ORDER GUIDE

Catalog Listing	Recommended For	Electrical Data and UL Codes	O.F. newtons ounces	O.T. min. mm inches	D.T. mm inches	O.P.* mm inches
BZ-2RW82-A2	1.90 inch (48,3 mm) steel roller lever applications	15 Amps L96	0,97 3.5	3,96 .156	0,10-1,0 .004-.040	30,17±0,76 1.188±.030
BA-2RV2-A2	Up to 20 ampere load handling	20 Amps L23	0,97 3.5	1,52 .060	2,16 .085	30,17±0,76 1.188±.030
BZ-RW922-A2	Best repeatability and O.P. stability	10 Amps L95	3,34 12	2,54 .100	0,013-0,025 .0005-.0010	31,37 1.235
BZ-2RW826-A2	One way roller (9,4 mm × 3,8 mm) .37" dia. × .15" wide roller	15 Amps L96	1,67 6	2,39 .094	0,08-0,51 .003-.020	41,34 1.625

* ±0,38 mm
±.015 in.


BZ Type



FLEXIBLE LEAF ORDER GUIDE

Catalog Listing	Recommended For	Electrical Data and UL Codes	O.F. newtons ounces	O.T. min. mm inches	D.T. mm inches	O.P.* mm inches
BZ-2RL-A2	Force and stability of the flexible actuator	15 Amps L96	1,39 5	1,52 .060	1,27 .050	17,48 .688

BZ Type



FLEXIBLE ROLLER LEAF ORDER GUIDE

Catalog Listing	Recommended For	Electrical Data and UL Codes	O.F. newtons ounces	O.T. min. mm inches	D.T. mm inches	O.P.* mm inches
BZ-2RL2-A2	Force and stability of the flexible leaf with roller	15 Amps L96	1,39 5	1,52 .060	1,27 .050	28,6 1.125
BZ-2RL25551-A2	Dustproof and splash resistant seal	15 Amps L96	1,95 7	1,52 .060	1,27 .050	28,6 1.125

** ±0,76 mm
±.030 in.