

**Series SSB3****Specifications**

(All dimensions in inches)

**MATERIALS**

<b>Insulator</b>	Polypropylene
<b>Color</b>	Black
<b>Terminal Contact</b>	Brass
<b>Plating</b>	Bright Tin
<b>Screw</b>	Steel
<b>Plating</b>	Zinc + Chromate
<b>Clamp</b>	Steel
<b>Plating</b>	Zinc + Chromate

**DIMENSIONAL DATA**

<b>Contact Spacing</b>	.325 in
<b>Screw Size</b>	6-32
<b>Wire Range (Binding Head Screw)</b>	#14-26 AWG.
<b>Wire Strip Length</b>	.31 in
<b>Mounting Screw Size</b>	#6
<b>Wire Lug Width (Max.)</b>	.265 in

**MECHANICAL TOLERANCES**

<b>Recommended Torque</b>	9 in -lbs
<b>Recommended Screwdrivers</b>	Stanley 1006-4 Sears Craftsman 41581 Any #2 Phillips-Head

**ENVIRONMENTAL LIMITS**

<b>Operating Temperature Range</b>	-60°C To +105°C (-76°F To +221°F)
------------------------------------	--------------------------------------

**FLAMMABILITY**

<b>UL94 Rating</b>	V-2
--------------------	-----

**ELECTRICAL CHARACTERISTICS**

<b>Dielectric Withstand</b>	4500V
<b>Operating Voltage</b>	300V
<b>Maximum Current</b>	15A

**RECOMMENDED PCB HOLE PATTERN**