


Type 601

Description
Springclamp system provides constant contact resistance and gas tight connection. 5mm spacing and is available in seven different colors.

Electrical/Technical Data
(according to UL/CSA)
Voltage: 250V - 5mm
Current: 13A
Wire range: 14-28 AWG
Pin Diameter: .8 mm x 1.0 mm
PCB hole diameter: 1.4 mm
Wire strip length: 6 mm
Housing: UL 94V-0


Spring clamp: stainless chrome molybdenum steel
Contact pin: copper alloy, tin pl.
Pole size: 2

316011xx=Pole Size (2-24)



Designed to VDE 0110

Shipped wire ready for tool-less operation




Type 602

Description
Springclamp system provides constant contact resistance and gas tight connection. 2.5mm spacing and is available in seven different colors.

Electrical/Technical Data
(according to UL/CSA)
Voltage: 125V - 2.5mm
Current: 4A
Wire range: 20-28 AWG
Pin Diameter: .8 mm square
PCB hole diameter: 1.3 mm
Wire strip length: 6 mm
Housing: UL 94V-0


Spring clamp: stainless chrome molybdenum steel
Contact pin: copper alloy, tin plated
Pole size: 2 - 24

316021xx=Pole Size (2-24)



Designed to VDE 0110

Shipped wire ready for tool-less operation




Type 605

Description
Pluggable spring-clamp system provides constant contact resistance and gas tight connection. 5mm spacing and is available in seven different colors.


Electrical/Technical Data
(according to UL/CSA)
Voltage: 250V - 5mm
Current: 13A
Wire range: 14-28 AWG
Square Pin: .8 mm x 1.0 mm
PCB Hole Diameter: 1.4 mm
Wire strip length: 6 mm
Housing: UL 94V-0

Spring clamp: stainless chrome molybdenum steel
Contact pin: copper alloy, tin plated
Pole size: 2 - 24



Designed to VDE 0110

Shipped wire ready for tool-less operation




Type 607

Description
Pluggable spring-clamp system provides constant contact resistance and gas tight connection. 5mm spacing and is available in seven different colors.

Electrical/Technical Data
(according to UL/CSA)
Voltage: 300V - 5mm
Current: 10A
Wire range: 18-28 AWG
Wire strip length: 4 mm
Housing: UL 94V-0

Spring clamp: stainless chrome molybdenum steel
Contact pin: copper alloy, tin plated
Pole size: 2 - 24

316071xx=Pole Size (2-24)



Designed to VDE 0110

Shipped wire ready for tool-less operation

