


## FNA SERIES DUAL-ELEMENT, PIN INDICATION, TIME-DELAY FUSES



1 1/2" long x 1 3/32" dia. fuses. Interrupting Rating: 10,000A at 125V. UL Recognized, 0-8A, 10A at 250V, Guide JDYX, File E19180. CSA Certified, 0-10 at 125V, Class 1422-01, File 53787, UL Listed 0-8 1/10A at 250V, 1-15A at 125V, Guide JDYX, File 19180. CSA Certified, 0-8 1/10A at 250V, 1-10A at 125V, Class 1422-01, File 53787.

Mfr. No.	Rating Amps	Ctn. Qty.	Mfr. No.	Rating Amps	Ctn. Qty.
<b>250V or Less</b>					
FNA-1/10	1/10	10	FNA-4/10	4/10	10
FNA-1/8	1/8	10	FNA-1/2	1/2	10
FNA-15/100	15/100	10	FNA-9/10	9/10	10
FNA-2/10	2/10	10	FNA-3/4	3/4	10
FNA-1/4	1/4	10	FNA-8/10	8/10	10
FNA-3/10	3/10	10	.....	.....	.....
<b>125V or Less</b>					
FNA-1	1	10	FNA-3 1/2	3 1/2	10
FNA-1 1/8	1 1/8	10	FNA-4	4	10
FNA-1 1/4	1 1/4	10	FNA-4 1/2	4 1/2	10
FNA-1 1/10	1 1/10	10	FNA-5	5	10
FNA-1 1/2	1 1/2	10	FNA-5 9/10	5 9/10	10
FNA-1 9/10	1 9/10	10	FNA-6	6	10
FNA-1 1/10	1 1/10	10	FNA-6 1/4	6 1/4	10
FNA-2	2	10	FNA-7	7	10
FNA-2 1/4	2 1/4	10	FNA-8	8	10
FNA-2 1/2	2 1/2	10	FNA-9	9	10
FNA-2 9/10	2 9/10	10	FNA-10	10	10
FNA-3	3	10	FNA-12	12	5
FNA-3 9/10	3 9/10	10	FNA-15	15	5
<b>32 Volts or Less</b>					
FNA-20	20	5	FNA-30	30	5
FNA-25	25	5	.....	.....	.....

## SC SERIES TIME-DELAY, 480V AC, CLASS G FUSES



25-30A—480V AC, 300V DC; 35-60A—480V AC, 400V DC. Interrupting Rating: 100,000A RMS Symmetrically. Can be used in 120/208V, 120/240V and 227/480V circuits. Branch circuit fuses that pass temporary overloads in fuses above 6A. Minimum opening time of 12 sec. with 200% overload. UL Listed, Class G, Guide JDDZ, File E4273. CSA Certified, Class 1422-01, File 53787.

Mfr. No.	Rating Amps	Ctn. Qty.	Mfr. No.	Rating Amps	Ctn. Qty.
<b>1.319" Long x 0.41" Dia.</b>					
SC-1/2	1/2	10	SC-5	5	10
SC-1	1	10	SC-6	6	10
SC-1 1/2	1 1/2	10	SC-8	8	10
SC-2	2	10	SC-10	10	10
SC-3	3	10	SC-15	15	10
SC-4	4	10	.....	.....	.....
<b>1.419" Long x 0.41" Dia.</b>					
SC-20	20	10	.....	.....	.....
<b>1.639" Long x 0.41" Dia.</b>					
SC-25	25	10	SC-30	30	10
<b>2.259" Long x 0.41" Dia.</b>					
SC-35	35	10	SC-50	50	10
SC-40	40	10	SC-60	60	10
SC-45	45	10	.....	.....	.....

## GMW SERIES PIN BASE FUSES



Carry 100%, open at 200% within 10 sec. or less. Interrupting Rating: 35A at 125V. HWA holder ordered separately. AF knob for fuseholder makes holder waterproof. UL Recognized. Packaged 10/ctn.

Mfr. No.	Rating Amps	Mfr. No.	Rating Amps
GMW-1/100	1/100	GMW-4/10	4/10
GMW-1/64	1/64	GMW-1/2	1/2
GMW-1/32	1/32	GMW-3/4	3/4
GMW-1/16	1/16	GMW-1	1
GMW-1/10	1/10	GMW-1 1/2	1 1/2
GMW-1/8	1/8	GMW-2	2
GMW-2/10	2/10	GMW-3	3
GMW-1/4	1/4	GMW-4	4
GMW-3/10	3/10	GMW-5	5

## GLR SERIES FAST ACTING, NON-REJECTING FUSES



Fast acting, non-rejecting fuse contained in cap for use with HLR Fuseholder. Interrupting Rating: 10,000A. UL Listed 0-15A; Guide JDYX, File E19180. CSA Certified 0-10A; Class 1422-01, File 53787. 5/ctn.

Mfr. No.	Rating Amps	Mfr. No.	Rating Amps
GLR-1/2	1/2	GLR-6	6
GLR-1	1	GLR-7	7
GLR-1 1/2	1 1/2	GLR-8	8
GLR-1 9/10	1 9/10	GLR-9	9
GLR-2	2	GLR-10	10
GLR-3	3	GLR-12	12
GLR-4	4	GLR-15	15
GLR-5	5	.....	.....

## FNQ SERIES TIME-DELAY FUSES 500 VAC, (5 AG SIZE)



1 1/2" long x 1 3/32" dia. fibre tube fuse. Interrupting Rating: 10,000A. UL Listed, Guide JDYX, File E19180. CSA Certified, Class 1422-01, File 53787. 10/ctn.

Mfr. No.	Rating Amps	Mfr. No.	Rating Amps
FNQ-1/10	1/10	FNQ-3	3
FNQ-1/8	1/8	FNQ-3 3/10	3 3/10
FNQ-15/100	15/100	FNQ-3 1/2	3 1/2
FNQ-3/16	3/16	FNQ-4	4
FNQ-2/10	2/10	FNQ-4 1/2	4 1/2
FNQ-1/4	1/4	FNQ-5	5
FNQ-3/10	3/10	FNQ-5 9/10	5 9/10
FNQ-4/10	4/10	FNQ-6	6
FNQ-1/2	1/2	FNQ-6 1/4	6 1/4
FNQ-5/10	5/10	FNQ-7	7
FNQ-9/10	9/10	FNQ-8	8
FNQ-1	1	FNQ-9	9
FNQ-1 1/8	1 1/8	FNQ-10	10
FNQ-1 1/4	1 1/4	FNQ-12	12
FNQ-1 1/2	1 1/2	FNQ-14	14
FNQ-1 9/10	1 9/10	FNQ-15	15
FNQ-2	2	FNQ-20	20
FNQ-2 1/4	2 1/4	FNQ-25	25
FNQ-2 1/2	2 1/2	FNQ-30	30