

A-Series Rocker

6

CIRCUIT BREAKERS & FUSES

COIL RATING ⁶		
CURRENT COIL		
	AMPERES	
	210	0.100
	225	0.250
S	250	0.500
E	275	0.750
L	410	1.000
E	425	2.500
C	450	5.000
T	475	7.500
	610	10.000
O	615	15.000
N	620	20.000
E	625 ⁷	25.000
	630 ⁷	30.000
	635 ^{7,8}	35.000
	640 ^{7,8}	40.000
	650 ^{7,8}	50.000
VOLTAGE COIL ^{5a}		
	VOLTS	MIN. TRIP VOLTS
A06	6 DC	5 DC
A12	12 DC	10 DC
K20	120 AC	65 AC
L40	240 AC	130 AC

ACTUATOR COLOR ¹			
SELECT ONE			
SINGLE COLOR ROCKER		VISI-ROCKER	
ROCKER		VISI	
COLOR LEGEND ^{9b}			
C	Black	I-O (White)	A White I-O (White)
D	Black	ON-OFF (White)	B White ON-OFF (White)
2	Black	Dual (White)	1 White Dual (White)
F	Red	I-O (White)	F Red I-O (Red)
G	Red	ON-OFF (White)	G Red ON-OFF (Red)
3	Red	Dual (White)	3 Red Dual (Red)
H	Green	I-O (White)	H Green I-O (Green)
J	Green	ON-OFF (White)	J Green ON-OFF (Green)
4	Green	Dual (White)	4 Green Dual (Green)
K	Blue	I-O (White)	
L	Blue	ON-OFF (White)	
5	Blue	Dual (White)	
M	Yellow	I-O (Black)	
N	Yellow	ON-OFF (Black)	
6	Yellow	Dual (Black)	
P	Gray	I-O (Black)	
Q	Gray	ON-OFF (Black)	
7	Gray	Dual (Black)	
R	Orange	I-O (Black)	
S	Orange	ON-OFF (Black)	
8	Orange	Dual (Black)	

AGENCY APPROVAL	
A	W/O Approval
B	UL Recognized
C	UL Recognized; CSA Certified
D¹⁰	UL Recognized; CSA & VDE Certified
I	UL 1500 Ignition Protected; UL Recognized; CSA Certified

24 - 630 - 2 3 1 - D

FREQUENCY AND DELAY	
03	DC, 50/60Hz When Delay is not applicable, i.e. Switch Only circuit option.
10 ^{5a}	DC Instantaneous
11	DC Ultra Short
12	DC Short
14	DC Medium
16	DC Long
20 ^{5a}	50/60Hz Instantaneous
21	50/60Hz Ultra Short
22	50/60Hz Short
24	50/60Hz Medium
26	50/60Hz Long
32	DC, 50/60Hz Short
34	DC, 50/60Hz Medium
36	DC, 50/60Hz Long
42 ^{5b}	50/60Hz Short (Hi-Inrush)
44 ^{5b}	50/60Hz Medium (Hi-Inrush)
46 ^{5b}	50/60Hz Long (Hi-Inrush)
52 ^{5b}	DC Short (Hi-Inrush)
54 ^{5b}	DC Medium (Hi-Inrush)
56 ^{5b}	DC Long (Hi-Inrush)

TERMINAL ^{7,11}	
1	Push-On 0.250 Tab (Q.C.)
2	Screw 8-32 w/ Upturned Lugs
3	Screw 8-32 (Bus Type)
4	Screw 10-32 w/ Upturned Lugs
5 ⁸	Screw 10-32 (Bus Type)

PRINTED CIRCUIT BOARD TERMINAL AVAILABLE; CONSULT FACTORY

MOUNTING ¹¹	
STANDARD ROCKER BEZEL	
1	Threaded insert 6-32x0.195 in. deep
2	Threaded insert ISO M3x5mm deep
ROCKERGUARD BEZEL ^{9d} or PUSH-TO-RESET BEZEL ^{9c,9e}	
3	Threaded insert 6-32 x0.195 in. deep
4	Threaded insert ISO M3x5mm deep