

6

CIRCUIT BREAKERS & FUSES

COIL RATING ⁶	
CURRENT COIL	AMPERES
210	0.100
225	0.250
250	0.500
275	0.750
410	1.000
425	2.500
450	5.000
475	7.500
610	10.000
615	15.000
620	20.000
625	25.000
630	30.000
635⁷	35.000
640⁷	40.000
650⁷	50.000
VOLTAGE COIL ^{5a}	
	MIN. TRIP RATING VOLTS
A06	6 DC 5 DC
A12	12 DC 10 DC
K20	120 AC 65 AC
L40	240 AC 130 AC

ACTUATOR COLOR ⁹		
	COLOR	LEGEND
1	White	Dual (Black)
2	Black	Dual (White)
3	Red	Dual (White)
6	Yellow	Dual (Black)

AGENCY APPROVAL	
A	W/O Approval
B	UL Recognized
C	UL Recognized CSA Certified
D¹¹	UL Recognized CSA & VDE Certified
I¹¹	UL Recognized Std 1077 UL Recognized Std 1500 (Ignition Protection) CSA Certified

10 - 450 - 1 2 1 - D

FREQUENCY AND DELAY	
03	DC, 50/60Hz When Delay is not applicable, i.e. Switch Only circuit option.
10^{5a}	DC Instantaneous
11	DC Ultra Short
12	DC Short
14	DC Medium
16	DC Long
20^{5a}	50/60Hz Instantaneous
21	50/60Hz Ultra Short
22	50/60Hz Short
24	50/60Hz Medium
26	50/60Hz Long
32	DC, 50/60Hz Short
34	DC, 50/60Hz Medium
36	DC, 50/60Hz Long
42^{5b}	50/60Hz Short (Hi-Inrush)
44^{5b}	50/60Hz Medium (Hi-Inrush)
46^{5b}	50/60Hz Long (Hi-Inrush)
52^{5b}	DC Short (Hi-Inrush)
54^{5b}	DC Medium (Hi-Inrush)
56^{5b}	DC Long (Hi-Inrush)

TERMINAL ⁸	
1	Push-On 0.250 Tab (Q.C.)
2	Screw 8-32 w/ Upturned Lugs
3	Screw 8-32 (Bus Type)
4	Screw 10-32 w/ Upturned Lugs
5	Screw 10-32 (Bus Type)
PRINTED CIRCUIT BOARD TERMINAL AVAILABLE; CONSULT FACTORY	

MOUNTING	
1¹⁰	Threaded insert, 6-32 x 0.195 inches deep - 2/pole
2	Threaded insert, ISO M3 x 5mm deep - 2/pole
5¹⁰	Front Panel Snap-In, 0.75 inch wide Bezel/Pole
7¹⁰	Front Panel Snap-In, 0.96 inch wide Bezel on Single Pole units. .105 inch Bezel Overhang Per Side on Multi-Pole units.