

CRADLE® SERIES RELAYS



T154 and T163 Cradle Series industrial relays with versatile mounting means including solder, PC board and socket options. Sensitivity selection to match applications ranging from 20 mW to 250 mW per pole. Contact selection meet load switching requirements. UL Recognized, File E20604. CSA Certified, File LR34171.

VOLTAGE ADJUSTED DC RELAYS

Mfr. No.					
Solder Plug-In	PC Mount	Input (VDC)	Coil Resis (Ohms)	Power (mW)	Contacts
Standard Single Point 2 Amp Contacts					
T154-2C	TP154-2C	12	185	690	2PDT
T154-2C	TP154-2C	24	700	690	2PDT
T154-4C	TP154-4C	12	185	690	4PDT
T154-4C	TP154-4C	24	700	690	4PDT
T154-6C	TP154-6C	12	90	1400	6PDT
T154-6C	TP154-6C	24	430	1400	6PDT
T154-8C	TP154-8C	12	75	1900	8PDT
T154-8C	TP154-8C	24	430	1900	8PDT

Mfr. No.					
Solder Plug-In	PC Mount	Input (VDC)	Coil Resis (Ohms)	Power (mW)	Contacts
Standard Single Point 5 Amp contacts					
TF154-2C	TFP154-2C	12	185	690	2PDT
TF154-2C	TFP154-2C	24	700	690	2PDT
TF154-4C	TFP154-4C	12	185	690	4PDT
TF154-4C	TFP154-4C	24	700	690	4PDT
TF154-6C	TFP154-4C	12	90	1400	6PDT
TF154-6C	TFP154-6C	24	430	1400	6PDT
TF154-8C	TFP154-8C	12	75	1900	8PDT
TF154-8C	TFP154-8C	24	430	1900	8PDT

Mfr. No.					
Solder Plug-In	PC Mount	Input (VDC)	Coil Resis (Ohms)	Power (mW)	Contacts
Sensitive Single Point 2 Amp Contacts					
TS154-2C	TSP154-2C	12	800	100	2PDT
TS154-2C	TSP154-2C	24	3200	100	2PDT
TS154-4C	TSP154-4C	12	430	175	4PDT
TS154-4C	TSP154-4C	24	1800	175	4PDT
TS154-6C	TSP154-6C	12	350	250	6PDT
TS154-6C	TSP154-6C	24	1275	250	6PDT
TS154-8C	TSP154-8C	12	190	400	8PDT
TS154-8C	TSP154-8C	24	800	400	8PDT

Mfr. No.					
Solder Plug-In	PC Mount	Input (VDC)	Coil Resis (Ohms)	Power (mW)	Contacts
Ultra Sensitive Single Point 1 Amp Contacts					
TSS154-2C	TSSP154-2C	24	7500	40	2PDT
TSS154-4C	TSSP154-4C	24	3700	80	4PDT

Mfr. No.					
Solder Plug-In	PC Mount	Input (VDC)	Coil Resis (Ohms)	Power (mW)	Contacts
Standard Bifurcated 2 Amp Contacts					
T163-2C	TP163-2C	12	185	690	2PDT
T163-2C	TP163-2C	24	700	690	2PDT
T163-4C	TP163-4C	12	185	690	4PDT
T163-4C	TP163-4C	24	700	690	4PDT
T163-6C	TP163-6C	12	90	1400	6PDT
T163-6C	TP163-6C	24	430	1400	6PDT
T163-8C	TP163-8C	12	75	1900	8PDT
T163-8C	TP163-8C	24	430	1900	8PDT

CRADLE® SERIES MAGNETIC LATCH COIL DC RELAYS



T351 and T362 Cradle Series bi-stable and magnetic latch industrial relays. Single or dual coil construction. Versatile mounting means including solder, PC board and socket options. Contact selection to meet load switching requirements input voltage from 6 VDC to 110 VDC. UL Recognized, File E20604. CSA Certified, File LR34171. **Weight:** 1.5 Oz. to 4.0 Oz.

SINGLE COIL

Mfr. No.					
Solder Plug-In	PC Mount	Input (VDC)	Coil Resis (Ohms)	Power (mW)	Contacts
Single Point 2 Amp Contacts					
T351-2C	TP351-2C	24	630	300	2PDT
T351-4C	T351-4C	24	630	300	4PDT
Bifurcated 2 Amp Contacts					
T362-2C	TP362-2C	24	630	300	2PDT
T362-4C	TP362-4C	24	630	300	4PDT

DUAL COIL

Mfr. No.					
Solder Plug-In	PC Mount	Input (VDC)	Coil Resis (Ohms)	Power (mW)	Contacts
Single Point 2 Amp Contacts					
T351-2C	TP351-2C	2/24	485/485	600	2PDT
T351-4C	TP351-4C	2/24	485/485	600	4PDT
Bifurcated 2 Amp Contacts					
T362-2C	TP362-2C	2/24	485/485/600	2PDT	4PDT
T362-4C	TP362-4C	2/24	485/485	600	4PDT
Single Point 5 Amp Contacts					
TF351-2C	TFP351-2C	2/24	485/485	600	2PDT
TF351-4C	TFP351-4C	2/24	485/485	600	4PDT

Mfr. No.					
Solder Plug-In	PC Mount	Input (VDC)	Coil Resis (Ohms)	Power (mW)	Contacts
Sensitive Bifurcated 2 Amp Contacts					
TS163-2C	TSP163-2C	12	800	100	2PDT
TS163-2C	TSP163-2C	24	3200	100	2PDT
TS163-4C	TSP163-4C	12	430	175	4PDT
TS163-4C	TSP163-4C	24	1800	175	4PDT
TS163-6C	TSP163-6C	12	350	250	6PDT
TS163-6C	TSP163-6C	24	1275	250	6PDT
TS163-8C	TSP163-8C	12	190	400	8PDT
TS163-8C	TSP163-8C	24	800	400	8PDT

Mfr. No.					
Solder Plug-In	PC Mount	Input (VDC)	Coil Resis (Ohms)	Power (mW)	Contacts
Ultra-Sensitive Bifurcated 2 Amp Contacts					
TSS163-2C	TSSP163-2C	24	7500	40	2PDT
TSS163-4C	TSSP163-4C	24	3700	80	4PDT

Mfr. No.					
Solder Plug-In	PC Mount	Input mADC	Coil Resis (Ohms)	Power (mW)	Contacts
Sensitive Single Point 2 Amp contacts					
TS154-2C	TSP154-2C	5.8	2500	85	2PDT
TS154-2C	TSP154-2C	4.1	5000	85	2PDT
TS154-4C	TSP154-4C	8.4	2500	175	4PDT
TS154-4C	TSP154-4C	6.2	5000	175	4PDT
TS154-6C	TSP154-6C	10.0	2500	250	4PDT
TS154-6C	TSP154-6C	7.1	5000	250	6PDT
TS154-8C	TSP154-8C	13.0	2500	400	8PDT
TS154-8C	TSP154-8C	9.0	5000	400	8PDT

Mfr. No.					
Solder Plug-In	PC Mount	Input VAC	Coil Resis (Ohms)	Power (VA)	Contacts
VOLTAGE ADJUSTED AC RELAYS					
Standard Single Point 2 Amp Contacts					
T154-2C	TP154-2C	115	6000	1.3	2PDT
T154-4C	TP154-4C	115	6000	1.3	4PDT
Standard Single Point 5 Amp Contacts					
TF154-2C	TFP154-2C	115	6000	1.3	2PDT
TF154-4C	TFP154-4C	115	6000	1.3	4PDT
Standard Bifurcated 2 Amp Contacts					
T163-2C	115	6000	1.3	2PDT
T163-4C	115	6000	1.3	4PDT