



L = 1-13/32  
W = 1-1/2  
H = 2-29/32  
Mounting Center = 2-1/2



Available upon request

**165F/166F SERIES**  
**FLANGE-MOUNTED VERSION OF 165/166 SERIES**

Stock No.	Series	Contacts		Coil		
		Arrang.	Rating (Amps)	Input Voltages	Resistance (Ohms)	Nominal Power
20546-82	166F	DPDT	13A	24VAC	72	2.2VA
20546-84	166F	DPDT	13A	120VAC	1,850	2.2VA
20547-82	166F	3PDT	13A	24VAC	72	2.2VA
20547-84	166F	3PDT	13A	120VAC	1,850	2.2VA



L = 1-7/8  
W = 1-5/8  
H = 1-1/4

JavaScript Picture  
R and CSA logos

High current relays for industrial control applications. Molded Class F encapsulated coil is resistant to fungus and moisture. Recognized under the Components Program of Underwriters Laboratories, Inc. (File No. E37066).

**177 SERIES**

Stock No.	Series	Contacts		Coil		
		Arrang.	Rating (Amps)	Input Voltages	Resistance (Ohms)	Nominal Power
20935-82	177	SPST	30A	24VAC	42	4.7VA
20935-83	177	NO-DM	30A	120VAC	1,100	4.7VA
20936-81	177	SPST	30A	12VDC	72	2W
20936-82	177	NO-DM	30A	24VDC	285	2W



L = 1-13/32  
W = 1-1/2  
H = 2-29/32  
Mounting Center = 2-1/2

JavaScript Picture  
R and CSA logos

General purpose relay with plastic cover. Molded Class F coil insures reliable continuous-duty performance. .250 quick connect terminals. Recognized under the Components Program of Underwriters Laboratories, Inc. (File No. E37066).

**267F SERIES**

Stock No.	Series	Contacts		Coil		
		Arrang.	Rating (Amps)	Input Voltages	Resistance (Ohms)	Nominal Power
20600-84	267F	SPDT	15A	120VAC	2,025	2.0VA
20601-82	267F	DPDT	15A	24VAC	80	2.2VA
20601-84	267F	DPDT	15A	120VAC	1,850	2.2VA
20606-81	267F	SPDT	15A	12VDC	120	1.2W
20606-82	267F	SPDT	15A	24VDC	480	1.2W
20607-81	267F	DPDT	15A	12VDC	120	1.2W
20607-82	267F	DPDT	15A	24VDC	480	1.2W



L = 1-13/32  
W = 1-1/2  
H = 2-3/16

JavaScript Picture  
R and CSA logos

Plastic covered general purpose plug-in relay. Molded class F coil. Continuous duty operation. .187 quick connect terminals. Recognized under the Components Program of Underwriters Laboratories, Inc. (File No. E37066). Also CSA recognized.

**268 SERIES**

Stock No.	Series	Contacts		Coil		
		Arrang.	Rating (Amps)	Input Voltages	Resistance (Ohms)	Nominal Power
20684-82	268	DPDT	15A	24VAC	72	2.2VA
20684-84	268	DPDT	15A	120VAC	1850	2.2VA
20686-82	268	DPDT	15A	24VDC	375	1.2W

ALL DIMENSIONS ARE NOMINAL.

