

SERIES 750
DPDT, 3PDT OCTAL STYLE POWER RELAY

RELAY PART NUMBERS

PART NUMBERS FOR DPDT

PART NUMBERS	Coil measured @ 25°C	
	Nominal Input Voltage	Nominal Resistance (Ohms)
AC COIL - 8 PIN OCTAL STYLE		
750XBXC4L-24A	24 VAC, 50/60 Hz	72
750XBXC4L-120A	120 VAC, 50/60 Hz	1,700
750XBXC4L-220/230A	220/230 VAC, 50 Hz	9,000
750XBXC4L-240A	240 VAC, 50/60 HZ	9,100
DC COIL - 8 PIN OCTAL STYLE		
750XBXC4L-110D	110 VDC	10,000
750XBXC4L-24D	24 VDC	470
750XBXC4L-12D	12 VDC	120

PART NUMBERS FOR 3PDT

PART NUMBERS	Coil measured @ 25°C	
	Nominal Input Voltage	Nominal Resistance (Ohms)
AC COIL - 11 PIN OCTAL STYLE		
750XCXC4L-24A	24 VAC, 50/60 Hz	72
750XCXC4L-120A	120 VAC, 50/60 Hz	1,700
750XCXC4L-220/230A	220/230 VAC, 50 Hz	9,000
750XCXC4L-240A	240 VAC, 50/60 HZ	9,100
DC COIL - 11 PIN OCTAL STYLE		
750XCXC4L-110D	110 VDC	10,000
750XCXC4L-24D	24 VDC	470
750XCXC4L-12D	12 VDC	120

STANDARD PART NUMBERS SHOWN ABOVE.

Magnecraft & Struthers-Dunn

ORDERING CODE 750

750 XBXC4L-120A

Series: Enclosed Power relay with flag indicator & I.D. tag.

Contact Arrangement: XB - (DPDT) 8 pin Base, XC - (3PDT) 11 pin Base


Standard Features: Push Button & Lock down door, L.E.D. Lamp Indicator

Coil Voltage: 6, 12, 24, 120, 220/230, 240 Add A for VAC Coils, 6, 12, 24, 48, 110 Add D for VDC Coils

Other coil voltages available on special order.


MATING SOCKETS

SOCKET PART NUMBERS LISTED BELOW.
 RATED: 15 AMPS, 300 VAC



70-464-1 8 PIN OCTAL SOCKET

SCREW TERMINAL SOCKETS,
 DIN RAIL/PANEL MOUNT



70-465-1 11 PIN SOCKET