

G2R

Power PCB Relay

7 RELAYS

Ordering Information

Part number	Rated voltage (V)	Coil res. (Ohms)	Power	Contact rating	Type
G2R-1-DC5	5 DC	47	530mW	10 A	SPDT
-DC6	6 DC	68		10 A	PCB
-DC12	12 DC	275		10 A	General
-DC24	24 DC	1,100		10 A	Purpose
-DC48	48 DC	4,170		10 A	Semi-Sealed
-AC24	24 AC	260	0.9 VA	10 A	
-AC120	120 AC	6,500		10 A	
-AC240	240 AC	30,000		10 A	
G2R-14-DC5	5 DC	47	530mW	10 A	SPDT
-DC6	6 DC	68		10 A	PCB
-DC9	9 DC	153		10 A	General
-DC12	12 DC	275		10 A	Purpose
-DC24	24 DC	1,100		10 A	Sealed
-DC48	48 DC	4,170		10 A	
-AC12	12 AC	65	0.9 VA	10 A	
-AC24	24 AC	260		10 A	
-AC120	120 AC	6,500		10 A	
-AC240	240 AC	30,000		10 A	
G2R-1-E-DC5	5 DC	47	530mW	16 A	SPDT
-DC12	12 DC	275		16 A	PCB
-DC24	24 DC	1,100		16 A	High-Capacity
-DC48	48 DC	4,170		16 A	Capacity
-AC24	24 AC	260	0.9 VA	16 A	Semi-Sealed
-AC120	120 AC	6,500		16 A	
G2R-14-H-DC5	5 DC	70	360mW	5 A	SPDT
-DC6	6 DC	100		5 A	PCB
-DC12	12 DC	400		5 A	High-Sensitivity
-DC24	24 DC	1,600		5 A	Sealed
G2R-1A-DC5	5 DC	47	530mW	10 A	SPST-NO
-DC6	6 DC	68		10 A	PCB
-DC12	12 DC	275		10 A	General
-DC24	24 DC	1,100		10 A	Purpose
G2R-1A4-DC5	5 DC	47	530mW	10 A	SPST-NO
-DC12	12 DC	275		10 A	PCB
-DC24	24 DC	1,100		10 A	General
-AC24	24 AC	260	0.9 VA	10 A	Purpose
-AC120	120 AC	6,500		10 A	Sealed
G2R-1A-E-DC5	5 DC	47	530mW	16 A	SPST-NO
-DC12	12 DC	275		16 A	PCB
-DC24	24 DC	1,100		16 A	High-Capacity
G2R-1-S-DC5	5 DC	47	530mW	10 A	SPDT
-DC6	6 DC	68		10 A	Plug-in
-DC12	12 DC	275		10 A	General
-DC24	24 DC	1,100		10 A	Purpose
-AC12	12 AC	65		10 A	Unsealed
-AC24	24 AC	260	0.9 VA	10 A	
-AC120	120 AC	6,500		10 A	

Note: 1. Other coil voltages available.

Part number	Rated voltage (V)	Coil res. (Ohms)	Power	Contact rating	Type
G2R-1-T-DC5	5 DC	47	530mW	10 A	SPDT
-DC12	12 DC	275		10 A	Quick
-DC24	24 DC	1,100		10 A	Connect
-AC24	24 AC	260	0.9 VA	10 A	Upper
-AC120	120 AC	6,500		10 A	Mounting Bracket Unsealed
G2R-2-DC5	5 DC	47	530mW	5 A	DPDT
-DC12	12 DC	275		5 A	PCB
-DC24	24 DC	1,100		5 A	General
-AC24	24 AC	260	0.9 VA	5 A	Purpose
-AC120	120 AC	6,500		5 A	Semi-Sealed
G2R-24-DC5	5 DC	47	530mW	5 A	DPDT
-DC6	6 DC	68		5 A	PCB
-DC12	12 DC	275		5 A	General
-DC24	24 DC	1,100		5 A	Purpose
-DC48	48 DC	4,170		5 A	Sealed
-AC24	24 AC	260	0.9 VA	5 A	
-AC120	120 AC	6,500		5 A	
G2R-24-H-DC5	5 DC	70	360mW	3 A	DPDT
-DC6	6 DC	100		3 A	PCB
-DC12	12 DC	400		3 A	High-Sensitivity
-DC24	24 DC	1,600		3 A	Sealed
G2R-2A4-DC5	5 DC	47	530mW	5 A	DPST-NO
-DC12	12 DC	275		5 A	PCB
-DC24	24 DC	1,100		5 A	General
-AC24	24 AC	260	0.9 VA	5 A	Purpose
-AC120	120 AC	6,500		5 A	Sealed
G2R-2-S-DC5	5 DC	47	530mW	5 A	DPDT
-DC12	12 DC	275		5 A	Plug-in
-DC24	24 DC	1,100		5 A	General
-AC24	24 AC	260	0.9 VA	5 A	Purpose
-AC120	120 AC	6,500		5 A	Unsealed
G2RK-1-DC5	5 DC	47	850mW (Set)	5 A	SPDT
-DC12	12 DC	275		5 A	PCB
-DC24	24 DC	1,100	600mW (Reset)	5 A	Dual Coil Latching Semi-Sealed
G2RK-2-DC5	5 DC	47	850mW (Set)	3 A	DPDT
-DC12	12 DC	275		3 A	PCB
-DC24	24 DC	1,100	600mW (Reset)	3 A	Dual Coil Latching Semi-Sealed