


P25 with DC coil



P25 with AC coil

P25 series

**DEFINITE PURPOSE
MAGNETIC CONTACTOR
25 AMPERE FULL LOAD
30 AMPERE RESISTIVE
AC & DC COILS**

- File E22575
- File LR15734
- No. R 97069

FEATURES

- AC and DC coils.
- For controlling motors, power supplies, heating elements and lighting.
- Dust cover available.
- Auxiliary switch available.

CONTACT DATA @ 25 C

Arrangements: Up to 3 Form X (3PST-NO-DM).
Ratings: See contact rating table.
Material: Silver-cadmium oxide.
Expected Life: 500,000 operations at full load.
AC coil: 2 million operations, mechanical.
DC coil: 5 million operations, mechanical.
Minimum Contact Load: 3A @ 120VAC.

MAIN CONTACT RATINGS @ +25°C, 60 HZ.

Type	Motor Rating in Amps, 3Ø3P or 1Ø2P				Resistive Rating (Electric Heat) @ 600V
	Full Load @ 600V	Locked Rotor			
		@ 240V	@ 480V	@ 600V	
P25	25A	150A	125A	100A	30A

Type	Motor Rating in Horsepower		
	@ 120V	@ 240V	@ 440-600V
1Ø2P 3Ø3P	1.5HP 3HP	3HP 7.5HP	— 10HP

Notes: Models utilizing box lug terminals are restricted to the following ratings: 25 FLA, 150 LRA @ 250VAC; 30A @ 277VAC Resistive; Horsepower ratings shown in the table are valid up to 240VAC.
Tungsten Lamp Rating: 30A, 277VAC.
Electric Discharge Lamp Rating: 30A, 277VAC.
Heavy Duty Pilot Ratings @ 120V through 600V, 720VA max.
 (Box lug nut units limited to 277VAC.)

AUXILIARY SNAP-ACTION SWITCH

Arrangements: Up to 2 Form C (DPDT).
Rating: 10 amps at 120VAC, 60 Hz. @ 25°C.
Material: Silver.

INITIAL DIELECTRIC STRENGTH

Initial Breakdown Voltage: 2,200V rms. minimum between all elements and between all elements and ground.

COIL DATA @ 25 C

Voltage: From 6 to 240VDC and 24 to 600VAC, 50/60 Hz.
Power: DC, 4-8W; AC, 40VA inrush; 10VA, sealed.
Duty Cycle: Continuous.
Insulation Class: Class A, standard. Class B available.
Initial Insulation Resistance: 100 megohms, minimum.

COIL DATA

Nominal VDC	Resistance (Ohms ± 10% @ 25°C)	Must Operate* Volts	Maximum Operating Volts	Nominal Coil Current (ma) @ Nominal Voltage
12	34	9	15	353
24	133	18	30	180

AC Voltage Rating	Nominal		Must Operate	
	60 Hz.	50 Hz.	60 Hz.	50 Hz.
24	24	24	20.4	20.4
120	120	110	102	94
240	208/240	208/220	177	177

*Must operate is 75% of nominal voltage for any mounting position, applicable for vertical or horizontal mounting, but not for upside-down mounting.
 **Units requiring less power can be provided for some applications.

Note: Coil suppression is recommended for all DC coil units, particularly 120 and 240VDC coils.

OPERATE DATA @ 25 C

Must-Operate Voltage: See coil data tables.

ENVIRONMENTAL DATA

Temperature Range: **AC:** -55°C to +65°C
DC: -55°C to +55°C
 Contact sales representative for higher temperature ratings.

MECHANICAL DATA

Mounting: No. 10 screws on 2.125" (53.98 mm) centers or universal mounting bracket.

Termination:

- Contacts:** 8-32 screw for No. 16 to No. 8 wire, dual .250" (6.35 mm) quick connect, box lug or captive pressure plate.
- Coil:** Combination 8-32 screw and .250" (6.35 mm) or .187" (4.75 mm) quick connect, combination captive pressure plate and .250" (6.35 mm) quick connect, or .250" (6.35 mm) quick connect.
- Aux. Switch:** .250" (6.35 mm) quick connect, .187" (4.75 mm) quick connect.

Weight: 14 oz. (397 g).