

UWZ Series AC VOLTAGE

For within panels or indoor mounting—non-resetable

All models are light grey color with white numerals on black background. Tenths and hundredths numerals are yellow. An orange dial adjacent to the hundredths digit provides running indication.

UL FILE:E86119

CSA FILE:LR44080



UWZ 48E Flush Mount



- Bezel:1.89" x 1.89" (48 x 48mm)
 - Capacity:99,999.99 hours
 - Mounting:Flush
 - Digits:7 – 0.16"high numerals
 - Voltage:24, 120, 240, 50 or 60Hz
 - Power Consumption:1VA
 - Temperature:–40° to 160°F (–40° to 72°C)
 - Termination:Combination 1/4"spade and screw clamp
 - Weight:2.1oz.
- Flush mounted with bracket.The UWZ 48E unit fits into a 1.79 x 1.79in.(45.5 x 45.5mm) cut-out.The thickness of the panel for flush mounting can be up to 0.35in.(9mm).The unit is secured in position by a plastic slip-on retaining bracket.Also fits square or round openings for 72mm meters with optional 72mm bezel.

Ord. Info.: UWZ 48E – voltage/freq.

UWZ 48 Surface Mount



- Bezel:1.89" x 1.89" (48 x 48mm)
- Capacity:99,999.99 hours
- Mounting:Surface
- Digits:7 – 0.16" high numerals
- Voltage: 24, 120, 240, 50 or 60Hz
- Power Consumption:1VA
- Temperature:–40° to 160°F (–40° to 72°C)
- Termination:Screw Lugs
- Weight:2.5oz.

Surface mounted type. The UWZ 48 unit with plug-in base where terminal protection is not necessary.The socket base is easy to install and connect.The meter is simply plugged into the base and secured by one screw.

Ord. Info.: UWZ 48 – voltage/freq.

UWZ 48A Enclosed Surface Mount



- Bezel:1.89" x 1.89" (48 x 48mm)
- Capacity: 99,999.99 hours
- Mounting:Surface
- Digits:7 – 0.16" high numerals
- Voltage:24, 120, 240, 50 or 60Hz
- Power Consumption: 1VA
- Temperature:–40° to 160°F (–40° to 72°C)
- Termination:Screw Lugs
- Weight: 2.5oz.

Wall mounted type.Used in conjunction with a terminal cover for added safety, the UWZ 48A is surface mounted. Installation merely requires fixing the base to wall or panel with two screws, wiring the base, and plugging in the meter with the terminal cover.

Ord. Info.: UWZ 48A – voltage/freq.

UWZ 48V DIN Rail Mount



- Bezel:1.89" x 1.89" (48 x 48mm)
 - Capacity:99,999.99 hours
 - Mounting:DIN Rail
 - Digits:7 – 0.16"high numerals
 - Voltage:24, 120, 240, 50 or 60Hz
 - Power Consumption:1VA
 - Temperature:–40° to 160°F (–40° to 72°C)
 - Termination:Combination 1/4"spade and screw clamp
 - Weight:2.5oz.
- DIN rail mounting.A special snap-on socket base enables the unit to be quickly and simply fitted on DIN rail.

Ord.Info.: UWZ 48V – voltage/freq.

UWZ 52E Flush Mount



- Bezel:2.28" round (58mm)
 - Capacity:99,999.99 hours
 - Mounting:Flush
 - Digits:7 – 0.16"high numerals
 - Voltage:24, 120, 240, 50 or 60Hz
 - Power Consumption:1VA
 - Temperature:–40° to 160°F (–40° to 72°C)
 - Termination:Combination 1/4" spade and screw clamp
 - Weight: 2.1oz.
- Flush mounted with bracket.The UWZ 52E with round face is fastened with a plastic slip-on retaining bracket. For larger cutouts up to a 60mm diameter, a slip-on 65mm ø bezel is available.

Ord.Info.: UWZ 52E – voltage/freq.

10 TIMERS & FLASHERS