

PLC

Micro³ and Micro³C

Part Numbers: Micro³C

Item	Part No.	Description	
AC Power (100 to 240V AC, 50/60Hz power supply)	FC2A-C24A1C	Base units: Input (24V DC sink/source) Relay output (240V AC/30V DC, 2A)	24 I/O (14 in, 10 out)
	FC2A-C16A1C		16 I/O (9 in, 7 out)
DC Power (24V DC, 19 to 30V DC)	FC2A-C24A4C		24 I/O (14 in, 10 out)
	FC2A-C16A4C		16 I/O (9 in, 7 out)
Program Loader	FC2A-HL1EC	Version 2.0+; also compatible with Micro ³ C	

Optional Item	Part No.	Description
Loader Cable (2m)	FC2A-KL3C	Connects basic unit (loader port) and program loader
Loader Cable (2m)	FC2A-KL4C	Connects basic unit (data link terminal) and program loader
Modem Cable (3m)	FC2A-KM1C	Connects basic unit (loader port) and modem (1:1 communications)
PC Interface Cable (3m)	FC2A-KC4C	Connects basic unit (loader port) and PC (1:1 communications)
PC Interface Cable (2m)	FC2A-KC6C	Connects basic unit (data link terminal) and PC (1:1 communications)
User Communication Cable (2.4m)	FC2A-KP1C	Connects basic unit (loader port) and user's equipment
PC Connect Cable (5m)	HG9Z-XC183	Connects basic unit (loader port) and Micro Q/I™
Memory Card (RAM)	FC2A-MC1	Memory to store user's programs (64K)
AC Adaptor	PSR-GA05005	Connects basic unit (data link terminal) and program loader/PC
Expansion Cable (25cm)	FC2A-KE1	Connects basic unit and expansion function unit
1:N Link Adaptor	FC2A- MD1	Connects basic unit (data link terminal) and PC
RS232C Cable (4 lines, 1.5m)	HD9Z-C52	Connects link adaptor and PC (1:N communications), D-sub 9-pin
WindLDR™, Version 1.0	WINDLDR	Windows-based application software, performs ladder programming and monitors IDEC's Micro-1, Micro ³ , and Micro ³ C PLCs
CUBIQ, Version 2.0	FC9Y-LP1E314	DOS-based application software, performs ladder programming and monitoring; also compatible with the Micro ³