

## THIN WALL HEAT SHRINK TUBING



# 22

Panduit Heat Shrink Tubing provides an economical and easy way to insulate, protect, harness and identify electrical and electronic components. 8 colors available. **Material:** Cross-linked polyolefin. **Voltage Rating:** 600V. MIL-I-23053/5 Class 1, Class 2(clear).

VW-1 flame rating and surface marked per UL/CSA requirements. **Material:** Cross-linked polyolefin. **Voltage Rating:** 600V. MIL-I-23053/5 Class 3.

Mfr. No.*	Minimum Expanded I.D. (In.)	Maximum Recovered I.D. (In.)	Length (Ft.)	Std. Pkg. Qty.
<b>TYPE HSTT—4 Ft. Lengths</b>				
HSTT05-48-Q	.046	.023	4	25
HSTT06-48-Q	.063	.031	4	25
HSTT09-48-Q	.093	.046	4	25
HSTT12-48-Q	.125	.062	4	25
HSTT19-48-Q	.187	.093	4	25
HSTT25-48-Q	.250	.125	4	25
HSTT38-48-Q	.375	.187	4	25
HSTT50-48-5	.500	.250	4	5
HSTT75-48-5	.750	.375	4	5
HSTT100-48-5	1.000	.500	4	5
HSTT150-48-5	1.500	.750	4	5
HSTT200-48-5	2.000	1.000	4	5
HSTT300-48-2	3.000	1.500	4	2
HSTT400-48-2	4.000	2.000	4	2

Mfr. No.*	Minimum Expanded I.D. (In.)	Maximum Recovered I.D. (In.)	Length (Ft.)	Std. Pkg. Qty.
<b>TYPE HSTTV—4 Ft. Lengths, VW-1 RATED, SURFACE MARKED</b>				
HSTTV05-48-Q	.046	.023	4	25
HSTTV06-48-Q	.063	.031	4	25
HSTTV09-48-Q	.093	.046	4	25
HSTTV12-48-Q	.125	.062	4	25
HSTTV19-48-Q	.187	.093	4	25
HSTTV25-48-Q	.250	.125	4	25
HSTTV38-48-Q	.375	.187	4	25
HSTTV50-48-5	.500	.250	4	5
HSTTV75-48-5	.750	.375	4	5
HSTTV100-48-5	1.000	.500	4	5

Mfr. No.*	Minimum Expanded I.D. (In.)	Maximum Recovered I.D. (In.)	Length (Ft.)	Std. Pkg. Qty.
<b>TYPE HSTT—ON REELS</b>				
HSTT05-M	.046	.023	1000	1
HSTT06-M	.063	.031	1000	1
HSTT09-M	.093	.046	1000	1
HSTT12-M	.125	.062	1000	1
HSTT19-M	.187	.093	1000	1
HSTT25-D	.250	.125	500	1
HSTT38-T	.375	.187	200	1
HSTT50-T	.500	.250	200	1
HSTT75-T	.750	.375	200	1
HSTT100-C	1.000	.500	100	1
HSTT150-C	1.500	.750	100	1
HSTT200-L	2.000	1.000	50	1
HSTT300-L	3.000	1.500	50	1
HSTT400-L	4.000	2.000	50	1

Mfr. No.*	Minimum Expanded I.D. (In.)	Maximum Recovered I.D. (In.)	Length (Ft.)	Std. Pkg. Qty.
<b>TYPE HSTTV—ON REELS, VW-1 RATED, SURFACE MARKED</b>				
HSTTV05-M	.046	.023	1000	2
HSTTV06-M	.063	.031	1000	2
HSTTV09-M	.093	.046	1000	2
HSTTV12-M	.125	.062	1000	2
HSTTV19-M	.187	.093	1000	2
HSTTV25-D	.250	.125	500	2
HSTTV38-T	.375	.187	200	2
HSTTV50-T	.500	.250	200	2
HSTTV75-T	.750	.375	200	2
HSTTV100-C	1.000	.500	100	2

WIRES & ACC

\*Part Numbers indicate black tubing. Add color code as necessary:

**Example:**  
HSTT25-48-Q (P/N for Black Tubing)  
HSTT25-48-QC (P/N for Clear Tubing)  
HSTT50-48-5-2 (P/N for Red Tubing)

**Color Codes:**  
Red=2 Blue=6  
Yellow=4 White=10  
Green=5 Clear=C  
Yellow/green=45

### HEAT TOOLS



Mfr. No.	Description	Pkg. Qty.
HSG-115V-300	Heat tool, 300F-450F, 8 amps	1
HSG-115V-500	Heat tool, 500F-650F, 11 amps	1
HSG-115V-650	Heat tool, 650F-900F, 14.3 amps	1

### ACCESSORIES

Mfr. No.	Description	Pkg. Qty.
HSG-A1	Heat reflector For tubing 3/4" & smaller	1
HSG-A2	Heat reflector For tubing 1/2" & smaller	1
HSG-A3	Heat concentrator	1
HSG-A4	Heat tool case	1