

THIN WALL HEAT SHRINK TUBING

Material: Teflon (TFE) MIL-I-23053/12, Class 3 & Class 5, 600V rating.

Mfr. No.	Maximum Recovered I.D. (In.)	Minimum Expanded I.D. (In.)	Std. Pkg. Qty.
TYPE HSTTT — 4' Lengths, MIL-I-23053/12 CLASS 3			
HSTTT03-48-Q	.015	.034	25
HSTTT04-48-Q	.018	.038	25
HSTTT046-48-Q	.022	.046	25
HSTTT05-48-Q	.027	.050	25
HSTTT055-48-Q	.032	.055	25
HSTTT06-48-Q	.039	.060	25
HSTTT08-48-Q	.049	.075	25
HSTTT09-48-Q	.061	.093	25
HSTTT12-48-Q	.072	.120	25
HSTTT15-48-Q	.089	.150	25
HSTTT19-48-Q	.112	.191	25
HSTTT24-48-Q	.141	.240	25
HSTTT30-48-Q	.178	.302	25
HSTTT37-48-Q	.224	.370	25
HSTTT43-48-Q	.278	.430	25
HSTTT47-48-Q	.347	.470	25
HSTTT56-48-5	.399	.560	5
HSTTT66-48-5	.462	.655	5
HSTTT75-48-5	.524	.750	5
HSTTT93-48-5	.655	.930	5
HSTTT112-48-5	.786	1.120	5
HSTTT131-48-2	.911	1.310	2
HSTTT150-48-2	1.036	1.500	2
HIGH SHRINK RATIO 4:1 CLASS 5			
HSTTT4X08-48-Q	.025	.078	25
HSTTT4X12-48-Q	.037	.125	25
HSTTT4X25-48-Q	.063	.250	25
HSTTT4X38-48-Q	.096	.375	25
HSTTT4X50-48-5	.144	.500	5
HSTTT4X63-48-5	.178	.625	5
HSTTT4X75-48-5	.224	.750	5
HSTTT4X88-48-5	.244	.875	5
HSTTT4X100-48-5	.278	1.000	5
HSTTT4X125-48-5	.347	1.250	5
TYPE HSTTF — 4' Lengths, MIL-I-23053/11			
Material: Teflon (FEP) MIL-I-23053/11, Class 1, 600V rating			
HSTTF03-48-Q	.027	.031	25
HSTTF04-48-Q	.032	.036	25
HSTTF05-48-Q	.039	.045	25
HSTTF06-48-Q	.049	.060	25
HSTTF08-48-Q	.061	.075	25
HSTTF09-48-Q	.072	.092	25
HSTTF12-48-Q	.089	.115	25
HSTTF14-48-Q	.114	.141	25
HSTTF16-48-Q	.124	.158	25
HSTTF18-48-Q	.143	.180	25
HSTTF20-48-Q	.158	.197	25
HSTTF23-48-Q	.180	.225	25
HSTTF25-48-Q	.198	.248	25
HSTTF29-48-Q	.226	.290	25
HSTTF31-48-Q	.249	.310	25
HSTTF36-48-Q	.280	.365	25
HSTTF40-48-Q	.311	.400	25
HSTTF44-48-Q	.349	.440	25
HSTTF50-48-5	.383	.500	5
HSTTF66-48-5	.510	.666	5
HSTTF100-48-5	.764	1.000	5
HSTTF133-48-2	1.020	1.330	2
HSTTF200-48-2	1.520	2.000	2