

REFK SERIES ECONOMY KNOCKDOWN RACK



- Standard 19"panel width (22" overall)
- 24"usable depth (24.5" overall)
- Includes 4 infinitely adjustable combination rack mount rails with full EIA spacing, 4 leveling feet and #10-32 clip nuts for rails
- Shipped in a flat pack container
- Simple assembly with one bolt in each corner to lock sides to the top and bottom
- Heavy-duty 16 gauge steel top, bottom and
- 14 gauge black steel rails
- Finished in a rugged textured enamel
- 2 horizontal rail supports per side on units 42"or higher

Mfr. No.		Dimensions (In.)		
Black	Grey	Height	Width	Depth
REFK1903524BK1	REFK1903524CG1	35	19	24
REFK1904224BK1	REFK1904224CG1	42	19	24
REFK1904924BK1	REFK1904924CG1	49	19	24
REFK1905624BK1	REFK1905624CG1	56	19	24
REFK1906324BK1	REFK1906324CG1	63	19	24
REFK1907024BK1	REFK1907024CG1	70	19	24
REFK1907724BK1	REFK1907724CG1	77	19	24

RSDF SERIES FLUSH SOLID DOOR



- Features lockable latch, magnetic catch, and spring-loaded hinge pins for easy installation
- Opens either left or right by inverting
- Allows full access to space between panel
- Mounts within the panel space flush with the rack frame

Mfr. No.		Dimensions (In.)	
Black	Grey	Height	Width
RSDF19035BK1	RSDF19035CG1	35	19
RSDF19042BK1	RSDF19042CG1	42	19
RSDF19049BK1	RSDF19049CG1	49	19
RSDF19056BK1	RSDF19056CG1	56	19
RSDF19063BK1	RSDF19063CG1	63	19
RSDF19070BK1	RSDF19070CG1	70	19
RSDF19077BK1	RSDF19077CG1	77	19

RSDL SERIES FLUSH LOUVERED DOOR



- Features lockable latch, magnetic catch, and spring-loaded hinge pins for easy installation
- Opens right hand only with louvers facing down
- Allows full access to space between panel
- Mounts within the panel space flush with the rack frame

Mfr. No.		Dimensi	ons (ln.)
Black	Grey	Height	Width
RSDL19035BK1	RSDL19035CG1	35	19
RSDL19042BK1	RSDL19042CG1	42	19
RSDL19049BK1	RSDL19049CG1	49	19
RSDL19056BK1	RSDL19056CG1	56	19
RSDL19063BK1	RSDL19063CG1	63	19
RSDL19070BK1	RSDL19070CG1	70	19
RSDL19077BK1	RSDL19077CG1	77	19

CONTEMPRA 2 SERIES RACK



- Standard 19"panel width (22" overall)
- Comes pre-assembled with the following components and hardware:
 - 1 Contempra 2 frame
 - 1 pair of side panels
 - 1 solid door
 - 1 solid top
 - 4 full length, black, punched combination rails
 - 4 adjustable levelling feet
 - type 10-32 clip nuts

Mfr. No.		Dimensions (In)		
Black	Grey	Height	Width	Depth
C2RR194223BK1	C2RR194223CG1	42	19	24
C2RR194231BK1	C2RR194231CG1	42	19	31.5
C2RR196323BK1	C2RR196323CG1	63	19	24
C2RR196331BK1	C2RR196331CG1	63	19	31.5
C2RR197023BK1	C2RR197023CG1	70	19	24
C2RR197031BK1	C2RR197031CG1	70	19	31.5
C2RR197823BK1	C2RR197823CG1	78	19	24
C2RR197831BK1	C2RR197831CG1	78	19	31.5

CDF SERIES FLUSH LOUVERED DOOR



- Constructed of 16 gauge steel
- Fits either front or back of frame
- Quick release hinge design allows for easy installation adn removal.
- Features lockablr batch

Mfr. No.		Dimensions (In.)	
Black	Grey	Height	Width
CDF1942LBK1	CDF1942LCG1	42	19
CDF1963LBK1	CDF1963LCG1	63	19
CDF1970LBK1	CDF1970LCG1	70	19
CDF1978LBK1	CDF1978LCG1	78	19

LIGHT DUTY RELAY RACK HEAVY DUTY RELAY RACK





- Provides complete access ro equipment
- An econimical option to an enclosed rack
- -Welded construction, painted black
- Engineered for use as a solid, single, free-standing unit
- The light-duty rack is constructed of 12 gauge steel
 The heavy-duty rack is constructed of 10 gauge steel
 EIA spacing (0.5"-1.25"0 is standard on front flange only
- Holes are drilled and tapped 10-32

Mfr. No.		Dimensions (In.)	
Light Duty	Heavy Duty	Height	Width
DNRR42LDW	DNRR42HDW	42	19
DNRR63LDW	DNRR63HDW	63	19
DNRR70LDW	DNRR70HDW	70	19
DNRR77LDW	DNRR77HDW	77	19
DNRR84LDW	DNRR84HDW	84	19

