



SPD200K AND SPD300K SERIES

The SPD200K and SPD300K Series offers continuous protection from damaging voltage transients and electrical noise commonly found at the service entrance or distribution panel. The design allows for installation flexibility and the robust design allows for installation in the most severe exposure locations. They are capable of handling the high-impulse, potentially damaging transients commonly found at the service entrance or distribution panels.

APPLICATIONS

The SPD200K and SPD300K Series can be a facility-wide product family and may be installed from service entrances to distribution panels to branch panels.

- Industrial Plants
- Commercial Buildings
- Institutional Facilities
- Any facility that has an environment with electronics based equipment


FEATURES

- Surge current capacity of 200 to 300 kA per phase
- Metal, UL Listed /NEMA type 1/12/3R/4 enclosure standard
- Rotary disconnect and transient counter
- All modes transient protection (L-N, L-G, and N-G)
- Form C dry contacts and audible alarm status indications
- Internal/external monitoring, including neutral to ground
- EMI/RFI Filtering
- Ten year limited warranty

SPECIFICATIONS

Catalog Number	Dimensions D x W x H mm (in.)	Suggested Breaker Size	Suggested Wire Size (AWG)	Weight lbs (kg)	Allowable Breaker Range	Allowable Wire Range
SPD200K	152.4 x 304.8 x 304.8 (6.0 x 12.0 x 12.0)	40 A	#8	23 (10.4)	40–100 A	#8–1/0
SPD300K	152.4 x 304.8 x 304.8 (6.0 x 12.0 x 12.0)	40 A	#8	24 (11.79)	40–100 A	#8–1/0

CERTIFICATIONS AND COMPLIANCES

-  Listed
 - UL 1449, Type 1 locations
 - UL rated 200 kA with component level fusing for safe operations
 - UL Listed/NEMA 4 enclosure standard
- ANSI/IEEE C62.11, C62.41, C62.45
Categories A, B, and C3 tested
- Tested to Third Party Witness Tested (former NEMALS1), ISO 9001

RELATED PRODUCTS

- Power Conditioners
- Uninterruptible Power System
- Transformers
- STV25K, STV100K, STFV and STC Series

SOLAHD For product information:
www.solahd.com
1.800.377.4384



CONSIDER IT SOLVED™

SPD200K SPECIFICATIONS

Catalog Number	SPD200K10YRC	SPD200K24DRC	SPD200K27YRC	SPD200K48DRC	SPD200K34YRC	SPD200K60DRC
Input Voltage	208Y/120 V	240D V	480Y/277 V	480D V	600Y/347 V	600D V
	3Ph Wye, 4 W + G	3Ph Delta, 3 W + G and HRG Wye	3Ph Wye, 4 W + G	3Ph Delta, 3 W + G and HRG Wye	3Ph Wye, 4 W + G	3Ph Delta, 3 W + G and HRG Wye
Maximum Continuous Operating Voltage (MCOV)	125% of the nominal level for 120 V; 115% for all other voltages					
Line Frequency	47–63 Hz					
Response Time	< 0.5 nanoseconds					
Enclosure	Metal, UL Listed /NEMA type 1/12/3R/4 standard					
Mounting Type	Wall Mounted (mounting hardware ¼ in.)					
Connection	Internal Rotary Disconnect					
Status Indication	Red and green LED status indicators, audible alarm, summary alarm contacts, counter					
Operating Temperature	-40 °C to +60 °C (-40 °F to +140 °F)					
Operating Humidity	0% to 95% non-condensing					
Noise Attenuation	50 dB from 10 kHz to 100 MHz					
Modes of Protection	All Modes: L–N, L–L, L–G, N–G ①					
SCCR Rating	200 kAIC					
Nominal Discharge Current Rating (In)	20 kA					
Warranty	10 year limited warranty					

SPD300K SPECIFICATIONS

Catalog Number	SPD300K10YRC	SPD300K24DRC	SPD300K27YRC	SPD300K48DRC	SPD300K34YRC
Input Voltage	120/208 V	240D V	480Y/277 V	480D V	600Y/347 V
	3Ph Wye, 4 W + G	3Ph Delta, 3 W + G and HRG Wye	3Ph Wye, 4 W + G	3Ph Delta, 3 W + G and HRG Wye	3Ph Wye, 4 W + G
Maximum Continuous Operating Voltage (MCOV)	125% of the nominal level for 120 V; 115% for all other voltages				
Line Frequency	47–63 Hz				
Response Time	< 0.5 nanoseconds				
Enclosure	Metal, UL Listed /NEMA type 1/12/3R/4 standard				
Mounting Type	Wall Mounted (mounting hardware ¼ in.)				
Connection	Internal Rotary Disconnect				
Status Indication	Red and green LED status indicators, audible alarm, summary alarm contacts, counter				
Operating Temperature	-40 °C to +60 °C (-40 °F to +140 °F)				
Operating Humidity	0% to 95% non-condensing				
Noise Attenuation	-50 dB from 10 kHz to 100 MHz				
Modes of Protection	All Modes: L–N, L–L, L–G, N–G ①				
SCCR Rating	200 kAIC				
Nominal Discharge Current Rating (In)	20 kA				
Warranty	10 year limited warranty				

① Delta Model does not offer L-N or N–G mode of protection.

SOLAHD

United States: 1.800.377.4384 | Asia/Pacific: + 65.6891.7600 | Australia: + 61.3.9721.0387
 Brazil: São Paulo/SP + 55.11.2122.5777 | Brazil: Camaçari/BA + 55.71.3496.4427 | Canada: + 1.888.765.2226
 China: + 86.21.3418.3888 | Europe: + 33.3.2254.1390 | Mexico/Latin America: + 52.55.5809.5049
 Middle East/Africa/India: + 971.4.811.8100
www.solahd.com


EMERSON