

microSD[™] Memory Card Connector



SCHA9B Series

The industry's thinnest* product height when installed (0.69mm)



Features

- Covering the top and bottom of the connector with a metal frame enables a structure resilient to scooping
- The detector switch employs a sliding contact structure resilient to foreign matter
- Hard lock structure makes it harder to remove a locked-in card
- Terminals face in the direction of card insertion, preventing terminal buckling

Applications


- Smartphones, other mobile devices and tablets
- Digital cameras and camcorders


*Alps Electric research as of July 2014

Typical Specifications	
Dimensions	14.97 imes 15.37mm (Installed height: 0.69 mm)
Media eject method	Push-push
Mount type	Surface mount
Mount system	Standard mount (PC Board cut-off type)
Card eject stroke	3.2 mm
Stand-off	- 0.7mm
No. of insertion and removal cycles	10,000 cycles

Dimensions

Unit:mm





Precautions when handling our products

- For the export of products which are controlled items subject to foreign and domestic export laws and regulations, you must obtain approval and/or follow the formalities of such laws and regulations.
 Products must not be used for military and/or antisocial purposes such as terrorism, and shall not be supplied to any party intending to use the

- Products must not be used for military and/or antisocial purposes such as terrorism, and shall not be supplied to any party intending to use the products for such purposes.
 Unless provided for otherwise, the products have been designed and manufactured for application in equipment and devices which are sold to end users in the market, including audio-visual (AV) equipment, electrical home appliances, office machines, information and communication equipment, and amusement equipment. The products are not intended for use in, and must not be used for, any application for nuclear equipment, driving equipment for aerospace or any other unauthorized use.
 With the exception of the abovementioned prohibited applications, please contact an Alps sales representative and/or evaluate the total system regarding applicability for applications involving high levels of safety and liability such as medical equipment, burglar alarm equipment, disaster prevention equipment and undersea equipment. Please also incorporate fail-safe design, protection and redundant circuitry, malfunction protection, and/or fire protection into the complete system to ensure safety and reliability of the total system.
 Before using products which were not specifically designed for use in automotive applications, please contact an Alps sales representative.

Cautions for using this catalog

- The specifications herein are an overview of the specifications. Obtain official specifications before use

- 1. The specifications better a an overview of the specifications. Obtain bifurcian specifications better before use.
 2. The colors of the products in the catalog may slightly differ from those of the actual products.
 3. The external appearance, functions and other specifications herein may be discontinued without prior notice.
 4. All product names, company names and names of standards described in this catalog are trademarks or registered trademarks of their respective owners.
 5. The contents of this catalog are according to Alps Electric as of July 2014.
 6. This catalog is valid until December 31, 2014.

Inquiries about this product

Product Information Center +81 (3) 5499-8154 **Product Information URL** http://www.alps.com/products/e/

ALPS ELECTRIC CO., LTD. 1-7,Yukigaya-otsukamachi,Ota-ku,Tokyo,145-8501,Japan