

# Emergency stop button

## Electrical characteristics

<b>Nominal thermal current</b>	■ I <sub>th</sub> = 10A				
<b>Breaking capacity</b>	■ AC - 15	U <sub>e</sub> (V)	240V	600V	
		I <sub>e</sub> (A)	3	1,2	
	DC - 13	U <sub>e</sub> (V)	24V	125V	250V
		I <sub>e</sub> (A)		0,55	0,27
<b>Electrical durability</b>	■ Used for 1 million of operations				
	AC - 15	U <sub>e</sub> (V)	24V	120V	230V
		I <sub>e</sub> (A)	4	3	2
	DC - 13	U <sub>e</sub> (V)	24V	110V	
		I <sub>e</sub> (A)	0,5	0,2	
	<b>Rated insulation voltage</b>	■ Pollution degree 3, UI = 600V according to IEC 60947 - 1			

## Other characteristics

<b>Certification</b>	■ UL listed, CSA - IEC 947-5-1- for YSK 2238 B1: EN 418 et EN 81
<b>Mechanical life expectancy</b>	■ 5 x 10 <sup>6</sup> actions
<b>Operating T°</b>	■ -25 à + 70°C
<b>Storage T°</b>	■ -40 à + 70°C
<b>Protection</b>	■ Tropicalization (use at +40°C with 95% of humidity)

## Complete devices

Designation	Partnumber	
Push/ pull button YSK 2308 with bracket, contacts 1 NO + 1 NC and ø 40 mm label	<b>YSK 2303</b>	
Push/ pull button YSK 2308 with bracket, with contacts 1 NO + 2 NC and ø 90 mm label	<b>YSK 2304</b>	
Push/ pull button YSK 2308 with bracket, with contacts 1 NO + 2 NC and box YSK 1513	<b>YSU 1514</b>	
Push/ pull button YSK 2238 B21 + bracket with contacts 1 NO + 1 NC and module LED 24V AC / DC and box YSK 1513	<b>YSU 1515</b>	
Bracket and contacts 1 NO + 1 NC	<b>YSK 2313</b>	

# Emergency stop button

## ■ Spare parts

Designation	Partnumber	
Push/ pull operator $\varnothing$ 40 mm	YSK 2308	
Push/ turn operator $\varnothing$ 40 mm	YSK 2309	
Push/ pull operator $\varnothing$ 40 mm with lighting and mechanical view	YSK 2238 B21	
Momentary mushroom black operator $\varnothing$ 60 mm	YSK 2310	
Contact NC with positive action	YSK 2305	
Contact NO	YSK 2306	
Illuminated element bright LED 24V AC / DC	YSK 2311	
Illuminated element bright LED 230V A/C	YSK 2312	
Bracket	YSK 2307	
$\varnothing$ 60 mm label. Boring $\varnothing$ 22 mm	PXK 567 A4	
$\varnothing$ 90 mm label. Boring $\varnothing$ 22 mm	PXK 568 A4	
Empty box	YSU 1513	

## ■ Dimensions

