

- Constructed of durable, high tensile Type 6/6 Nylon, natural color. Special colors available on request.

- Cable Tie slips easily through slot. Tie is securely contained for easy assembly and tensioning.

- Recognized under the component program of Underwriters Laboratories, Inc. File No. E 57800. 

CRADLE MOUNTS



10044
#4 screw;
for miniature
ties.



10045
#8 screw;
for ties up to
standard.



10046
#10 screw;
for ties up to
heavy duty.



10079
1/4" screw; (6 mm Hole)
for heat stabilized ties
up to heavy duty.

- Accommodate miniature, intermediate, standard and heavy duty sized cable ties.
- Provide Stability in Wire Run.

PART NO.	STYLE	PACKAGE QUANTITY
10044 10045 10046 10079	CRADLE MOUNT SMALL #4 SCREW CRADLE MOUNT MEDIUM #8 SCREW CRADLE MOUNT LARGE #10 SCREW CRADLE MOUNT LARGE 1/4" SCREW HEAT STABILIZED (6 mm Hole)	100/BAG 100/BAG 100/BAG 100/BAG

TIE ANCHOR BASE




10027
#8 Screw



10028
#10 Screw

- Accommodate miniature, intermediate, and standard sized cable ties.
- Allows four-way tie mounting with low profile.

LOW PROFILE MOUNT



08458
#8 Screw

- Accommodate miniature, intermediate, and standard sized cable ties.
- Low height accommodates minimal space limitations.

PUSH-IN MOUNTS



10056


- Accommodate miniature, intermediate, and standard sized cable ties.
- For use in .250" hole. (6 mm Hole)

PART NO.	STYLE	PACKAGE QUANTITY
10027 10028 08458 10056	TIE ANCHOR BASE #8 SCREW TIE ANCHOR BASE #10 SCREW LOW PROFILE MOUNT #8 SCREW PUSH-IN MOUNT 1/4" HOLE (6 mm Hole)	100/BAG 100/BAG 100/BAG 100/BAG

Cable Clip

- Available in acrylic-based adhesive
- Allows use of any width cable
- Accommodates stacked cable
- Made of Type 6/6 Nylon
- High quality, durable, non-conductive 

Adhesive Mount



PART. NO.	STYLE	PACKAGE QUANTITY
08406	ADHESIVE FLAT CABLE CLIP	100/BAG

Adhesive Backed Mount Selection Chart

Mount Application	Adhesive Selection	
	Rubber	Acrylic
Paper/Cardboard	X	
Steel/Aluminum	X	X
Glass/Ceramics		X
Rubber	X	
Painted Surfaces	X	X
Cloth	X	
Rigid Vinyl	X	X
Plasticized Vinyl		X
Polypropylene/Polyethylene	X	
ABS Acrylics	X	
Polystyrene	X	X
Urethane	X	

Relative Solvent Resistance	
Rubber	Medium
Acrylic	High

Painted Surfaces	Surface Selection	
	Rubber	Acrylic
Polene	X	
Urethane	X	
Silicone	X	
Latex	X	
Enamel		X
Acrylic		X


Temperature Performance	Low Temperature	High Temperature	
		Continuous	Intermittent
Rubber	-20°F	150°F	200°F
Acrylic	-20°F	180°F	375°F

Relative Shear Strength	
Rubber	High
Acrylic	Very High


Peel Strength	Initial	Ultimate
Rubber	High	High
Acrylic	Medium	High

Cable Tie Mounts


Adhesive Backed and Screw Mount



3/4" (19 mm)
08461
Acrylic-based adhesive
10029
Rubber-based adhesive



1" (25 mm)
08462
Acrylic-based adhesive
10030
Rubber-based adhesive



1" (25 mm)
08463
For use with #6 screw

- Two mounts per peel-off strip provides faster separation from backing.
- Type 6 Nylon for high impact and tensile strength.
- Nylon operating temperatures from -40°F (-40°C) to 185°F (85°C)
- Four-way tie insertion speeds assembly. Ties slide easily into mounts from any of four sides.
- Adhesive-backed mounts (Acrylic or Rubber based) conform to minor surface irregularities.
- Load carrying capability for 1" (25 mm) adhesive-backed mounts is 0.5 lb. (.23 kg); 3/4" (19 mm) mounts is 0.25 lb. (.11 kg).
- Stocked in natural color. Other colors available on request.
- Recognized under the component program of Underwriters Laboratories, Inc. File No. E 57800. 

PART NO.	STYLE	PACKAGE QUANTITY
08461	3/4" ACRYLIC ADHESIVE MOUNT FOR MINIATURE AND INTERMEDIATE TIES (19mm)	100/BAG
10029	3/4" RUBBER BASED ADHESIVE MOUNT FOR MINIATURE AND INTERMEDIATE TIES (19mm)	100/BAG
08462	1" ACRYLIC ADHESIVE MOUNT FOR INTERMEDIATE AND STANDARD TIES (25mm)	100/BAG
10030	1" RUBBER BASED ADHESIVE MOUNT FOR INTERMEDIATE AND STANDARD TIES (25mm)	100/BAG
08463	1" PLAIN BACKED MOUNT FOR INTERMEDIATE AND STANDARD TIES (25mm)	100/BAG