


Kits

for Non-fusible disconnect switches


16A – 3150A, 600V, 3 pole¹



2

Each kit includes:

- 1 three pole¹ switch
- 1 handle
- 1 shaft
- 1 terminal lug kit



Kit

handle

shaft²

switch

terminal lug kit³

Kits with base & DIN rail mounted switches and selector handles

UL general purpose amp rating	IEC AC21 amp rating	Maximum horsepower rating						Kit catalog number
		Single phase		Three phase				
		120V	240V	200V – 208V	240V	480V	600V	
16	16	1/2	1.5	2	2	7.5	7.5	OT16E3S
25	25	3/4	2	3	3	7.5	10	OT25E3S
30	32	1	3	5	5	10	15	OT32E3S
40	45	2	5	10	10	20	20	OT45E3S
60	63	2	5	10	10	20	20	OT63E3S
80	100	3	7.5	15	15	30	30	OT100E3S
100	125	5	10	20	20	40	40	OT125E3S

Kits with base and/or DIN rail mounted switches and pistol handles

UL general purpose amp rating	IEC AC21 amp rating	Maximum horsepower rating						Kit catalog number
		Single phase		Three phase				
		120V	240V	200V – 208V	240V	480V	600V	
16	16	1/2	1.5	2	2	7.5	7.5	OT16E3P
25	25	3/4	2	3	3	7.5	10	OT25E3P
30	32	1	3	5	5	10	15	OT32E3P
40	45	2	5	10	10	20	20	OT45E3P
60	63	2	5	10	10	20	20	OT63E3P
80	100	3	7.5	15	15	30	30	OT100E3P
100	125	5	10	20	20	40	40	OT125E3P
125	160	7	20	30	30	60	75	OT160E3P
175	200	—	—	30	40	75	100	OETL-NF175
200	250	—	—	60	75	150	200	OETL-NF200A
400	630	—	—	100	125	250	350	OETL-NF400
600	800	—	—	150	200	400	500	OETL-NF600A
800	1250	—	—	200	250	500	600	OETL-NF800A
1200	1600	—	—	—	—	—	—	OETL-NF1200
1600	2500	—	—	—	—	—	—	OETL-NF1600
2000	2500	—	—	—	—	—	—	OETL-NF2000
—	3150	—	—	—	—	—	—	OETL-NF3150

Kits with door mounted switches

UL general purpose amp rating	IEC AC21 amp rating	Maximum horsepower rating						Kit catalog number
		Single phase		Three phase				
		120V	240V	200V – 208V	240V	480V	600V	
16	16	1/2	1.5	2	2	7.5	7.5	
25	25	3/4	2	3	3	7.5	10	
30	32	1	3	5	5	10	15	
40	45	2	5	10	10	20	20	
60	63	2	5	10	10	20	20	
80	100	3	7.5	15	15	30	30	
100	125	5	10	20	20	40	40	
125	160	7	20	30	30	60	75	

S W I T C H E S & K N O B S