




TL series tiny sealed toggle switches

Contact rating 0.4 volt-amperes (VA) max. at 20 volts max. (AC or DC). Operating temp. range -30° C to +85° C. Chrome plated brass toggle. Gold over nickel plated brass contacts & terminals. Blue glass filled PBT body, UL94V-0. O-ring bushing seal. Epoxy terminal seal. S.P. body size .200" w x .320" h x .320" d. D.P. body size .360" w x .320" h x .320" d. Process compatible.


MODEL NO.	CIRCUIT	ACTION	
TL36P000000 TL39P000000 TL37P000000 TL38P000000 TL32P000000	SPDT	On-None-On On-Off-On (On)-Off-(On) On-Off-(On) On-None-(On)	 STRAIGHT P.C. TERMINALS
TL46P000000 TL49P000000 TL47P000000 TL48P000000 TL42P000000	DPDT	On-None-On On-Off-On (On)-Off-(On) On-Off-(On) On-None-(On)	
TL36Y0000050 TL39Y0000050 TL37Y0000050 TL38Y0000050 TL32Y0000050	SPDT	On-None-On On-Off-On (On)-Off-(On) On-Off-(On) On-None-(On)	
TL46Y0000050 TL49Y0000050 TL47Y0000050 TL48Y0000050 TL42Y0000050	DPDT	On-None-On On-Off-On (On)-Off-(On) On-Off-(On) On-None-(On)	
TL36W0000050 TL39W0000050 TL37W0000050 TL38W0000050 TL32W0000050	SPDT	On-None-On On-Off-On (On)-Off-(On) On-Off-(On) On-None-(On)	
TL46W0000050 TL49W0000050 TL47W0000050 TL48W0000050 TL42W0000050	DPDT	On-None-On On-Off-On (On)-Off-(On) On-Off-(On) On-None-(On)	 RT. ANGLE HORIZ. PC TERMS.
TL36WW000050 TL39WW000050 TL37WW000050 TL38WW000050 TL32WW000050	SPDT	On-None-On On-Off-On (On)-Off-(On) On-Off-(On) On-None-(On)	
TL46WW000050 TL49WW000050 TL47WW000050 TL48WW000050 TL42WW000050	DPDT	On-None-On On-Off-On (On)-Off-(On) On-Off-(On) On-None-(On)	
TL36MW000000 TL39MW000000 TL37MW000000 TL38MW000000 TL32MW000000	SPDT	On-None-On On-Off-On (On)-Off-(On) On-Off-(On) On-None-(On)	
TL46MW000000 TL49MW000000 TL47MW000000 TL48MW000000 TL42MW000000	DPDT	On-None-On On-Off-On (On)-Off-(On) On-Off-(On) On-None-(On)	
			WIRE-WRAP TERMINALS

S series miniature sealed toggle switches (p.c. mt.)

Contact rating 0.4 volt-amperes (VA) max. at 20 volts max. (AC or DC). Operating temp. range -20° C to +85° C. Chrome plated brass toggle (.296" lg.). Gold over nickel plated brass contacts & terminals. Glass filled polyamide body, UL94V-0. O-ring bushing seal. Epoxy terminal seal. S.P. body size .500" w x .259" h x .425" d. D.P. body size .500" w x .458" h x .425" d. Process compatible.


MODEL NO.	CIRCUIT	ACTION	
SW236CD7 SW239CD7 SW237CD7 SW238CD7 SW232CD7	SPDT	On-None-On On-Off-On (On)-Off-(On) On-Off-(On) On-None-(On)	 RT. ANGLE HORIZ. PC TERMS.
SW246CD7 SW249CD7 SW247CD7 SW248CD7 SW242CD7 SW244THCD7	DPDT	On-None-On On-Off-On (On)-Off-(On) On-Off-(On) On-None-(On) On-On-On	

S series mini. sealed toggle switches (p.c. mt.) (cont.)

MODEL NO.	CIRCUIT	ACTION	
SWW236CD7 SWW239CD7 SWW237CD7 SWW238CD7 SWW232CD7	SPDT	On-None-On On-Off-On (On)-Off-(On) On-Off-(On) On-None-(On)	 RT. ANGLE VERT. PC TERMS.
SWW246CD7 SWW249CD7 SWW247CD7 SWW248CD7 SWW242CD7 SWW244THCD7	DPDT	On-None-On On-Off-On (On)-Off-(On) On-Off-(On) On-None-(On) On-On-On	
SY236CD7 SY239CD7 SY237CD7 SY238CD7 SY232CD7	SPDT	On-None-On On-Off-On (On)-Off-(On) On-Off-(On) On-None-(On)	
SY246CD7 SY249CD7 SY247CD7 SY248CD7 SY242CD7 SY244THCD7	DPDT	On-None-On On-Off-On (On)-Off-(On) On-Off-(On) On-None-(On) On-On-On	


SF series mini. sealed toggle switches (Panel mt.)

Contact ratings: **S0** models- 5 amps at 125 VAC, 2 amps at 250 VAC or 4 amps at 30 VDC (silver contacts & terminals). **P0** models- 0.4 volt-amperes (VA) max. at 20 volts max. (gold plated contacts & terms.). Operating temp. range -20° C to +85° C. Chrome plated brass toggle (.421" lg.). Glass filled polyamide body, UL94V-0. O-ring bushing seal. Epoxy terminal seal. S.P. body size .500" w x .259" h x .425" d. D.P. body size .500" w x .458" h x .425" d. Mounts in 1/4" hole. Mounting hardware supplied. Process compatible.

MODEL NO.	CIRCUIT	ACTION	
SF36S0100 SF39S0100 SF37S0100 SF37S0100 SF32S0100	SPDT	On-None-On On-Off-On (On)-Off-(On) On-Off-(On) On-None-(On)	 STRAIGHT PC TERMS. SHOWN
SF36P0000 SF39P0000 SF37P0000 SF38P0000 SF32P0000	SPDT	On-None-On On-Off-On (On)-Off-(On) On-Off-(On) On-None-(On)	

5000 series miniature toggle switches (panel mt.)

Contact rating 6 amps at 120 VAC or 3 amps at 250 VAC or 4 amps at 30 VDC. Operating temperature range -40° C to 85° C. Chrome plated brass toggle. Nickel plated brass bushing. Silver contacts. Silver plated brass terminals. Diallyl phthalate case. Epoxy term. seal. Mounting hardware included. S.P. body size .275" w x .519" h x .472" d. D.P. body size .519" w x .472" h x .472" d. 3P. body size .519" w x .649" h x .516" d. 4P. body size .519" w x .834" h x .516" d. Mounts in 1/4" hole (except 'M' models). UL & CSA listing available - consult factory. Dry ckt. models w/gold over nickel conts. & terms. and rating of 0.4 volt-amperes (VA) max. at 20 volts max. also available. To specify, substitute 'CD' for 'A' in model number below. **This Series continued on next page**

MODEL NO.	CIRCUIT	ACTION	
5636AB 5639AB 5637AB 5638AB 5632AB	SPDT	On-None-On On-Off-On (On)-Off-(On) On-Off-(On) On-None-(On)	 STANDARD ROUND HANDLE SOLDER LUG TERMINALS
5646AB 5649AB 5647AB 5648AB 5642AB 5644THAB	DPDT	On-None-On On-Off-On (On)-Off-(On) On-Off-(On) On-None-(On) On-On-On	
5656AB 5659AB 5657AB 5658AB 5652AB	3PDT	On-None-On On-Off-On (On)-Off-(On) On-Off-(On) On-None-(On)	
5666AB 5669AB 5667AB 5668AB 5662AB 5664THAB	4PDT	On-None-On On-Off-On (On)-Off-(On) On-Off-(On) On-None-(On) On-On-On	