

S series miniature sealed rocker switches (p.c. mt.)

Contact rating 0.4 volt-amps (VA) max. at 20 volts max. (AC or DC). Operating temp. range -20° C to +85° C. Black polyamide rocker. Gold over nickel plated brass contacts & terminals. Glass filled polyamide body, UL94V-0. O-ring bushing seal. Epoxy terminal seal. S.P. body size .500" w x .259" h x .425" d. D.P. body size .500" w x .446" h x .425" d. Process compatible.

MODEL NO.	CKT.	ACTION	
SW236CD6+U622 SW239CD6+U622 SW237CD6+U622 SW238CD6+U622 SW232CD6+U622	SPDT	On-None-On On-Off-On (On)-Off-(On) On-Off-(On) On-None-(On)	
SW246CD6+U622 SW249CD6+U622 SW247CD6+U622 SW248CD6+U622 SW242CD6+U622 SW244THCD6+U622	DPDT	On-None-On On-Off-On (On)-Off-(On) On-Off-(On) On-None-(On) On-On-On	
SWW236CD6+U622 SWW239CD6+U622 SWW237CD6+U622 SWW238CD6+U622 SWW232CD6+U622	SPDT	On-None-On On-Off-On (On)-Off-(On) On-Off-(On) On-None-(On)	
SWW246CD6+U622 SWW249CD6+U622 SWW247CD6+U622 SWW248CD6+U622 SWW242CD6+U622 SWW244THCD6+U622	DPDT	On-None-On On-Off-On (On)-Off-(On) On-Off-(On) On-None-(On) On-On-On	
SY236CD6+U622 SY239CD6+U622 SY237CD6+U622 SY238CD6+U622 SY232CD6+U622	SPDT	On-None-On On-Off-On (On)-Off-(On) On-Off-(On) On-None-(On)	
SY246CD6+U622 SY249CD6+U622 SY247CD6+U622 SY248CD6+U622 SY242CD6+U622 SY244THCD6+U622	DPDT	On-None-On On-Off-On (On)-Off-(On) On-Off-(On) On-None-(On) On-On-On	
SWW236CD6X653+U622 SWW239CD6X653+U622 SWW237CD6X653+U622 SWW238CD6X653+U622 SWW232CD6X653+U622	SPDT	On-None-On On-Off-On (On)-Off-(On) On-Off-(On) On-None-(On)	
SWW246CD6X653+U622 SWW249CD6X653+U622 SWW247CD6X653+U622 SWW248CD6X653+U622 SWW242CD6X653+U622 SWW244THCD6X653+U622	DPDT	On-None-On On-Off-On (On)-Off-(On) On-Off-(On) On-None-(On) On-On-On	

RIGHT ANGLE HORIZ.
P.C. TERMINALS

RIGHT ANGLE VERT.
P.C. TERMINALS

STRAIGHT P.C. TERMS.
W/MOUNTING BRKT.

RT. ANGLE VERT. P.C.
TERMS./ SPACING BRKT.

SR series mini. sealed rocker switches (panel mt.)

Contact rating 0.4 volt-amps (VA) max. at 20 volts max. (AC or DC). Operating temp. range -20° C to +85° C. Black polyamide rocker. Gold over nickel plated brass contacts & terminals. Glass filled polyamide body, UL94V-0. O-ring bushing seal. Epoxy terminal seal. S.P. body size .500" w x .259" h x .425" d. D.P. body size .500" w x .446" h x .425" d. Mounts in .610" x 1.082" panel cutout. Process compatible.

MODEL NO.	CIRCUIT	ACTION	
SR36S010012 SR39S010012 SR37S010012 SR37S010012 SR32S010012	SPDT	On-None-On On-Off-On (On)-Off-(On) On-Off-(On) On-None-(On)	
SR46S010012 SR49S010012 SR47S010012 SR48S010012 SR42S010012 SR44S010012	DPDT	On-None-On On-Off-On (On)-Off-(On) On-Off-(On) On-None-(On) On-On-On	

SOLDER LUG TERMINALS

7000 series miniature rocker/lever switches (pnl. mt.)

Contact rating 6 amps at 120 VAC or 3 amps at 250 VAC or 4 amps at 30 VDC. Operating temperature range -40° C to 85° C. Black polyamide actuator/bezel. Silver contacts. Silver plated brass terminals. Diallyl phthalate case. Epoxy term. seal. Mounting hardware included. S.P. body size .275" w x .500" h x .433" d. D.P. body size .500" w x .472" h x .433" d. Mounts in panel cutout. UL & CSA listing available - consult factory. Dry ckt. models with gold over nickel conds. & terms. and rating of 0.4 volt-amps (VA) max. at 20 volts max. also available. To specify, substitute 'CD' for 'A' in model number below.

MODEL NO.	CKT.	ACTION	
7636AB+U732+U1202 7639AB+U732+U1202 7637AB+U732+U1202 7638AB+U732+U1202 7632AB+U732+U1202	SPDT	On-None-On On-Off-On (On)-Off-(On) On-Off-(On) On-None-(On)	
7646AB+U732+U1202 7649AB+U732+U1202 7647AB+U732+U1202 7648AB+U732+U1202 7642AB+U732+U1202 7644THAB+U732+U1202	DPDT	On-None-On On-Off-On (On)-Off-(On) On-Off-(On) On-None-(On) On-On-On	
7236AB+U732+U1202 7239AB+U732+U1202 7237AB+U732+U1202 7238AB+U732+U1202 7232AB+U732+U1202	SPDT	On-None-On On-Off-On (On)-Off-(On) On-Off-(On) On-None-(On)	
7246AB+U732+U1202 7249AB+U732+U1202 7247AB+U732+U1202 7248AB+U732+U1202 7242AB+U732+U1202 7244THAB+U732+U1202	DPDT	On-None-On On-Off-On (On)-Off-(On) On-Off-(On) On-None-(On) On-On-On	
7736AB+U532 7739AB+U532 7737AB+U532 7738AB+U532 7732AB+U532	SPDT	On-None-On On-Off-On (On)-Off-(On) On-Off-(On) On-None-(On)	
7746AB+U532 7749AB+U532 7747AB+U532 7748AB+U532 7742AB+U532 7744THAB+U532	DPDT	On-None-On On-Off-On (On)-Off-(On) On-Off-(On) On-None-(On) On-On-On	
7936AB+U532 7939AB+U532 7937AB+U532 7938AB+U532 7932AB+U532	SPDT	On-None-On On-Off-On (On)-Off-(On) On-Off-(On) On-None-(On)	
7946AB+U532 7949AB+U532 7947AB+U532 7948AB+U532 7942AB+U532 7944THAB+U532	DPDT	On-None-On On-Off-On (On)-Off-(On) On-Off-(On) On-None-(On) On-On-On	
7736NAB+U622 7739NAB+U622 7737NAB+U622 7738NAB+U622 7732NAB+U622	SPDT	On-None-On On-Off-On (On)-Off-(On) On-Off-(On) On-None-(On)	
7746NAB+U622 7749NAB+U622 7747NAB+U622 7748NAB+U622 7742NAB+U622 7744NTHAB+U622	DPDT	On-None-On On-Off-On (On)-Off-(On) On-Off-(On) On-None-(On) On-On-On	
7936NAB+U622 7939NAB+U622 7937NAB+U622 7938NAB+U622 7932NAB+U622	SPDT	On-None-On On-Off-On (On)-Off-(On) On-Off-(On) On-None-(On)	
7946NAB+U622 7949NAB+U622 7947NAB+U622 7948NAB+U622 7942NAB+U622 7944NTHAB+U622	DPDT	On-None-On On-Off-On (On)-Off-(On) On-Off-(On) On-None-(On) On-On-On	

SMALL ROCKER
SOLDER LUG TERMINALS

SMALL LEVER U702 SHOWN
STRAIGHT P.C. TERMINALS

LARGE ROCKER
SOLDER LUG TERMINALS

LARGE LEVER U492 SHOWN
STRAIGHT P.C. TERMINALS

MEDIUM ROCKER
SOLDER LUG TERMINALS

MEDIUM LEVER U612 SHOWN
STRAIGHT P.C. TERMINALS