

TG series microminiature slide switches (cont.)

	MODEL NUMBER	CONT. MAT'L	ACTION	
Vertical p.c. mount. with bracket	TG36Y000000	Gold	on - on	
	TG39Y000000	Gold	on off on	
	TG36Y010000	Silver	on - on	
	TG39Y010000	Silver	on off on	
	TG36Y000050	Gold	On - on	
	TG39Y000050	Gold	on off on	
	TG36Y010050	Silver	on - on	
Rt. angle p.c. mount. with bracket	TG36W000000	Gold	on - on	
	TG39W000000	Gold	on off on	
	TG36W010000	Silver	on - on	
	TG39W010000	Silver	on off on	
	TG36W000050	Gold	on - on	
	TG39W000050	Gold	on off on	
	TG36W010050	Silver	on - on	
	TG39W010050	Silver	on off on	
				TRANSLUCENT SEAL SHOWN

GH series instrument grade miniature slide switches

Contact rating: 4 amps at 125 VAC, 2 amps at 250 VAC or 3 amps at 30 VDC. SPDT & DPDT maint'd. circuits. Op. temp. range -30° C to 85° C. Glass filled polyamide actuator. PES case. Stainless st. cover. Silver plated contacts & terms. Epoxy sealed terms. Body size approx. - SP .500"l x .262"w x .250"h. DP .500"l x .449"w x .299"h. Note - dry circuit models with gold plated contacts & terms. available - consult factory.

	MODEL NO.	CIRCUIT	ACTION	
Panel mnt. w/brkt.	GH36S010001	SPDT	on - on	
	GH39S010001	SPDT	on off on	
	GH46S010001	DPDT	on - on	
	GH49S010001	DPDT	on off on	
	GH36P010001	SPDT	on - on	
	GH39P010001	SPDT	on off on	
	GH46P010001	DPDT	on - on	
	GH49P010001	DPDT	on off on	
	GH36W010001	SPDT	on - on	
	GH39W010001	SPDT	on off on	
	GH46W010001	DPDT	on - on	
	GH49W010001	DPDT	on off on	
Actuator length approx. .200"	GH36WW10001	SPDT	on - on	
	GH39WW10001	SPDT	on off on	
	GH46WW10001	DPDT	on - on	
	GH49WW10001	DPDT	on off on	
	GH36Y010001	SPDT	on - on	
	GH39Y010001	SPDT	on off on	
	GH46Y010001	DPDT	on - on	
	GH49Y010001	DPDT	on off on	
	GH36Y410001	SPDT	on - on	
	GH39Y410001	SPDT	on off on	
	GH46Y410001	DPDT	on - on	
	GH49Y410001	DPDT	on off on	

25000 series miniature slide switches

Contact rating: 4 amps at 125 VAC, 2 amps at 250 VAC or 3 amps at 30 VDC. SPDT & DPDT maint'd. circuits. Op. temp. range -40° C to +85° C. Glass filled polyamide actuator and cover. PBT case. Silver plated contacts & terms. Epoxy sealed terms. Terminal spacing is .200" c to c. Body size- SP .555"l x .295"w x .319"h. DP same except .465"w. Note - dry circuit models with gold plated contacts & terminals available - consult factory.

	MODEL NO.	CIRCUIT	ACTION	
1.00" c to c terminal spacing	25136NAB	SPDT	on - on	
	25139NAB	SPDT	on off on	
	25146NAB	DPDT	on - on	
	25149NAB	DPDT	on off on	
	25336NA	SPDT	on - on	
	25339NA	SPDT	on off on	
	25346NA	DPDT	on - on	
	25349NA	DPDT	on off on	
	25136NAH	SPDT	on - on	
	25139NAH	SPDT	on off on	
	25146NAH	DPDT	on - on	
	25149NAH	DPDT	on off on	
2.00" c-c	25336NA6	SPDT	on - on	
	25339NA6	SPDT	on off on	
	25346NA6	DPDT	on - on	
	25349NA6	DPDT	on off on	
2.00" c-c	25436NAB	SPDT	on - on	
	25439NAB	SPDT	on off on	
	25446NAB	DPDT	on - on	
	25449NAB	DPDT	on off on	

25000 series miniature slide switches (cont.)

	MODEL NO.	CIRCUIT	ACTION	
2.00" c to c terminal spacing	25449NAB	DPDT	on off on	
	25536NA	SPDT	on - on	
	25539NA	SPDT	on off on	
	25546NA	DPDT	on - on	
	25549NA	DPDT	on off on	
	25436NAH	SPDT	on - on	
	25439NAH	SPDT	on off on	
	25446NAH	DPDT	on - on	
	25449NAH	DPDT	on off on	
	25536NA6	SPDT	on - on	
	25539NA6	SPDT	on off on	
	25546NA6	DPDT	on - on	
	25549NA6	DPDT	on off on	

PT65 series DIP coded rotary switches

Contact rating : Carry - 400 mA max. at 24 VDC; Switching - 150 mA max. at 24 VDC.


Op. temp. range -20° C to +70° C. Glass filled thermoplastic body, color - lt. gray. Glass filled thermoplastic actuator, color - dk. gray. Internal o-ring actuator seal. Contacts gold over nickel plated. Molded-in solder coated terms.. 10 & 16 position models. Body size .393" sq. x .256" high. Process compatible. **Code 1:** BCD (2 common terms.). **Code 2:** BCD complement. **Code 3:** Hexadecimal. **Code 6:** Hex. comp. **Code 5:** Gray code

CODE	MODEL NO. BY TERMINAL STYLE				
	STRAIGHT .200"X.300"	RIGHT ANGLE AT PITCH =			
		.100"	.200"		
1	PT65101	PT65101L254	PT65101L508	PT65101	
2	PT65102	PT65102L254	PT65102L508		
3	PT65103	PT65103L254	PT65103L508		
4	PT65106	PT65106L254	PT65106L508		
5	PT65105	PT65105L254	PT65105L508		
1	PT65301	PT65301L254	PT65301L508	PT65301	
2	PT65302	PT65302L254	PT65302L508		
3	PT65303	PT65303L254	PT65303L508		
4	PT65306	PT65306L254	PT65306L508		
5	PT65305	PT65306L254	PT65306L508		
1	PT65501	PT65501L254	PT65501L508	PT65501	
2	PT65502	PT65502L254	PT65502L508		
3	PT65503	PT65503L254	PT65503L508		
4	PT65506	PT65506L254	PT65506L508		
5	PT65505	PT65505L254	PT65506L508		

DS & DP series DIP switches

Contact rating : Carry - 100 mA max. at 50 VDC; Switching - 50 mA max. at 24 VDC.

Op. temp. range -40° C to +70° C. UL94V-O case, color - red. UL94V-O actuator, color - white. Contacts & terms. gold over nickel over phosphor bronze. Epoxy sealed terms.. Std'd. DIP package term. spacing of .100" x .300". Process compatible when optional tape seal is specified. SPST Off-On action.

ACT- UATOR STYLE	MOD. NO. NO TAPE SEAL	MOD. NO. W/TAPE SEAL	NO. OF POS.	
RAISED ACTUATOR	DS02	DS02T	2	
	DS03	DS03T	3	
	DS04	DS04T	4	
	DS05	DS05T	5	
	DS06	DS06T	6	
	DS07	DS07T	7	
	DS08	DS08T	8	
	DS09	DS09T	9	
	DS10	DS10T	10	
	DS12	DS12T	12	
RECESSED ACTUATOR	DP02	DP02T	2	
	DP03	DP03T	3	
	DP04	DP04T	4	
	DP05	DP05T	5	
	DP06	DP06T	6	
	DP07	DP07T	7	
	DP08	DP08T	8	
	DP09	DP09T	9	
	DP10	DP10T	10	
	DP12	DP12T	12	

Consult factory for extensive DIP switch listings.