



14.7 x 5.4 x 11.3mm

F6 SERIES

Ultraminiature sealed switch with long overtravel.

Rating- 50mA @ 250VAC & 2mA @ 12-24VDC

PC Terminals

Operating Temperature- -40°C to +85°C

Sealed to IP67



14.4 x 5.7 x 6.5mm

F1NCST8 SERIES

Ultraminiature sealed switch with side facing terminals.

F1NCST8

1

2

3

Rating- 1A @ 125/250VAC & 2A 30VDC

PC Terminals

Operating Temperature- -40°C to +85°C

Sealed to IP54

(1) Contact Type

No Symbol- Changeover

C2 - Normally Closed

C4 - Normally Open

(2) Actuators

No Symbol- Button

A1- 18mm Straight

AC- 18.5mm Cam Follower

(3) Contact Material

No Symbol- Fine Silver

GP-Gold Plated



31.7 x 10.5 x 29.2mm

CV3S SERIES

Miniature sealed snap-action switch.

CV3S

1

UL/CSA Rating - 5A up to 250VAC & 30VDC

Contact Type - Single pole Changeover

Contact Material - Fine Silver

Temperature Range- -10°C- +85°C

Sealed To - IP67

Leadwires - PVC 18 Gauge 0.5m (19.7") long

(1) Actuators

No Symbol- Pin Plunger

Y1 - 26.2 mm Straight

YR - 11.7mm Roller

YR1 - 24.2mm Roller