

# WRSP Series Weatherproof Single-pole Rocker Switches

**Approvals**

UL recognized. CSA and VDE approvals pending.  
 Load rating: 20A 125/250 VAC. 3/4 HP, 125/250 VAC. 14A 14VDC. Contacts: fine silver for long life dependability. Di-electric strength: 1250 volts (live parts to ground).  
 Life: 35,000 operations at maximum rating.  
 Insulation resistance: 5 megohms.

**Water & Dust Resistance**

Designed to meet IP-64.

**High Inrush**

125 Amp inrush capability (AgNi contacts).

**Low Level Control**

For low level/dry circuit applications (<100 am) contact factory for part number.

**Terminals**

Style A - 1/4-inch quick-connect

**Mechanical Features**

100,000 mechanical operations

**Markings**

Letters, numbers and symbols can be applied to rocker actuator or to integral nylon bezel; see inside back cover for details.


**Mounting**

Snap-in type panel mounting for ease of installation without additional mounting hardware.

Circuit	Switching	
1	SPST Maintained	
2	SPDT Maintained	
3	SPDT Maintained Center Off	
4	SPST (Momentary) Normally Open	
5	SPDT (Momentary) Normally Closed	
6	SPDT (Momentary) Transfer	
7	SPDT Maintained Center Off (Momentary)	
8	SPDT (Momentary) Center Off (Momentary)	

**Ordering Information:**

**WRSP**



**Circuit**

- 1=SPST Maintained
- 2=SPDT Maintained
- 3=SPDT Maintained Center Off
- 4=SPST (Momentary) Normally Open
- 5=SPST (Momentary) Normally Closed
- 6=SPDT (Momentary) Transfer
- 7=SPDT Maintained Center Off (Momentary)
- 8=SPDT (Momentary) Center Off (Momentary)

**Terminal Option**

- A=Fine Silver (Normal Duty)
- G=Gold Plated Contacts
- H=High Inrush Contacts