



Momentary / Maintained / Signal Lamps

2

S W I T C H E S & K N O B S

Round aluminum bezel style


IP65/IP40



	Faston Connection	Solder Connection
Momentary	505018	505118
Maintained	515018	515118
Indicator lamps	555018	555118

Round aluminum bezel style



With built in silicone cap.
IP65



	Faston Connection	Solder Connection
Momentary	505033	505133
Maintained	515033	515133
Indicator lamps	555033	555133

Round straight plastic bezel style Q25


IP65



	Faston Connection	Solder Connection
Momentary	505020	505120
Maintained	515020	515120
Indicator lamps	555020	555120

Round flush metal bezel style

IP67



	Faston Connection	Solder Connection
Momentary	505051	505151
Maintained	515051	515151
Indicator lamps	555051	555151

Lens Ø18 IP65

	Opaque	Transparent
white	464001	465001
yellow	464101	465101
green	464201	465201
blue	464301	465301
red	464401	465401
black	464501	
orange	464601	465601

Lens Ø18 IP65

	Opaque	Transparent
white	464001	465001
yellow	464101	465101
green	464201	465201
blue	464301	465301
red	464401	465401
black	464501	
orange	464601	465601

Lens flat Ø21 IP65

	Opaque	Transparent
white	564024	565024
yellow	564124	565124
green	564224	565224
blue	564324	565324
red	564424	565424
black	564524	
orange	564624	565624

Lens flat Ø18 IP67

	Opaque	Transparent
white	564025	565025
yellow	564125	565125
green	564225	565225
blue	564325	565325
red	564425	565425
black	564525	
orange	564625	565625

Lens Ø18 IP40

	Opaque	Transparent
white	464015	465015
yellow	464115	465115
green	464215	465215
blue	464315	465315
red	464415	465415
black	464515	
orange	464615	465615

Bezels made of anodized aluminum alloy are also available in black anodized aluminum by adding the suffix 500 i.e. 404018 500. It is splash proof and oil tight in accordance with IP65, similar to NEMA 4 and 13.

The IP65 standard (splash proof oil tight) is achieved with a sealing ring which comes supplied with the corresponding lens.

Splash proof and oil tight in accordance with IP65, similar to NEMA 4 and 13.

Bezels made of anodized aluminum alloy are also available in black anodized aluminum by adding the suffix 500 i.e. 404018 500.

It is splash proof and oil tight in accordance with IP67 and submersible up to 1.2 meters. Exceeds NEMA 6.

Bezels made of anodized aluminum alloy are also available in black anodized aluminum by adding the suffix 500 i.e. 404018 500. It is splash proof and oil tight in accordance with IP65.

The IP65 standard (splash proof oil tight) is achieved with a sealing ring which comes supplied with the corresponding lens.

An IP40 version can be achieved by specifying standard lens caps Ø18 IP40.


ORDER CONTACT BLOCK SEPARATELY

COMMON INFORMATION CONTACT BLOCKS TO BE SPECIFIED SEPARATELY.

Lamp holder T 1³/₄ MG

For a brighter light, all transparent lens can be specified with a clear lower lens diffuser. Use 010 suffix (i.e. 461012 010).

PANEL CUT-OUTS FOR UP TO 1 SINGLE CONTACT BLOCK + 1 DOUBLE CONTACT BLOCK



PANEL CUT-OUTS FOR 2 DOUBLE CONTACT BLOCK

