

Series SSB3

Ordering information

(All dimensions in inches)

SSB	3	F	F	06	02	02	11	N	N
A	B	C	D	E	F	G	H	I	J

A Single Screw Barrier Block
SSB

B Contact Spacing
(Center-to-Center)
3= .325

C Base
F=Flat Base

D Mounting Options
F=Open end positions without end
barriers
M=Open end positions with end barriers
P=All positions filled with contacts, with
end barriers
T=Threaded mounting plate in each
end position. End barriers removed.

E Number of Circuits (Not Positions)
02 through 36

F Terminal Options
02=Circuit Board
03=Non-Feedthrough
04=Extended Circuit Board
07=Machine Wrap
11=Right Angle Bend .29 × .12
12=Right Angle Bend .44 × .12

G Top Hardware Options
01=Bright zinc and chromate plated
steel binding-head screw
02=Bright zinc and chromate plated
steel screw and captive clamp — Do
not order in combination with other
top hardware.

QUICK-CONNECT BLADES (supplied
with 01 screw)

.110 wide x.020 thick	.187 wide x.020 thick
10	70 = 
11	71 = 
12	72 = 
13	73 = 
14	74 = 
15	75 = 

H Circuit Identification Options
11=1 2 3 4 5 . . .
12=. . . 5 4 3 2 1
13= . . .
14=. . .  . . .
15=. . . 5 4 3 2 1
16=1 2 3 4 5 . . .

I Material
N=Polypropylene

J Color
N=Black

4

T E R M I N A L B L O C K S