

SKINTOP® SL / SLR

Liquid Tight, Non-Metallic Strain Relief Connector
with PG Thread



5

SKINTOP® SL/SLR is a unique, liquid tight, easy to assemble strain relief connector with a PG thread, that is universally suited for all types of

machinery & equipment, including automation, motion control and robotics.



Materials:

Body: Polyamide

Seal: Neoprene

Halogen Free Seals Available
on Special Order

See page 166 for dimensional details.

Protection:

70 PSI

Seal:

IP 68 (Comparable to NEMA 6)

Temperature range: -20°C to +80°C

CONNECTORS

Part Number	Grey	Description	Thread Type	UL Status	Range	A Mounting Hole	B Maximum Overall Length	C Thread Length	D Wrenching Nut Thickness	E Wrenching Flats	Pack Size
PG THREAD – STANDARD TYPE											
S2207	S1207	SLR-7	PG-7	R	.079 - .197	.492	1.259	.315	.203	.591	100
S2107	S1107	SL-7	PG-7	R	.118 - .255	.492	1.259	.315	.203	.591	100
S2209	S1209	SLR-9	PG-9	R	.079 - .236	.599	1.378	.315	.218	.750	100
S2109	S1109	SL-9	PG-9	R	.157 - .314	.599	1.378	.315	.218	.750	100
S2211	S1211	SLR-11	PG-11	R	.118 - .279	.733	1.500	.315	.218	.866	100
S2111	S1111	SL-11	PG-11	R	.197 - .394	.733	1.500	.315	.218	.866	100
S2213	S1213	SLR-13	PG-13	L	.341 - .353	.804	1.614	.354	.218	.945	100
S2113	S1113	SL-13	PG-13	L	.236 - .472	.804	1.614	.354	.218	.945	100
S2216	S1216	SLR-16	PG-16	L	.423 - .481	.886	1.732	.394	.234	1.063	50
S2116	S1116	SL-16	PG-16	L	.394 - .551	.886	1.732	.394	.234	1.063	50
S2221	S1221	SLR-21	PG-21	L	.481 - .617	1.115	1.929	.433	.250	1.299	50
S2121	S1121	SL-21	PG-21	L	.545 - .709	1.115	1.929	.433	.250	1.299	50
S2229	S1229	SLR-29	PG-29	R	.512 - .787	1.457	2.165	.433	.297	1.654	25
S2129	S1129	SL-29	PG-29	R	.708 - .984	1.457	2.165	.433	.297	1.654	25
S2236	S1236	SLR-36	PG-36	L	.787 - 1.023	1.850	2.519	.512	.315	2.087	10
S2136	S1136	SL-36	PG-36	L	.866 - 1.259	1.850	2.519	.512	.315	2.087	10
S2242	S1242	SLR-42	PG-42	R	.945 - 1.220	2.126	2.638	.512	.360	2.362	5
S2142	S1142	SL-42	PG-42	R	1.259 - 1.496	2.126	2.638	.512	.360	2.362	5
S2248	S1248	SLR-48	PG-48	L	1.141 - 1.378	2.335	2.717	.551	.360	2.559	5
S2148	S1148	SL-48	PG-48	L	1.456 - 1.732	2.335	2.717	.551	.360	2.559	5

* "R" in description indicates reducer bushing.

** Locknuts provided with PG sizes.

*** Orders of 2000 pieces or more per item will be bulk packaged unless otherwise requested.

UL Status: R = Recognized; L = Listed