

AGC, AGC-V SERIES FAST ACTING GLASS TUBE FUSES 1/4" LONG x 1/4" DIA.



AGC—Glass tube with albaloy plated brass end caps. Packaged 5/ctn.

AGC-V—Glass tube with axial leads. Packaged 4/box.

UL Listed 0-10A, Guide JDYX, File E19180. UL Recognized 15-30A, Guide JDYX2, File E19180. CSA Certified, Class 1422-01, File 53787.

AGC SERIES FUSES

Mfr. No.	Rating Amps	AC/DC* Inter. Rating Amps	Mfr. No.	Rating Amps	AC/DC* Inter. Rating Amps
Rated 250 VAC/VDC*					
AGC-1/200	1/200	35	AGC-1 1/4	1 1/4	100
AGC-1/100	1/100	35	AGC-1 1/2	1 1/2	100
AGC-1/32	1/32	35	AGC-1 3/10	1 3/10	100
AGC-1/20	1/20	35	AGC-1 3/4	1 3/4	100
AGC-1/16	1/16	35	AGC-1 9/10	1 9/10	100
AGC-1/10	1/10	35	AGC-2	2	100
AGC-1/8	1/8	35	AGC-2 1/4	2 1/4	100
AGC-15/100	15/100	35	AGC-2 1/2	2 1/2	100
AGC-175/1000	175/1000	35	AGC-3	3	100
AGC-3/16	3/16	35	AGC-3 3/10	3 3/10	100
AGC-2/10	2/10	35	AGC-3 1/2	3 1/2	100
AGC-1/4	1/4	35	AGC-4	4	200
AGC-3/10	3/10	35	AGC-5	5	200
AGC-3/8	3/8	35	AGC-6	6	200
AGC-4/10	4/10	35	AGC-6 1/4	6 1/4	200
AGC-1/2	1/2	35	AGC-7	7	200
AGC-6/10	6/10	35	AGC-7 1/2	7 1/2	200
AGC-3/4	3/4	35	AGC-8	8	200
AGC-9/10	9/10	35	AGC-9	9	200
AGC-1	1	35	AGC-10	10	200

Rated 32 VAC

AGC-12	12	1000	AGC-30	30	1000
AGC-14	14	1000	AGC-35	35	1000
AGC-15	15	1000	AGC-40	40	1000
AGC-20	20	1000	AGC-50	50	1000
AGC-25	25	1000

*DC ratings are self certified. †Interrupting rating for VAC only.

Note: Interrupting ratings were measured at 70% to 80% power factor on AC, and at a time constant described in UL 198L.

AGC-V SERIES AXIAL LEAD FUSES

Mfr. No.	Rating Amps	AC/DC* Inter. Rating Amps	Mfr. No.	Rating Amps	AC/DC* Inter. Rating Amps
Rated 250 VAC/VDC*					
AGC-V-1/8	1/8	35	AGC-V-2 1/2	2 1/2	100
AGC-V-1/4	1/4	35	AGC-V-3	3	100
AGC-V-1/2	1/2	35	AGC-V-4	4	200
AGC-V-3/4	3/4	35	AGC-V-5	5	200
AGC-V-1	1	35	AGC-V-6	6	200
AGC-V-1 1/4	1 1/4	100	AGC-V-7	7	200
AGC-V-1 1/2	1 1/2	100	AGC-V-7 1/2	7 1/2	200
AGC-V-1 3/4	1 3/4	100	AGC-V-8	8	200
AGC-V-2	2	100	AGC-V-10	10	200
Rated 32 VAC					
AGC-V-15	15	1000†	AGC-V-25	25	1000†
AGC-V-20	20	1000†	AGC-V-30	30	1000†

*DC ratings are self certified. †Interrupting Rating VAC only.

Note: Interrupting ratings were measured at 70% to 80% power factor on AC, and at a time constant described in UL 198L.

MDA AND MDA-V PC BOARD & SMALL DIMENSION TIME-DELAY FUSES



Time-Delay fuse constructed of ceramic tube; Albaloy plated brass end caps. UL Listed, Guide JDYX, File E19180, 0-15A. CSA Certification, Class 1422-01, File 53787, 0-15A. Dimensions: 1/4" long x 1/4" dia.

Mfr. No.	Rating Amps	Ctn. Qty.	Mfr. No.	Rating Amps	Ctn. Qty.
250 VAC					
MDA-2/10	2 1/10	5	MDA-4	4	5
MDA-1/4	1/4	5	MDA-5	5	5
MDA-1/2	1/2	5	MDA-6	6	5
MDA-3/4	3/4	5	MDA-7	7	5
MDA-1	1	5	MDA-8	8	5
MDA-11/2	1 1/2	5	MDA-10	10	5
MDA-2	2	5	MDA-15	15	5
MDA-21/2	2 1/2	5	MDA-20	20	5
MDA-3	3	5

125 VAC

MDA-25	25	5	MDA-30	30	5
--------	----	---	--------	----	---

MDA-V SERIES FUSES WITH AXIAL LEAD

Mfr. No.	Rating Amps	Ctn. Qty.	Mfr. No.	Rating Amps	Ctn. Qty.
250 VAC					
MDA-V-1	1	4	MDA-V-10	10	4
MDA-V-2	2	4	MDA-V-12	12	4
MDA-V-3	3	4	MDA-V-15	15	4
MDA-V-4	4	4	MDA-V-20	20	4
MDA-V-5	5	4	MDA-V-30	30	4
MDA-V-8	8	4

ABC SERIES FAST ACTING CERAMIC TUBE FUSES 1/4" LONG x 1/4" DIA.



UL Listed 0-15A, Guide JDYX, File E19180. UL Recognized 20-25A, Guide JDYX2, File E19180. CSA Certified 0-15A, Class 1422-01, File 53787. CSA Certified 20-25A, Class 1422-30, File 53787. Packaged 5/ctn.

Mfr. No.	Rating Amps	AC Inter. Rating Amps	Mfr. No.	Rating Amps	AC Inter. Rating Amps
Rated 250 VAC					
ABC-1/8	1/8	35	ABC-5	5	200
ABC-1/4	1/4	35	ABC-6	6	200
ABC-1/2	1/2	35	ABC-7	7	200
ABC-3/4	3/4	35	ABC-8	8	200
ABC-1	1	35	ABC-9	9	200
ABC-1 1/2	1 1/2	100	ABC-10	10	200
ABC-2	2	100	ABC-12	12	200
ABC-2 1/2	2 1/2	100	ABC-15	15	750
ABC-3	3	100	ABC-20	20	400
ABC-4	4	200
Rated 125 VAC					
ABC-25	25	1000	ABC-30	30	1000