

GMC SERIES MEDIUM TIME-DELAY 5 x 20mm Glass Tube Fuses



Designed to North American Standards. 0.788" Long x 0.197" Dia. glass tube fuse with nickel or silver plated Brass end caps.

Designed to UL 198G and CSA 22.2 N59 standards. UL Listed 0-6.3A, Guide JDYX, File E75865. UL Recognized 7-10A, Guide JDYX2, File 75865. CSA Certified 0-6.3A, Class 1422-01, File 65063. Packaged 5/carton.


Mfr. No.	Amps	Mfr. No.	Amps
Rated 250 VAC, p.f.—0.7 to 0.8			
Breaking Capacity: 35A at 250 VAC; 10000A at 125 VAC			
GMC-63mA	.063	GMC-400mA	.400
GMC-100mA	.100	GMC-500mA	.500
GMC-125mA	.125	GMC-600mA	.600
GMC-150mA	.150	GMC-630mA	.630
GMC-200mA	.200	GMC-750mA	.750
GMC-250mA	.250	GMC-800mA	.800
GMC-300mA	.300	GMC-1A	1.000
GMC-315mA	.315

Mfr. No.	Amps	Mfr. No.	Amps
Rated 250 VAC, p.f.—0.7 to 0.8			
Breaking Capacity: 100A at 250 VAC; 10000A at 125 VAC			
GMC-1.5A	1.500	GMC-2.5A	2.500
GMC-1.6A	1.600	GMC-2.5A	2.500
GMC-2A	2.000	GMC-3.15A	3.150

Mfr. No.	Amps	Mfr. No.	Amps
Rated 125 VAC, p.f.—0.7 to 0.8			
Breaking Capacity: 10000A at 125 VAC			
GMC-3.5A	3.500	GMC-5A	5.000
GMC-4A	4.000	GMC-6A	6.000

Mfr. No.	Amps	Mfr. No.	Amps
Rated 125 VAC, p.f.—1.0			
Breaking Capacity: 200A at 125 VAC			
GMC-7A	7.000	GMC-10A	10.000
GMC-8A	8.000

GMA SERIES FAST-ACTING 5 x 20mm Glass Tube Fuses



Designed to North American Standards. 0.788" Long x 0.197" Dia. glass tube fuse with nickel or silver plated brass end caps.

Designed to UL 198G and CSA 22.2 N59 standards. UL Listed 0-6A, Guide JDYX, File E75865. UL Recognized 7-15A, Guide JDYX2, File 75865. CSA Certified 0-6A, Class 1422-01, File E75865. Packaged 5/carton.

Mfr. No.	Amps	Mfr. No.	Amps
Rated 250 VAC, p.f.—0.7 to 0.8			
Breaking Capacity: 35A at 250 VAC; 1000A at 125 VAC			
GMZ-63mA	.063	GMA-315mA	.315
GMA-100mA	.100	GMA-500mA	.500
GMA-125mA	.125	GMA-600mA	.600
GMA-200mA	.200	GMA-750mA	.750
GMA-250mA	.250	GMA-800mA	.800
GMA-300mA	.300	GMA-1A	1.000


Mfr. No.	Amps	Mfr. No.	Amps
Rated 125 VAC, p.f.—0.7 to 0.8			
Breaking Capacity: 100A at 250 VAC; 1000A at 125 VAC			
GMA-1.25A	1.250	GMA-2A	2.000
GMA-1.5A	1.500	GMA-3A	3.000
GMA-1.6A	1.600

Mfr. No.	Amps	Mfr. No.	Amps
Rated 125 VAC, p.f.—0.7 to 0.8			
Breaking Capacity: 10000A at 125 VAC			
GMA-3.15A	3.150	GMA-5A	5.000
GMA-3.5A	3.500	GMA-6A	6.000
GMA-4A	4.000

Mfr. No.	Amps	Mfr. No.	Amps
Rated 125 VAC, p.f.—1.0			
Breaking Capacity: 200A at 125 VAC			
GMA-7A	7.000	GMA-8A	8.000

Mfr. No.	Amps	Mfr. No.	Amps
Rated 125 VAC, p.f.—1.0			
Breaking Capacity: 150A at 125 VAC			
GMA-10A	10.000	GMA-15A	15.000


GBA SERIES FAST ACTING PIN INDICATING FUSES



Fast acting 1/4" Long x 1/4" Dia. pin indicating fuse. Red pin for high visibility. UL Listed 0-5A at 125 VAC; 10,000AIC, Guide JDYX, File E19180. UL Recognized 6A at 125 VAC, 1000AIC; 8-15A at 150 VAC/VDC, 300AIC, Guide JDYX2, File E19180. CSA Certified, Class 1422-01, File 53787.

Mfr. No.	Amp	Mfr. No.	Amp
GBA-1/2	1/2	GBA-4	4
GBA-3/4	3/4	GBA-5	5
GBA-1	1	GBA-8	8
GBA-1 1/2	1 1/2	GBA-10	10
GBA-2	2	GBA-15	15
GBA-3	3

AGX SERIES FAST ACTING GLASS TUBE FUSES



1" Long x 1/4" Dia. UL Listed 0-5A, Guide JDYX, File E19180. UL Recognized 6-30A, Guide JDYX2, File E19180, CSA Certified 0-5A, Class 1422-01, File 47233. Package 5/carton.

Mfr. No.	Amp	Mfr. No.	Amp
Rated 250 VAC			
AGX-1/200	1/200	AGX-3/6	3/6
AGX-1/100	1/100	AGX-4/10	4/10
AGX-1/62	1/62	AGX-1/2	1/2
AGX-1/48	1/48	AGX-3/4	3/4
AGX-1/10	1/10	ABX-1	1
AGX-1/8	1/8	AGX1 1/4	1 1/4
AGX-3/16	3/16	AGX-1 1/2	1 1/2
AGX-2/10	2/10	AGX-2	2
AGX-1/4	1/4

Mfr. No.	Amp	Mfr. No.	Amp
Rated 125 VAC			
AGX-2 1/2	2 1/2	AGX-4	4
AGX-3	3	AGX-5	5

Mfr. No.	Amp	Mfr. No.	Amp
Rated 32 VAC			
AGX-6	6	AGX-20	20
AGX-7	7	AGX-25	25
AGX-8	8	AGX-30	30
AGX-10	10	AGX-35	35
AGX-15	15	AGX-50	50

GDC SERIES TIME-DELAY LOW BREAKING CAPACITY 5mm x 20mm GLASS TUBE FUSES



Designed to IEC Standards. 0.788" long x 0.197" dia. glass tube fuse with nickel or silver plated brass end caps. Interrupting Rating: 35A at 250 VAC or 10x rated current. UL Recognized 32mA-6.3A, Guide JDYX2, File E75865. SEMKO Approval. VDE Approval, IMQ. British Standard Approval. Designed to IEC (Pub 127) Sheet III. Packaged 5/carton.

Mfr. No.	Rating Amps	I ² t	Max. Voltage Drop mV
GDC-32mA	.032	0.0014	1050
GDC-40mA	.040	0.0034	920
GDC-50mA	.050	0.006	800
GDC-63mA	.063	0.012	760
GDC-80mA	.080	0.015	580
GDC-100mA	.100	0.022	490
GDC-125mA	.125	0.034	390
GDC-160mA	.160	0.052	320
GDC-200mA	.200	0.078	340
GDC-250mA	.250	0.17	270
GDC-315mA	.315	0.41	250
GDC-400mA	.400	0.61	210
GDC-500mA	.500	0.75	168
GDC-630mA	.630	1.3	158
GDC-800mA	.800	3.1	132
GDC-1A	1.000	3.6	85
GDC-1.25A	1.250	7.0	80
GDC-1.60A	1.600	10.0	80
GDC-2A	2.000	17.0	80
GDC-2.5A	2.500	34.0	80
GDC-3.15A	3.150	56.0	75
GDC-4A	4.000	91.0	75
GDC-5A	5.000	133.0	75
GDC-6.3A	6.300	270.0	65