

M-Series Rocker

6

CIRCUIT BREAKERS & FUSES

TERMINAL
1 Push-On
 0.250 Tab (Q.C.)
2¹² Screw 8-32
 w/upturned lugs
3¹² Screw 8-32
 (Bus Type)

ROCKER & LEGEND COLORS
ILLUMINATED ROCKER¹⁰

ROCKER	LEGEND ⁷
A Clear	White
B Red Transparent	White
C Green Transparent	White
D Amber Transparent	White
E Smoke Gray Transparent	White
F White Translucent	Black

BEZEL COLOR/STYLE⁶
WITHOUT ROCKERGUARD
A White
B Black
G Gray
WITH ROCKERGUARD
1 White
2 Black
7 Gray

NON-ILLUMINATED ROCKER
SINGLE COLOR

ROCKER	LEGEND ⁷
1 White	Black
2 Black	White
3 Red	White
8 Orange	Black

VISI-ROCKER
VISI⁶ & LEGEND

	ROCKER ⁶
1 White	[Remainder of rocker same color as bezel]
2 Black	
3 Red	
4 Green	

620

1

H

C

6

7

C

CURRENT COIL RATING ³ (amperes)	
210	0.100
225	0.250
250	0.500
275	0.750
410	1.000
420	2.000
425	2.500
430	3.000
440	4.000
450	5.000
460	6.000
470	7.000
475	7.500
480	8.000
490	9.000
610	10.000
611	11.000
612	12.000
613	13.000
614	14.000
615	15.000
618	18.000
620	20.000
625	25.000

ROCKER ILLUMINATION

A NON-ILLUMINATED
 (single color & Visi-Rocker
 options only)

B⁴ Neon (w/o resistor)
 120VAC/250VAC

C^{4,10} Green Glow Neon
 (w/o resistor)
 120VAC/250VAC

D^{5,10} Red LED (w/o resistor)

E¹⁰ Red LED (w/ resistor)
 4-8 VDC

F¹⁰ Red LED (w/ resistor)
 9-16 VDC

G^{5,10} Green LED (w/o resistor)

H¹⁰ Green LED (w/ resistor)
 4-8 VDC

J¹⁰ Green LED (w/ resistor)
 9-16 VDC

K^{5,10} Amber LED (w/o resistor)

L¹⁰ Amber LED (w/ resistor)
 4-8 VDC

M¹⁰ Amber LED (w/ resistor)
 9-16 VDC

ROCKER LEGEND¹¹

1 No legend
 (Single color or
 illuminated
 rocker options
 only)

2 ON-OFF
 Vertical

3 ON-OFF
 Horizontal

4 I-O
 Vertical

5 I-O
 Horizontal

6 Dual
 Vertical

7 Dual
 Horizontal

AGENCY APPROVAL¹³

A W/O Approval

B UL Recognized

C UL Recognized;
 CSA Certified

D UL Recognized;
 CSA and VDE
 Certified