

C-Series Rocker

Ordering Scheme

PROD CODE
C

POLES
1 One
2^a Two
3^a Three

AUXILIARY SWITCH⁴
0 w/o Aux Switch
2 S.P.D.T., 0.110 Q.C. Term.
3 S.P.D.T., 0.139 Solder Lug
4 S.P.D.T., 0.110 Q.C. Term.
(Gold Contacts)
8 S.P.S.T., 0.187 Q.C. Term.



ROCKER STYLE DESCRIPTIONS			
	INDICATE "ON"	INDICATE "OFF"	SINGLE COLOR
VERTICAL STYLE	CODE "C"	CODE "F"	CODE "J"
HORIZONTAL STYLE	CODE "D"	CODE "G"	CODE "K"

FIG. A

C F 1 - B 0 - 24 -

ACTUATOR¹ VISI-ROCKER

C Indicate ON;Vertical Legend
D Indicate ON;Horizontal Legend
F Indicate OFF;Vertical Legend
G Indicate OFF;Horizontal Legend

SINGLE COLOR ROCKER

J Vertical Legend
K Horizontal Legend

PUSH-TO-RESET (VISI-ROCKER)

N Indicate OFF;Vertical Legend
O Indicate OFF;Horizontal Legend

PUSH-TO-RESET

(SINGLE COLOR ROCKER)

R Vertical Legend
U Horizontal Legend

CIRCUIT

A³ Switch Only (No Coil)
B Series Trip (Current)
C Series Trip (Voltage)
D Shunt Trip (Current)
E Shunt Trip (Voltage)
F Relay Trip (Current)
G Relay Trip (Voltage)

DUAL COIL AVAILABLE;
CONSULT FACTORY.

FREQUENCY AND DELAY

03 DC 50/60 Hz. When delay is not applicable, i.e. switch only circuit option.
10^{5a} DC Instantaneous
11 DC Ultra Short
12 DC Short
14 DC Medium
16 DC Long
20^{5a} 50/60Hz Instantaneous
21 50/60Hz Ultra Short
22 50/60Hz Short
24 50/60Hz Medium
26 50/60Hz Long
32 DC, 50/60Hz Short
34 DC, 50/60Hz Medium
36 DC, 50/60Hz Long
42^{5b} 50/60Hz Short (Hi-Inrush)
44^{5b} 50/60Hz Medium (Hi-Inrush)
46^{5b} 50/60Hz Long (Hi-Inrush)
52^{5b} DC Short, Hi-Inrush
54^{5b} DC Medium, Hi-Inrush
56^{5b} DC Long, Hi-Inrush