

6

CIRCUIT BREAKERS &

FUSES

CURRENT RATING ⁶	
AMPERES	
210	0.100
225	0.250
250	0.500
275	0.750
410	1.000
425	2.500
450	5.000
475	7.500
610	10.000
615	15.000
620	20.000
625	25.000
630	30.000
635	35.000
640	40.000
650	50.000
660	60.000
670	70.000
680	80.000
690	90.000
695	95.000
810	100.000

ACTUATOR STYLE & COLOR HANDLE ^{5c}		
HANDLE	LEGEND	
1	White	Dual (Black)
2	Black	Dual (White)
3	Red	Dual (White)
6	Yellow	Dual (Black)
VISI-ROCKER ^{1c, 5b, 5c}		
VISI-COLOR LEGEND		
1	White	Dual (White)
3	Red	Dual (Red)
4	Green	Dual (Green)
SINGLE COLOR ROCKER ^{1e, 5c}		
ROCKER		LEGEND
2	Black	Dual (White)
3	Red	Dual (White)
4	Green	Dual (White)
5	Blue	Dual (White)
6	Yellow	Dual (Black)
7	Gray	Dual (Black)
8	Orange	Dual (Black)

MAXIMUM APP. RATING	
B	125 DC
C ^{2b}	120/240 AC
D ^{2b}	240 AC
K	120 AC
M	80 DC

620 - 1 2 1 - K G

TERMINAL ^{5a}	
1	10-32 THD. Stud, .625 long
2	10-32 Screw
3	1/4-20 THD. Stud, .675 long

MOUNTING/BARRIERS/VOLTAGE		
MOUNTING INSERT		ACTUATOR
1	6-32 x 0.195 inches	Handle
2	ISO M3 x 5mm	Handle
A	6-32 X 0.195 inches	Rocker w/ standard bezel
D	ISO M3 x 5mm	Rocker with Rockerguard
C	ISO M3 x 5mm	Rocker w/ standard bezel
B	6-32 x 0.195 inches	Rocker with Rockerguard

AGENCY APPROVAL ⁷	
A	W/O Approval
G	UL489 Listed CSA Certified

ROCKER STYLE DESCRIPTIONS			
	INDICATE "ON"	INDICATE "OFF"	SINGLE COLOR
VERTICAL STYLE	CODE "C" 	CODE "F" 	CODE "J"
	INDICATE COLOR LOCATION		
HORIZONTAL STYLE	CODE "D" 	CODE "G" 	CODE "K"

FIG. A