

## Ordering Information

### RM-RELAY

Ex. RM    2 — L2 — 24V

| Contact arrangement | Operating function                                                   | Coil voltage (DC)         |
|---------------------|----------------------------------------------------------------------|---------------------------|
| 2:2 Form C          | Nil: Single side stable<br>L: 1 coil latching<br>L2: 2 coil latching | 3, 4.5, 5, 6, 9, 12, 24 V |

Note: Standard packing; Carton: 20 pcs. Case 200 pcs.

### RP-RELAY

Ex. RP    1 — H — 3V

| Contact arrangement | Terminal shape                                                | Coil voltage (DC)              |
|---------------------|---------------------------------------------------------------|--------------------------------|
| 1:1 Form C          | Nil: Standard PC board terminal<br>H: Self-clinching terminal | 1.5, 3, 4.5, 5, 6, 9, 12, 24 V |

Note: Standard packing; Carton: 50 pcs. Case 1,000 pcs.

### HY-RELAY

Ex. HY    1    Z — 3V

| Contact arrangement | Sensitivity                                        | Coil voltage (DC)              |
|---------------------|----------------------------------------------------|--------------------------------|
| 1: 1 Form C         | Nil: High sensitivity 150 mW<br>Z: Standard 200 mW | 1.5, 3, 4.5, 5, 6, 9, 12, 24 V |

Standard packing; Carton: 100 pcs. Case 500 pcs.

### DK-RELAY

Ex. DK    1a — L2 — 12V

| Contact arrangement                                     | Operating function                             | Coil voltage        |
|---------------------------------------------------------|------------------------------------------------|---------------------|
| 1a: 1 Form A<br>2a: 2 Form A<br>1a1b: 1 Form A 1 Form B | Nil: Single side stable<br>L2: 2 coil latching | 3, 5, 6, 9, 12, 24V |

Note: Standard packing Carton: 50 pcs.; Case: 500 pcs.

### S-RELAY

Ex. S    2    EB — L2 — 48V

| Contact arrangement                                         | Classification of type | Operating function                             | Coil voltage (DC)     |
|-------------------------------------------------------------|------------------------|------------------------------------------------|-----------------------|
| 2: 2 Form A 2 Form B<br>3: 3 Form A 1 Form B<br>4: 4 Form A | EB: Amber sealed type  | Nil: Single side stable<br>L2: 2 coil latching | 3, 5, 6, 12, 24, 48 V |

(Notes) 1. Standard packing Carton: 50 pcs. Case: 500 pcs.

2. 1 coil latching also available as option. Contact our sales office for details.

# 7 RELAYS