

Ordering Information

LA-RELAY

Ex. A LA 2 P F 12

Product name	Contact arrangement	Contact capacity	Protective construction	Coil voltage(V DC)
LA	2: 2 Form A	Nil: 3A P: 5A TV-3	F: Flux-resistant type	12, 24

Notes: 1. Standard packing Carton: 100 pcs. Case: 500 pcs.
2. 4.5V, 5V, 9V and 18V DC types are also available. Please consult us for details.

LD-RELAY

Ex. A LD 1 12

Product name	Contact arrangement	Coil voltage(V DC)
LD	1: 1 Form A	4H: 4.5, 09: 9, 24: 24 05: 5, 12: 12 06: 6, 18: 18

Note: Standard packing; Tube: 50 pcs. Case: 1,000 pcs.

PA-RELAY

Ex. PA 1a — 12V

Contact arrangement	Coil voltage (DC)
1a: 1 Form A	5, 6, 9, 12, 18, 24V

Note: Standard packing; Tube: 25 pcs.; Case: 1,000 pcs.

JQ-RELAY

Ex. JQ 1a P — 12 V

Contact arrangement	Contact capacity	Coil voltage (DC)
1a: 1 Form A 1: 1 Form C	Nil: Standard P: High capacity	3, 5, 6, 9, 12, 18, 24, 48* V

* Available only for 1 Form C type

JT-N/JT-RELAY

JTN	1a	E	TMP	F	DC12V
Contact arrangement	Protective construction	Mounting classification	Coil insulation	Coil voltage	
1a: 1 Form A 1: 1 Form C	G: Dust cover type E: Sealed type	PA: PCB type (UL508) TMP: TMP type (UL508)	F: Class F	DC 5, 6, 9, 12, 15, 18, 24 V	

JT	1a	DC12V
Contact arrangement	Coil voltage	
1a: 1 Form A 1: 1 Form C	DC 5, 6, 9, 12, 15, 18, 24 V	

Note: DC rating is available for class A type. For the class A type, please consult us.

7 RELAYS