

ORDERING INFORMATION								
VDE APPROVED DESIGN		Typical Part No. >	KUIP KUGP	-11	A	1	5	-120
1. BASIC SERIES AND TYPE: KUIP = Enclosed relay designed for General VDE 0435.* KUGP = Enclosed relay with 3 mm open contact spacing. (Form A and Form X arrangements only)*								
2. CONTACT ARRANGEMENT: 1 = 1 Form A (SPST-NO) 5 = 1 Form C (SPDT)* 7 = 2 Form A (DPST-NO) 11 = 2 Form C (DPDT)* 14 = 3 Form C (3PDT)*								
3. COIL INPUT: A = AC, 50/60 Hz.* D = DC*								
4. MOUNTINGS: 1 = PLAIN CASE, SOCKET MOUNT.* T = TOP FLANGE CASE.* 5 = BRACKET MOUNT CASE.*								
5. TERMINAL & CONTACT MATERIAL: 3 = .047" (1.19 mm) printed circuit board; silver. 5 = .187" (4.75 mm) quick connect/solder; silver-cadmium oxide.*								
6. COIL VOLTAGE: To 240VAC, 50/60 Hz. or 110VDC. * Options included in VDE file.		See coil data tables.						

STOCK ITEMS – The following items are normally maintained in stock for immediate delivery.		
KUGP-7D55-24	KUIP-11D55-12	KUIP-14D15-12
KUIP-5A55-120	KUIP-11D55-24	KUIP-14D15-24
KUIP-11A55-120	KUIP-14A15-120	

ORDERING INFORMATION																				
HIGH VOLTAGE DC SWITCHING		Typical Part No. >	KUEP	-3	A	1	5	-120												
1. BASIC SERIES AND TYPE: KUEP = Enclosed relay with magnetic blow-outs.																				
2. CONTACT ARRANGEMENT: 3 = 1X (SPST-NO-DM) 7 = 2A (DPST-NO) 11 = 2C (DPDT)																				
3. COIL INPUT: A = AC 50/60 Hz. D = DC																				
4. MOUNTINGS:																				
<table border="1"> <thead> <tr> <th>Type</th> <th>KUE</th> <th>KUEP</th> </tr> </thead> <tbody> <tr> <td>1 = PLAIN CASE;</td> <td></td> <td>G = with indicator lamp.*</td> </tr> <tr> <td>3 = with indicator lamp.*</td> <td></td> <td>T = TOP FLANGE CASE.</td> </tr> <tr> <td>5 = BRACKET MOUNT CASE;</td> <td></td> <td></td> </tr> </tbody> </table>		Type	KUE	KUEP	1 = PLAIN CASE;		G = with indicator lamp.*	3 = with indicator lamp.*		T = TOP FLANGE CASE.	5 = BRACKET MOUNT CASE;									
Type	KUE	KUEP																		
1 = PLAIN CASE;		G = with indicator lamp.*																		
3 = with indicator lamp.*		T = TOP FLANGE CASE.																		
5 = BRACKET MOUNT CASE;																				
*Indicator lamps are available on models with the following coils: 6-24VAC and DC, 110VDC and 120-240VAC. Only models with 120-240VAC coils are UL recognized.																				
5. TERMINAL & CONTACT MATERIAL: 5 = .187" (4.75 mm) quick connect/solder; silver-cadmium-oxide. 7 = .047" (1.19 mm) printed circuit; silver-cadmium-oxide.																				
6. COIL VOLTAGE: To 240VAC, 50/60 Hz. or 110VDC.																				

STOCK ITEMS – The following items are normally maintained in stock for immediate delivery.		
KUEP-3A15-120	KUEP-3D15-110	KUEP-11A15-120
KUEP-3D15-12	KUEP-7D15-12	KUEP-11D15-12
KUEP-3D15-24	KUEP-7D15-24	KUEP-11D15-24