

# 7 RELAYS

**ORDERING INFORMATION**

Typical Part No. > **PRD -7 A Y 0 -120**

**1. TYPE:**

PRD = Open relay.  
PRDA = Open relay with aux. SPDT snap-action switch.

**2. MAIN CONTACT ARRANGEMENT:**

1 = SPST-NO  
2 = SPST-NC  
3 = SPST-NO-DM  
5 = SPDT  
7 = DPST-NO  
7V = DPST-NO with 3mm contact gap.  
11 = DPDT

**3. COIL INPUT:**

A = 50/60 Hz. D = DC

**4. MAIN CONTACT MATERIAL:**

Y = .312" (7.92mm) dia. silver  
G = .312" (7.92mm) dia. silver cad.-oxide  
†H = Silver w/magnetic blow out  
†J = Silver cad.-oxide w/magnetic blow out  
N = Tungsten stationary & silver cad.-oxide movable. Code 1,2,5,7,8 & 11 only

†Available with Code 3,7,8,6X.  
& 11 contact arrangement only.

**5. TERMINATION:**

CODE	PRD			PRDA (With Aux. SPDT Snap-Action Switch)		
	0	1	3	A	B	L
MAIN	Screw Term.	.250" (6.35mm) QC	Screw Term.	Screw Term.	250" (6.35mm) QC	Twin .250" (6.35mm) QC
COIL	Screw Term.	.250" (6.35mm) QC	.250" (6.35mm) QC	Screw Term.	250" (6.35mm) QC	.250" (6.35mm) QC
AUX. SWITCH				Screw Term.	250" (6.35mm) QC	.250" (6.35mm) QC

**6. COIL VOLTAGE:**

6, 12, 24, 110VDC  
6, 12, 24, 120, 240, 480VAC, 50/60 Hz. Coil voltages are available to 125VDC and 600VAC.

**OUTLINE DIMENSIONS**

