

Status Indicator

Light Frame Assembly Kits With Top Strobe

SK Version W/18" Leads & One Top Mounted Strobe			SKT Version W/Terminal Block & One Top Mounted Strobe	
Frame Height	Voltage	Catalog No.	Frame Height	Catalog No.
1	240 VAC	SK1-240AC-S	1	SKT1-240AC-S
1	120 VAC	SK1-120AC-S	1	SKT1-120AC-S
2	240 VAC	SK2-240AC-S	2	SKT2-240AC-S
2	120 VAC	SK2-120AC-S	2	SKT2-120AC-S
3	240 VAC	SK3-240AC-S	3	SKT3-240AC-S
3	120 VAC	SK3-120AC-S	3	SKT3-120AC-S
4	240 VAC	SK4-240AC-S	4	SKT4-240AC-S
4	120 VAC	SK4-120AC-S	4	SKT4-120AC-S
5	240 VAC	SK5-240AC-S	5	SKT5-240AC-S
5	120 VAC	SK5-120AC-S	5	SKT5-120AC-S
6	240 VAC	SK6-240AC-S	6	SKT6-240AC-S
6	120 VAC	SK6-120AC-S	6	SKT6-120AC-S



13

P-I-L-I-G-H-T-S & I-N-D-I-C-A-T-O-R-S

Separate Lenses

Color	Catalog No.
Red	KS-R
Amber	KS-A
Green	KS-G
Clear	KS-C
Blue	KS-B
White	KS-W

* One Lens required for every height of frame.



Separate Lamps (AC or DC)

Voltage	Catalog No.
6 VAC	KRB09-6
12 VAC	KRB09-12
24 VAC	KRB09-24
48 VAC	KRB09-48
120 VAC	KRB09-120
240 VAC	KRB09-240

* One Lamp required for every height of frame.

STAK-LITE Options

Description	Catalog No.
3/4" Conduit Mounting Flange ¹	KSH
Extended Tubing - 4"	KSLP04
Extended Tubing - 8"	KSLP08
Extended Tubing - 16"	KSLP16

¹ The standard unit can be panel mounted directly to any flat surface through two 5/16" DIA. holes. To elevate the unit, use standard 3/4" conduit or JCC Extended Tubing, and the KSLH mounting flange.

