

Character Modules

Standard Operating Temp 0~50°C

Standard Storage Temp -20~70°C

Includes LED Backlight

Driving Method is STN Transflective

View Angle is 6:00

13

P
I
L
O
T
L
I
G
H
T
S
&
I
N
D
I
C
A
T
O
R
S

Lumex Part Number	Overall Size w/Backlight	Viewing Area	Character Size	Pixel Size	Fig.
LCM-S01601DSF	80.00 x 36.00 x 12.70	66.00 x 16.00	3.07 x 6.56	0.55 x 0.75	57
LCM-S01602DSF/A	80.00 x 36.00 x 12.70	66.00 x 16.00	2.96 x 5.56	0.56 x 0.66	58
LCM-S01602DSF/B	84.00 x 44.00 x 12.70	66.00 x 16.00	2.96 x 5.56	0.56 x 0.66	59
LCM-S01604DSF	87.00 x 60.00 x 12.70	62.00 x 25.60	2.95 x 4.75	0.55 x 0.55	60
LCM-S02002DSF	116.00 x 37.00 x 12.70	85.00 x 18.60	3.20 x 5.55	0.60 x 0.65	61
LCM-S02004DSF	98.00 x 60.00 x 12.70	77.00 x 26.30	2.95 x 4.75	0.55 x 0.55	62
LDM-S04002DSF	182.00 x 33.50 x 12.70	154.00 x 15.30	3.20 x 5.55	0.60 x 0.65	63
LDM-S04004DSF	190.00 x 54.00 x 14.50	149.00 x 29.50	2.78 x 4.89	0.50 x 0.55	64

