


- 80mm to 225mm Sizes
- 19 to 607 CFM
- Excellent Efficiency
- Long Life Operation
- Axial Air Flow Pattern
- Available in FAN TRAYS



| Model                                                        | Bearing | Volts   | Watts | CFM | dBA | Max C° | Connect   |
|--------------------------------------------------------------|---------|---------|-------|-----|-----|--------|-----------|
| 79roundx38mm (3.1 x 1.5inch), AC (60/50Hz), 5oz, UL/CSA/VDE  |         |         |       |     |     |        |           |
| 900                                                          | Sleeve  | 24      | 2.7   | 19  | 75  | 85     | Terminals |
| 950                                                          | Sleeve  | 24      | 7     | 39  | 35  | 70     | Leads     |
| 62roundx38mm (no housing), AC (60/50Hz), 4oz, UL/CSA/VDE     |         |         |       |     |     |        |           |
| 971TR                                                        | Sleeve  | 12      | 7     | 15  | 17  | 70     | Leads     |
| 970T                                                         | Sleeve  | 24      | 7     | 21  | 29  | 70     | Leads     |
| 80x80x38mm (3.2 x 1.5inch), AC (60/50Hz), 17oz, UL/CSA/VDE   |         |         |       |     |     |        |           |
| 8830N                                                        | Sleeve  | 115     | 8     | 21  | 21  | 80     | Leads     |
| 8880N                                                        | Sleeve  | 230     | 8     | 21  | 21  | 80     | Leads     |
| 8800N                                                        | Sleeve  | 115     | 11    | 28  | 28  | 70     | Leads     |
| 8850N                                                        | Sleeve  | 230     | 11    | 28  | 28  | 70     | Leads     |
| 8500N                                                        | Sleeve  | 115     | 11    | 36  | 34  | 75     | Leads     |
| 8500DP                                                       | Sleeve  | 115     | 11    | 36  | 34  | 75     | Leads     |
| 8550N                                                        | Sleeve  | 230     | 11    | 36  | 34  | 75     | Leads     |
| 8506N                                                        | Ball    | 115     | 11    | 36  | 35  | 95     | Leads     |
| 8556N                                                        | Ball    | 230     | 11    | 36  | 35  | 95     | Leads     |
| 80x80x38mm (3.2 x 1.5inch), AC (60/50Hz), 17oz, UL/CSA/VDE   |         |         |       |     |     |        |           |
| 8830A                                                        | Sleeve  | 115     | 8     | 20  | 29  | 80     | Leads     |
| 8880A                                                        | Sleeve  | 230     | 8     | 20  | 29  | 80     | Leads     |
| 8800A                                                        | Sleeve  | 115     | 11    | 27  | 34  | 70     | Leads     |
| 8850A                                                        | Sleeve  | 230     | 11    | 27  | 34  | 70     | Leads     |
| 8500A                                                        | Sleeve  | 115     | 11    | 34  | 41  | 75     | Leads     |
| 8550A                                                        | Sleeve  | 230     | 11    | 34  | 41  | 75     | Leads     |
| 8506A                                                        | Ball    | 115     | 11    | 34  | 42  | 95     | Leads     |
| 8556A                                                        | Ball    | 230     | 11    | 34  | 42  | 95     | Leads     |
| 80x80x38mm (3.2 x 1.5inch), AC (60/50Hz), 17oz, UL/CSA/VDE   |         |         |       |     |     |        |           |
| 8830V                                                        | Sleeve  | 115     | 8     | 21  | 21  | 80     | Terminals |
| 8880V                                                        | Sleeve  | 230     | 8     | 21  | 21  | 80     | Terminals |
| 8800V                                                        | Sleeve  | 115     | 11    | 28  | 28  | 70     | Terminals |
| 8850V                                                        | Sleeve  | 230     | 11    | 28  | 28  | 70     | Terminals |
| 8500V                                                        | Sleeve  | 115     | 11    | 36  | 34  | 75     | Terminals |
| 8550V                                                        | Sleeve  | 230     | 11    | 36  | 34  | 75     | Terminals |
| 8506V                                                        | Ball    | 115     | 11    | 36  | 35  | 95     | Terminals |
| 8556V                                                        | Ball    | 230     | 11    | 36  | 35  | 95     | Terminals |
| 8560VW                                                       | Sleeve  | 115/230 | 1136  | 34  | 70  | Leads  |           |
| 76roundx37mm (no housing), AC (60/50Hz), 13oz, UL/CSA/VDE    |         |         |       |     |     |        |           |
| 8830TA                                                       | Sleeve  | 115     | 8     | 15  | 18  | 80     | Leads     |
| 8880TA                                                       | Sleeve  | 230     | 8     | 15  | 18  | 80     | Leads     |
| 8800TA                                                       | Sleeve  | 115     | 11    | 20  | 23  | 70     | Leads     |
| 8850TA                                                       | Sleeve  | 230     | 11    | 20  | 23  | 70     | Leads     |
| 8500TA                                                       | Sleeve  | 115     | 11    | 27  | 30  | 75     | Leads     |
| 8550TA                                                       | Sleeve  | 230     | 11    | 27  | 30  | 75     | Leads     |
| 8506TA                                                       | Ball    | 115     | 11    | 27  | 31  | 95     | Leads     |
| 8556TA                                                       | Ball    | 230     | 11    | 27  | 31  | 95     | Leads     |
| 76roundx37mm (no housing), AC (60/50Hz), 13oz, UL/CSA/VDE    |         |         |       |     |     |        |           |
| 8830TV                                                       | Sleeve  | 115     | 8     | 16  | 18  | 80     | Leads     |
| 8880TV                                                       | Sleeve  | 230     | 8     | 16  | 18  | 80     | Leads     |
| 8800TV                                                       | Sleeve  | 115     | 11    | 21  | 24  | 70     | Leads     |
| 8850TV                                                       | Sleeve  | 230     | 11    | 21  | 24  | 70     | Leads     |
| 8500TV                                                       | Sleeve  | 115     | 11    | 28  | 32  | 75     | Leads     |
| 8550TV                                                       | Sleeve  | 230     | 11    | 28  | 32  | 75     | Leads     |
| 8506TV                                                       | Ball    | 115     | 11    | 28  | 33  | 95     | Leads     |
| 8556TV                                                       | Ball    | 230     | 11    | 28  | 33  | 95     | Leads     |
| 92x92x25mm (3.6 x 1.0inch), AC (60/50Hz), 10oz, UL/CSA/VDE   |         |         |       |     |     |        |           |
| 3906L                                                        | Ball    | 115     | 5     | 23  | 27  | 80     | Terminals |
| 3956L                                                        | Ball    | 230     | 5     | 23  | 27  | 80     | Terminals |
| 3906M                                                        | Ball    | 115     | 5     | 31  | 34  | 80     | Terminals |
| 3956M                                                        | Ball    | 230     | 5     | 31  | 34  | 80     | Terminals |
| 3906                                                         | Ball    | 115     | 9     | 41  | 40  | 80     | Terminals |
| 3956                                                         | Ball    | 230     | 9     | 41  | 40  | 80     | Terminals |
| 119x119x25mm (4.7 x 1.0inch), AC (60/50Hz), 11oz, UL/CSA/VDE |         |         |       |     |     |        |           |
| 9906L                                                        | Ball    | 115     | 8     | 59  | 35  | 80     | Terminals |
| 9956L                                                        | Ball    | 230     | 8     | 59  | 35  | 80     | Terminals |
| 9906M                                                        | Ball    | 115     | 8     | 65  | 37  | 80     | Terminals |
| 9956M                                                        | Ball    | 230     | 8     | 65  | 37  | 80     | Terminals |
| 9906                                                         | Ball    | 115     | 12    | 79  | 42  | 70     | Terminals |
| 9956                                                         | Ball    | 230     | 12    | 79  | 42  | 70     | Terminals |
| 119x119x38mm (4.7 x 1.5inch), AC (60/50Hz), 18oz, UL/CSA/VDE |         |         |       |     |     |        |           |
| 4800N                                                        | Sleeve  | 115     | 9     | 57  | 32  | 75     | Terminals |
| 4850N                                                        | Sleeve  | 230     | 9     | 57  | 32  | 75     | Terminals |
| 4530N                                                        | Sleeve  | 115     | 16    | 89  | 45  | 65     | Terminals |
| 4580N                                                        | Sleeve  | 230     | 16    | 89  | 45  | 65     | Terminals |
| 4500N                                                        | Sleeve  | 115     | 15    | 100 | 48  | 65     | Terminals |
| 4550N                                                        | Sleeve  | 230     | 15    | 100 | 48  | 65     | Terminals |
| 119x119x38mm (4.7 x 1.5inch), AC (60/50Hz), 18oz, UL/CSA/VDE |         |         |       |     |     |        |           |
| 4800AX                                                       | Sleeve  | 115     | 9     | 57  | 32  | 75     | Terminals |
| 4850AX                                                       | Sleeve  | 230     | 9     | 57  | 32  | 75     | Terminals |
| 4530AX                                                       | Sleeve  | 115     | 16    | 89  | 45  | 65     | Terminals |
| 4580AX                                                       | Sleeve  | 230     | 16    | 89  | 45  | 65     | Terminals |
| 4500AX                                                       | Sleeve  | 115     | 15    | 100 | 48  | 65     | Terminals |
| 4550AX                                                       | Sleeve  | 230     | 15    | 100 | 48  | 65     | Terminals |

| Model                                                          | Bearing | Volts   | Watts | CFM | dBA | Max C° | Connect.   |
|----------------------------------------------------------------|---------|---------|-------|-----|-----|--------|------------|
| 119x119x38mm (4.7 x 1.5inch), AC (60/50Hz), 19oz, UL/CSA/VDE   |         |         |       |     |     |        |            |
| 4840N                                                          | Sleeve  | 115     | 10    | 50  | 26  | 80     | Terminals  |
| 4890N                                                          | Sleeve  | 230     | 10    | 50  | 26  | 80     | Terminals  |
| 4600N                                                          | Sleeve  | 115     | 18    | 106 | 50  | 60     | Terminals  |
| 4600X                                                          | Sleeve  | 115     | 18    | 106 | 50  | 60     | Terminals  |
| 4600XP                                                         | Sleeve  | 115     | 18    | 106 | 50  | 60     | Terminals  |
| 4650N                                                          | Sleeve  | 230     | 18    | 106 | 50  | 60     | Terminals  |
| 4650X                                                          | Sleeve  | 230     | 18    | 106 | 50  | 60     | Terminals  |
| 4606N                                                          | Ball    | 115     | 18    | 106 | 51  | 90     | Terminals  |
| 4606X                                                          | Ball    | 115     | 18    | 106 | 51  | 90     | Terminals  |
| 4656N                                                          | Ball    | 230     | 18    | 106 | 51  | 90     | Terminals  |
| 4656X                                                          | Ball    | 230     | 18    | 106 | 51  | 90     | Terminals  |
| 4660N                                                          | Sleeve  | 115/230 | 18    | 106 | 51  | 60     | Leads      |
| 4624N                                                          | Sleeve  | 24      | 18    | 106 | 50  | 60     | Terminals  |
| 119x119x38mm (4.7 x 1.5inch), AC (60/50Hz), 18oz, UL/CSA/VDE   |         |         |       |     |     |        |            |
| 4600AX                                                         | Sleeve  | 115     | 18    | 106 | 50  | 60     | Terminals  |
| 4650AX                                                         | Sleeve  | 230     | 18    | 106 | 50  | 60     | Terminals  |
| 4606AX                                                         | Ball    | 115     | 18    | 106 | 51  | 90     | Terminals  |
| 4656AX                                                         | Ball    | 230     | 18    | 106 | 51  | 90     | Terminals  |
| 119x119x38mm (4.7 x 1.5inch), AC (60/50Hz), 18oz, UL/CSA/VDE   |         |         |       |     |     |        |            |
| 4600VX                                                         | Sleeve  | 115     | 18    | 106 | 45  | 60     | Terminals  |
| 4650VX                                                         | Sleeve  | 230     | 18    | 106 | 45  | 60     | Terminals  |
| 4606VX                                                         | Ball    | 115     | 18    | 106 | 45  | 90     | Terminals  |
| 4656VX                                                         | Ball    | 230     | 18    | 106 | 45  | 90     | Terminals  |
| 119x119x38mm (4.7 x 1.5inch), AC (60/50Hz), 19oz, UL/CSA/VDE   |         |         |       |     |     |        |            |
| 4800Z                                                          | Sleeve  | 115     | 10    | 56  | 28  | 75     | Terminals  |
| 4800ZW                                                         | Sleeve  | 115     | 10    | 56  | 28  | 75     | Leads      |
| 4850Z                                                          | Sleeve  | 230     | 10    | 56  | 28  | 75     | Terminals  |
| 4850ZW                                                         | Sleeve  | 230     | 10    | 56  | 28  | 75     | Leads      |
| 4530Z                                                          | Sleeve  | 115     | 12    | 71  | 33  | 65     | Terminals  |
| 4530ZW                                                         | Sleeve  | 115     | 12    | 71  | 33  | 65     | Leads      |
| 4580Z                                                          | Sleeve  | 230     | 12    | 71  | 33  | 65     | Terminals  |
| 4580ZW                                                         | Sleeve  | 230     | 12    | 71  | 33  | 65     | Leads      |
| 4590ZW                                                         | Sleeve  | 115/230 | 12    | 71  | 33  | 65     | Leads      |
| 4600Z                                                          | Sleeve  | 115     | 18    | 106 | 45  | 60     | Terminals  |
| 4600ZW                                                         | Sleeve  | 115     | 18    | 106 | 45  | 60     | Leads      |
| 4650Z                                                          | Sleeve  | 230     | 18    | 106 | 45  | 60     | Terminals  |
| 4650ZW                                                         | Sleeve  | 230     | 18    | 106 | 45  | 60     | Leads      |
| 4606Z                                                          | Ball    | 115     | 18    | 106 | 45  | 75     | Terminals  |
| 4606ZW                                                         | Ball    | 115     | 18    | 106 | 45  | 75     | Leads      |
| 4656Z                                                          | Ball    | 230     | 18    | 106 | 45  | 75     | Terminals  |
| 4656ZW                                                         | Ball    | 230     | 18    | 106 | 45  | 75     | Leads      |
| 4624ZW                                                         | Ball    | 24      | 18    | 106 | 45  | 75     | Leads      |
| 113roundx37mm (no housing), AC (60/50Hz), 15oz, UL/CSA/VDE     |         |         |       |     |     |        |            |
| 4600TA                                                         | Sleeve  | 115     | 18    | 87  | 43  | 60     | Leads      |
| 4650TA                                                         | Sleeve  | 230     | 18    | 87  | 43  | 60     | Leads      |
| 4606TA                                                         | Ball    | 115     | 18    | 87  | 44  | 90     | Leads      |
| 4656TA                                                         | Ball    | 230     | 18    | 87  | 44  | 90     | Leads      |
| 112roundx37mm (no housing), AC (60/50Hz), 15oz, UL/CSA/VDE     |         |         |       |     |     |        |            |
| 4600TZ                                                         | Sleeve  | 115     | 18    | 82  | 45  | 60     | Leads      |
| 4650TZ                                                         | Sleeve  | 230     | 18    | 82  | 45  | 60     | Leads      |
| 4606TZ                                                         | Ball    | 115     | 18    | 82  | 45  | 85     | Leads      |
| 4656TZ                                                         | Ball    | 230     | 18    | 82  | 45  | 85     | Leads      |
| 127x127x38mm 5.0 x 1.5inch), AC (60/50Hz), 20oz, UL/CSA/VDE    |         |         |       |     |     |        |            |
| W2K121-AB11-13                                                 | Ball    | 115     | 14    | 106 | 41  | 65     | Terminals  |
| W2K121-AB11-39                                                 | Sleeve  | 115     | 14    | 106 | 41  | 55     | Terminals  |
| W2K121-AB07-13                                                 | Ball    | 230     | 14    | 106 | 41  | 65     | Terminals  |
| W2K121-AB07-39                                                 | Sleeve  | 230     | 14    | 106 | 41  | 55     | Terminals  |
| W2K121-AA15-13                                                 | Ball    | 115     | 17    | 121 | 47  | 75     | Terminals  |
| W2K121-AA15-39                                                 | Sleeve  | 115     | 17    | 121 | 47  | 75     | Terminals  |
| W2K121-AA15-01                                                 | Ball    | 115     | 17    | 121 | 47  | 75     | Leads      |
| W2K121-AA15-03                                                 | Sleeve  | 115     | 17    | 121 | 47  | 75     | Leads      |
| W2K121-AA01-13                                                 | Ball    | 230     | 17    | 121 | 47  | 75     | Terminals  |
| W2K121-AA01-39                                                 | Sleeve  | 230     | 17    | 121 | 47  | 75     | Terminals  |
| W2K121-AA01-01                                                 | Ball    | 230     | 17    | 121 | 47  | 75     | Leads      |
| W2K121-AA01-03                                                 | Sleeve  | 230     | 17    | 121 | 47  | 75     | Leads      |
| 135x135x38mm (5.3 x 1.5inch), AC (60/50Hz), 28oz, UL/CSA/VDE   |         |         |       |     |     |        |            |
| 5606S                                                          | Ball    | 115     | 26    | 159 | 50  | 80     | Terminals  |
| 5656S                                                          | Ball    | 230     | 26    | 159 | 50  | 80     | Terminals  |
| 150x172x38mm (5.9x6.8x1.5inch), AC (60/50Hz), 32oz, UL/CSA/VDE |         |         |       |     |     |        |            |
| W2E142-CC13-16                                                 | Ball    | 115     | 16    | 175 | 54  | 75     | Terminals  |
| W2E142-CC15-16                                                 | Ball    | 230     | 16    | 175 | 54  | 75     | Terminals  |
| W2E142-BB05-01                                                 | Ball    | 115     | 26    | 236 | 62  | 75     | Terminals  |
| W2E142-BB05-87                                                 | Ball    | 115     | 26    | 236 | 62  | 75     | T, HallEff |
| W2E142-BB01-01                                                 | Ball    | 230     | 26    | 236 | 62  | 75     | Terminals  |
| W2E142-BB01-87                                                 | Ball    | 230     | 26    | 236 | 62  | 75     | T, HallEff |
| 150x172x55mm (5.9x6.4x2.2inch), AC (60/50Hz), 42oz, UL/CSA/VDE |         |         |       |     |     |        |            |
| W2S130-AA25-01                                                 | Ball    | 115     | 42    | 233 | 52  | 75     | Leads      |
| W2S130-AA25-44                                                 | Ball    | 115     | 42    | 233 | 52  | 75     | Terminals  |
| W2S130-AA25-51                                                 | Ball    | 115     | 42    | 233 | 52  | 75     | T, HallEff |
| W2S130-AA03-01                                                 | Ball    | 230     | 42    | 233 | 52  | 75     | Leads      |
| W2S130-AA03-44                                                 | Ball    | 230     | 42    | 233 | 52  | 75     | Terminals  |
| W2S130-AA03-51                                                 | Ball    | 230     | 42    | 233 | 52  | 75     | T, HallEff |
| W2S130-AA03-49                                                 | Ball    | 115/230 | 42    | 233 | 52  | 75     | Leads      |
| W2S130-BM15-01                                                 | Ball    | 115     | 46    | 233 | 62  | 80     | Leads      |
| W2S130-BM03-01                                                 | Ball    | 230     | 46    | 233 | 62  | 80     | Leads      |
| 172roundx51mm (6.8 x 2.0inch), AC (60/50Hz), 35oz, UL/CSA/VDE  |         |         |       |     |     |        |            |
| W2E143-AA15-01                                                 | Ball    | 115     | 29    | 260 | 60  | 70     | Terminals  |
| W2E143-AA09-01                                                 | Ball    | 230     | 29    | 260 | 60  | 70     | Terminals  |
| W2E143-AA09-88                                                 | Ball    | 230     | 29    | 260 | 60  | 70     | T, HallEff |
| 225x225x38mm (8.9 x 3.2inch), AC (60/50Hz), 42oz, UL/CSA/VDE   |         |         |       |     |     |        |            |
| W2E200-HH82-01                                                 | Ball    | 115     | 60    | 500 | 56  | 75     | Terminals  |
| W2E200-HH64-01                                                 | Ball    | 230     | 60    | 500 | 56  | 75     | Terminals  |
| W2E200-HH86-01                                                 | Ball    | 115     | 80    | 607 | 61  | 75     | Terminals  |
| W2F200-HH38-01                                                 | Ball    | 230     | 80    | 607 | 61  | 75     | Terminals  |