

Model	Bearing	Volts	Range	Watts	CFM	dBA	Connect
119x119x38mm (4.7 x 1.5inch), DC, Max 75°C, 10 oz., UL/CSA/VDE							
4212L	Ball	12	7-14.5	1.2	51	29	Leads
4212M	Ball	12	7-14.5	2.2	75	38	Leads
4212GM	Sleeve	12	7-14.5	2.2	75	38	Leads
4292GM	Sleeve	12	7-14.5	2.2	75	38	02Term
4212	Ball	12	7-14.5	4.3	97	45	Leads
4212/2	Ball	12	7-14.5	4.3	97	45	L,TachOut
4212/12	Ball	12	7-14.5	4.3	97	45	L,TachOut
4212H	Ball	12	7-14.5	4.3	97	45	Leads
4214	Ball	24	12-28	4.3	97	45	Leads
4294	Ball	24	12-28	4.3	97	45	02Term
4214G	Sleeve	24	12-28	4.3	97	45	Leads
4214H	Ball	24	12-28	5.3	108	49	Leads
4294H	Ball	24	12-28	5.3	108	49	02Term
4218	Ball	48	36-56	4.3	97	45	Leads
4218/12	Ball	48	36-56	4.3	97	45	L,TachOut
4298	Ball	48	36-56	4.3	97	45	02Term
4218H	Ball	48	36-56	5.6	108	49	Leads
119x119x38mm (4.7 x 1.5inch), DC, Max 75°C, 14 oz., UL/CSA/VDE							
4182NGX	Sleeve	12	7-15	3.5	94	44	02Termin
4182NX	Ball	12	7-15	4.5	106	49	02Termin
4184NGX	Sleeve	24	12-30	3.5	94	44	02Termin
4184NX	Ball	24	12-29	4.5	106	49	02Termin
4188NXM	Ball	48	36-56	3.5	94	44	02Termin
4105GX	Sleeve	5	4.5-5.5	4.0	94	44	02Termin
127x127x38mm (5.0 x 1.5inch), DC, Max 72°C, 25 oz., UL/CSA/VDE							
W2G115-AD15-13	Ball	12	8-16	4.5	118	44	02Termin
W2G115-AD15-01	Ball	12	8-16	4.5	118	44	Leads
W2G115-AD17-13	Ball	24	18-30	4.7	118	44	02Termin
W2G115-AD17-01	Ball	24	18-30	4.7	118	44	Leads
W2G115-AD19-01	Ball	48	36-56	4.6	118	44	Leads
W2G115-AE53-13	Ball	12	8-16	5.9	130	48	02Termin
W2G115-AE53-01	Ball	12	8-16	5.9	130	48	Leads
W2G115-AE31-13	Ball	24	18-30	5.7	130	48	02Termin
W2G115-AE31-01	Ball	24	18-30	5.7	130	48	Leads
135x135x38mm (5.3 x 1.5inch), DC, Max 72°C, 23 oz., UL/CSA/VDE							
5112N	Ball	12	6-15	9.5	147	48	Leads
5114N	Ball	24	12-30	9.5	147	48	Leads
5118N	Ball	48	24-60	9.5	147	48	Leads

Model	Bearing	Volts	Range	Watts	CFM	dBA	Connect
150x172x38mm (5.9 x 1.5inch), DC, Max 72°C, 22 oz., UL/CSA/VDE							
7112N	Ball	12	6-15	12	212	55	Leads
7114N	Ball	24	12-30	12	212	55	Leads
7118N	Ball	48	24-60	12	212	55	Leads
150x172x55mm (5.9 x 2.2inch), DC, Max 60°C, 42 oz., UL/CSA							
W2G130-AA31-01	Ball	12	6-15	14	203	51	Leads
W2G130-AA31-20	Ball	12	6-15	14	203	51	L,HallEff
W2G130-AA33-01	Ball	24	12-30	14	203	51	Leads
W2G130-AA33-20	Ball	24	12-30	14	203	51	L,HallEff
W2G130-AA09-01	Ball	48	36-56	14	203	51	Leads
W2G130-AA09-20	Ball	48	36-56	14	203	51	L,HallEff
150x172x55mm (5.9 x 2.2inch), DC, Max 72°C, 26 oz., UL/CSA/VDE							
7212N	Ball	12	6-15	12	212	50	Leads
7214N	Ball	24	12-30	12	212	50	Leads
7214N/12	Ball	24	12-30	12	212	50	L,TachOut
7218N	Ball	48	24-60	12	212	50	Leads
172roundx51mm (6.8 x 2.0inch), DC, Max 72°C, 28 oz., UL/CSA/VDE							
6212NM	Ball	12	8-15	12	206	50	02Term
6224NM	Ball	24	12-32	12	206	50	02Term
6224N	Ball	24	12-28	18	241	55	02Term
6224N/2	Ball	24	12-28	18	241	55	02TermTO
6224N/12	Ball	24	12-28	18	241	55	02TermTO
6248NM	Ball	48	28-60	12	206	50	02Term
6248N	Ball	48	28-60	17	241	55	02Term
6248N/2	Ball	48	28-60	17	241	55	02TermTO
6248N/12	Ball	48	28-60	17	241	55	02TermTO
172ovalx51mm (6.8 x 2.0inch), DC, Max 72°C, 27 oz., UL/CSA/VDE							
6424	Ball	24	12-28	18	241	57	02Term
6448	Ball	48	28-60	17	241	57	02Term
200roundx70mm (7.9 x 2.8inch), DC, Max 72°C, 67 oz., UL/CSA/VDE							
2224	Ball	24	16-30	36	376	59	Leads
2248	Ball	48	32-60	36	376	59	Leads
225x225x80mm (8.9 x 3.2inch), DC, Max 60°C, 42 oz., UL/CSA/VDE							
W1G200-HH19-01	Ball	24	18-28	51	550	61	TermBlock
W1G200-HH01-01	Ball	48	36-56	51	550	61	TermBlock

Mega Fans

Curve	PART NUMBER	Type of Bearing	DC Volts	Voltage Range	Watts	CFM @ 0"	dBA	Temp. Max °C	Wgt. (oz)	Features	Approvals* UL CSA VDE		
1	612NGL	Sintec	12	8 to 15	0.8	12	16	70	3	24 AWG 12.2" Leads	✓	✓	✓
2	612NGML	Sintec	12	8 to 15	1.0	15	19	70	3	24 AWG 12.2" Leads	✓	✓	✓
4	612NGN	Sintec	12	8 to 15	2.1	24	35	70	3	24 AWG 12.2" Leads	✓	✓	✓
6	612NGHH	Sintec	12	8 to 15	3.8	33	43	70	3	24 AWG 12.2" Leads	✓	✓	✓
1	614NGL	Sintec	24	18 to 28	0.8	12	16	70	3	24 AWG 12.2" Leads	✓	✓	✓
2	614NGML	Sintec	24	18 to 28	1.0	15	19	70	3	24 AWG 12.2" Leads	✓	✓	✓
5	614NGH	Sintec	24	18 to 28	2.6	27	38	70	3	24 AWG 12.2" Leads	✓	✓	✓
1	3412NGL	Sintec	12	8 to 15	1.2	36	23	75	5	24 AWG 12.2" Leads	✓	✓	✓
1	3412NL	Ball	12	8 to 15	1.2	36	23	75	5	24 AWG 12.2" Leads	✓	✓	✓
2	3412NGM	Sintec	12	8 to 15	1.6	42	28	75	5	24 AWG 12.2" Leads	✓	✓	✓
2	3412NM	Ball	12	8 to 15	1.6	42	28	75	5	24 AWG 12.2" Leads	✓	✓	✓
3	3412NG	Sintec	12	8 to 15	2.2	49	32	75	5	24 AWG 12.2" Leads	✓	✓	✓
3	3412N	Ball	12	8 to 15	2.2	49	32	75	5	24 AWG 12.2" Leads	✓	✓	✓
1	3414NGL	Ball	24	18 to 28	1.4	36	23	75	5	24 AWG 12.2" Leads	✓	✓	✓
1	3414NL	Sleeve	24	18 to 28	1.4	36	23	75	5	24 AWG 12.2" Leads	✓	✓	✓
2	3414NGM	Ball	24	18 to 28	1.8	42	28	75	5	24 AWG 12.2" Leads	✓	✓	✓
2	3414NM	Sleeve	24	18 to 28	1.8	42	28	75	5	24 AWG 12.2" Leads	✓	✓	✓
1	4412FGL	Sintec	12	7 to 14	1.25	55	26	75	6	24 AWG 12.2" Leads	✓	✓	✓
2	4412FGML	Sintec	12	7 to 13	2.0	67	32	75	6	24 AWG 12.2" Leads	✓	✓	✓
1	4312NGL	Sintec	12	7 to 14.5	1.2	55	28	70	8	22 AWG 12.2" Leads	✓	✓	✓
2	4312NGM	Sintec	12	7 to 14.5	2.6	81	37	70	8	22 AWG 12.2" Leads	✓	✓	✓
1	4314NGL	Sintec	24	12 to 28	1.2	55	28	70	8	22 AWG 12.2" Leads	✓	✓	✓
2	4314NGM	Sintec	24	12 to 28	2.6	81	37	70	8	22 AWG 12.2" Leads	✓	✓	✓

* UL yellow card E38324, CSA file 27697, VDE file 1887