



RECTIFIER, CONTROL, AND FILAMENT TRANSFORMERS

WITH SINGLE SECONDARY


All primaries 50/60 Hz. May be operated from a 400 Hz source with no change in output rating. All secondary voltages $\pm 3\%$. Insulation test voltage is twice allowable rms working voltage plus 1000 volts.




Mtg. Style "A"



Mtg. Style "C"



Mtg. Style "NV"



Mtg. Style "S"

Mfr. No.	Secondary Volts	Secondary Amps	Test Volts (rms)	Primary Volts	Terminations	Mtg. Style	Size, Inches H x W x D
P-8629	2.5	1.0	1500	117	Leads	A	1 3/8 x 2 3/8 x 1 3/8
P-4026	2.5	1.5	2500	117	Leads	A	1 1/2 x 2 7/8 x 1 1/2
P-6133†	2.5 CT	5.0	7500	117	Leads	S	2 3/4 x 3 1/8 x 2 1/4
P-6454	2.5 CT	10.0	7500	117/107	Leads	S	3 1/8 x 3 5/8 x 2 1/2
P-6467	5.0 CT	3.0	2500	117	Leads	A	2 x 3 1/4 x 2 1/8
P-6135	5.0 CT	10.0	2500	117	Leads	NV	3 1/8 x 2 1/2 x 2 3/4
P-8385	6.3 CT	0.3	1500	117	Leads	A	1 1/4 x 2 1/8 x 1 1/8
P-6465‡	6.3 CT	0.6	1500	117	Leads	A	1 3/8 x 2 3/8 x 1 1/2
P-8705	6.3 CT	0.6	1500	230	Leads	A	1 3/8 x 2 3/8 x 1 1/2
P-8389‡	6.3	1.0	1500	117	Leads	A	1 1/2 x 2 7/8 x 1 1/8
P-6134‡	6.3 CT	1.2	3000	117	Leads	A	1 1/2 x 2 7/8 x 1 1/8
P-8190	6.3	1.2	5000	117	Leads	A	2 x 3 1/4 x 1 7/8
P-6466	6.3 CT	3.0	2500	117	Leads	A	2 x 3 1/4 x 2 1/8
P-8648	6.3 CT	4.0	1500	117	Leads	A	2 3/8 x 3 3/4 x 2 1/8
P-8649	6.3 CT	5.0	1500	117	Leads	A	2 3/8 x 3 3/4 x 2 1/8
P-3064†	6.3 CT	6.0	2500	117	Lugs	NV	3 1/8 x 2 1/2 x 2 3/8
P-6456	6.3 CT	6.0	2000	117/107	Leads	A	2 3/8 x 3 3/4 x 2 3/8
P-8651	6.3 CT	8.0	1500	117	Leads	A	2 3/8 x 4 x 2 1/4
P-6464	6.3 CT	10.0	2000	117	Leads	C	3 1/2 x 2 1/8 x 3 1/4
P-6308†	6.3 CT	10.0	2500	117/107	Leads	NV	3 3/16 x 2 1/16 x 2 3/8
P-6309	6.3 CT	20.0	2500	117/107	Leads	NV	4 9/16 x 3 3/4 x 3 3/8
P-5015†	7.5 CT	4.0	2500	117	Lugs	NV	3 1/8 x 2 1/2 x 2 1/4
P-6138†	7.5 CT	8.0	2500	117	Leads	NV	3 1/8 x 3 3/8 x 2 3/4
P-8652	10.0 CT	1.0	1500	117	Leads	A	2 x 3 1/4 x 1 5/8
P-8653	10.0 CT	2.0	1500	117	Leads	A	2 x 3 1/4 x 2
P-8380	10.0 CT	3.0	1500	117	Leads	A	2 3/8 x 3 3/4 x 2 1/4
P-8654	10.0 CT	4.0	1500	117	Leads	A	2 3/8 x 4 x 2 1/8
P-5016†	10.0 CT	4.0	2500	117	Lugs	NV	3 7/16 x 2 1/16 x 2 1/2
P-6458	10.0 CT	5.0	2000	117/107	Leads	NV	3 1/8 x 2 1/2 x 2 1/8
P-8655	10.0 CT	6.0	1500	117	Leads	NV	3 1/8 x 2 1/2 x 2 3/8
P-8656	10.0 CT	8.0	1500	117	Leads	NV	3 7/16 x 2 1/16 x 3
P-6461	10.0 CT	10.0	2000	117	Leads	C	3 7/8 x 3 1/4 x 3 9/16
P-8391	12.0	0.15	1500	117	Leads	A	1 1/4 x 2 1/8 x 1 1/4
P-8392‡	12.0	0.35	1500	117	Leads	A	1 3/8 x 2 3/8 x 1 3/8
P-8393‡	12.0	0.70	1500	117	Leads	A	1 1/2 x 2 7/8 x 1 1/8
P-8393	12.0	1.2	1500	117	Leads	A	2 x 3 1/4 x 1 5/8
P-8657	12.0	2.0	1500	117	Leads	A	2 x 3 1/4 x 2 1/8
P-8658	12.0	4.0	1500	117	Leads	A	2 3/8 x 4 x 2 1/4
P-8659	12.0	6.0	1500	117	Leads	NV	3 7/16 x 2 1/16 x 2 3/8
P-8660	12.0	8.0	1500	117	Leads	NV	3 1/8 x 3 1/8 x 2 3/4
P-8384	12.6 CT	1.0	1500	117	Leads	A	2 x 3 1/4 x 1 3/4
P-8550	12.6 CT	1.5	1500	115	Leads	A	1 1/8 x 3 9/16 x 2
P-8130‡	12.6 CT	2.0	1500	117	Leads	A	2 x 3 1/4 x 2 1/8
P-8715	12.6 CT	2.0	1500	230	Leads	A	2 x 3 1/4 x 2 1/8
P-8358	12.6 CT	3.0	1500	117	Leads	A	2 3/8 x 3 3/4 x 2 1/4
P-8641	12.6 CT	4.0	1500	117	Leads	A	2 3/8 x 4 x 2 3/8
P-8716	12.6 CT	4.0	2500	230	Leads	A	2 3/8 x 4 x 2 3/8
P-8642	12.6 CT	6.0	1500	117	Leads	C	3 1/2 x 2 1/8 x 3 3/8
P-8644	12.6 CT	10.0	1500	117	Leads	C	4 1/4 x 3 7/16 x 3 3/8
P-8577	14.0 CT	0.25	1500	115/230	Leads	A	1 3/8 x 2 3/8 x 1 1/2
P-8553	14.0 CT	0.25	1500	115	Leads	A	1 3/8 x 2 3/8 x 1 1/8
P-8555	14.0 CT	1.0	1500	115	Leads	A	1 1/8 x 3 1/4 x 1 3/4
P-8556	14.0 CT	2.0	1500	115	Leads	A	2 1/4 x 3 11/16 x 1 1 5/16
P-8557	14.0 CT	4.0	1500	115	Leads	NV	3 x 2 1/2 x 2 7/16
P-8558	14.0 CT	6.0	1500	115	Leads	NV	3 3/8 x 2 1/8 x 2 7/8
P-8690	18.0 CT	0.75	1500	115	Leads	A	1 1/8 x 3 9/16 x 2
P-8691	18.0 CT	1.0	1500	115	Leads	A	1 1/8 x 3 9/16 x 2 1/8
P-8692	18.0 CT	1.5	1500	115	Leads	A	2 3/32 x 3 3/4 x 2 1/8
P-8693	18.0 CT	2.0	1500	115	Leads	A	2 3/32 x 3 3/4 x 2 1/4
P-8500	20.0 CT	0.05	2500	115/230	Leads	A	1 1/4 x 2 1/8 x 1 1/4
P-8504	20.0 CT	0.25	2500	115/230	Leads	A	1 3/8 x 2 3/8 x 1 3/8
P-8505	20.0 CT	0.3	2500	115/230	Leads	A	1 3/8 x 2 3/8 x 1 3/8
P-8507	20.0 CT	0.5	2500	115/230	Leads	A	1 3/8 x 2 3/8 x 1 1/2
P-8508	20.0 CT	1.0	2500	115/230	Leads	A	2 x 3 1/4 x 2 1/4
P-8604‡	20.0 CT	1.0	1500	117	Leads	A	2 x 3 1/4 x 2 1/8
P-8559	20.0 CT	2.0	1500	115	Leads	NV	2 3/16 x 4 x 2 1/4
P-8560	20.0 CT	4.0	1500	115	Leads	NV	3 3/8 x 2 1/8 x 2 7/8
P-8551*	24.0	1.0	1500	115	Leads	A	1 1/8 x 3 1/4 x 2 1/8
P-8694*	24.0	2.0	1500	115	Leads	A	2 3/16 x 4 x 2
P-8394	24.0 CT	0.09	1500	117	Leads	A	1 1/4 x 2 1/8 x 1 1/4
P-8720	24.0 CT	0.09	1500	230	Leads	A	1 1/4 x 2 1/8 x 1 1/4
P-8395‡	24.0 CT	0.2	1500	117	Leads	A	1 3/8 x 2 3/8 x 1 3/8
P-8721	24.0 CT	.200	1500	230	Leads	A	1 3/8 x 2 3/8 x 1 3/8
P-8578	24.0 CT	0.2	1500	115/230	Leads	A	1 3/8 x 2 3/8 x 1 1/2
P-8396‡	24.0 CT	0.4	1500	117	Leads	A	1 3/8 x 2 7/8 x 1 3/8
P-8722	24.0 CT	.400	1500	230	Leads	A	1 3/8 x 2 7/8 x 1 1/2
P-8397‡	24.0 CT	0.7	1500	117	Leads	A	2 x 3 1/4 x 1 3/4
P-8723	24.0 CT	.700	1500	230	Leads	A	2 x 3 1/4 x 1 5/8
P-8661	24.0 CT	1.0	1500	117	Leads	A	2 x 3 1/4 x 2 1/8
P-8575	24.0 CT	1.0	1500	115/230	Leads	A	1 1/8 x 3 9/16 x 2
P-8662	24.0 CT	2.0	1500	117	Leads	A	2 3/8 x 4 x 2 3/8
P-8663‡	24.0 CT	4.0	1500	117	Leads	NV	3 1/8 x 3 1/8 x 2 1/8
P-8664	24.0 CT	6.0	1500	117	Leads	NV	4 3/16 x 3 7/16 x 3
P-8665	24.0 CT	8.0	1500	117	Leads	NV	4 3/16 x 3 7/16 x 3 3/8
P-8695	24.0 CT	10.0	1500	115	Leads	NV	4 3/8 x 3 7/16 x 3 3/4
P-8666‡	24.0 CT	12.0	1500	117	Leads	NV	4 3/8 x 3 3/4 x 4 3/8
P-6469	25.2	1.0	1500	117	Leads	A	2 x 3 1/4 x 2 1/8
P-8707	25.2	1.0	1500	230	Leads	A	2 x 3 1/4 x 2 1/8
P-8180	25.2 CT	1.0	1500	117	Leads	A	2 x 3 1/4 x 2 1/4

* 60 Hz only.

† Has electrostatic shield.

‡ U.L. Recognized.

LISTING CONTINUED ON FOLLOWING PAGE