

## ORIGINAL EQUIPMENT CORDS 3-CONDUCTOR BELDFOIL® SHIELDED, PVC JACKETED

W I R E S L I N E C O R D S & A C C



| Belden No. | Length of Cord | Temp. °C | Color Coding | AWG (Stranding) | Nominal OD (In.) | Rating @125V |      | Type Cordage | Jacket Color |
|------------|----------------|----------|--------------|-----------------|------------------|--------------|------|--------------|--------------|
|            |                |          |              |                 |                  | Watts        | Amps |              |              |
| 17720†     | 6'7"           | 60       | INT'L        | 18(42×34)       | .270             | 1250         | 10   | SVT          | Black        |
| 17740      | 6'7"           | 60       | INT'L        | 18(42×34)       | .270             | 1250         | 10   | SVT          | Black        |
| 17741      | 9'10"          | 60       | INT'L        | 18(42×34)       | .270             | 1250         | 10   | SVT          | Black        |
| 17612      | 6'7"           | 60       | INT'L        | 18(42×34)       | .3280            | 1250         | 10   | SJT          | Black        |
| 17613      | 9'10"          | 60       | INT'L        | 18(42×34)       | .328             | 1250         | 10   | SJT          | Black        |
| 17614      | 6'7"           | 60       | INT'L        | 16(65×34)       | .353             | 1625         | 13   | SJT          | Black        |
| 17615      | 9'10"          | 60       | INT'L        | 16(65×34)       | .353             | 1625         | 13   | SJT          | Black        |
| 17616      | 6'7"           | 60       | INT'L        | 14(41×30)       | .388             | 1875         | 15   | SJT          | Black        |
| 17617      | 9'10"          | 60       | INT'L        | 14(41×30)       | .388             | 1875         | 15   | SJT          | Black        |




| Belden No. | Length of Cord | Temp. °C | Color Coding | AWG (Stranding) | Nominal OD (In.) | Rating |            |            | Type Cordage | Jacket Color |
|------------|----------------|----------|--------------|-----------------|------------------|--------|------------|------------|--------------|--------------|
|            |                |          |              |                 |                  | Watts  | @125V Amps | @250V Amps |              |              |
| 17749      | 6'7"           | 60       | INT'L        | 18(42×34)       | .270             | 1250   | 10         | 10         | SVT          | Black        |
| 17750      | 9'10"          | 60       | INT'L        | 18(42×34)       | .270             | 1250   | 10         | 10         | SVT          | Black        |
| 17618      | 6'7"           | 60       | INT'L        | 18(42×34)       | .328             | 1250   | 10         | 10         | SJT          | Black        |
| 17619      | 9'10"          | 60       | INT'L        | 18(42×34)       | .328             | 1250   | 10         | 10         | SJT          | Black        |
| 17620      | 6'7"           | 60       | INT'L        | 16(65×34)       | .353             | 1625   | 13         | 10         | SJT          | Black        |
| 17621      | 9'10"          | 60       | INT'L        | 16(65×34)       | .353             | 1625   | 13         | 10         | SJT          | Black        |



| Belden No. | Length of Cord | Temp. °C | Color Coding | AWG (Stranding) | Nominal OD (In.) | Rating |            |            | Type Cordage | Jacket Color |
|------------|----------------|----------|--------------|-----------------|------------------|--------|------------|------------|--------------|--------------|
|            |                |          |              |                 |                  | Watts  | @125V Amps | @250V Amps |              |              |
| 17751      | 6'7"           | 60       | INT'L        | 18(42×34)       | .270             | 1250   | 10         | 10         | SVT          | Black        |
| 17752      | 9'10"          | 60       | INT'L        | 18(42×34)       | .270             | 1250   | 10         | 10         | SVT          | Black        |
| 17636      | 6'7"           | 60       | INT'L        | 18(42×34)       | .328             | 1250   | 10         | 10         | SJT          | Black        |
| 17637      | 9'10"          | 60       | INT'L        | 18(42×34)       | .328             | 1250   | 10         | 10         | SJT          | Black        |

## DETACHABLE, BELDFOIL® SHIELDED, PVC JACKETED



| Belden No. | Length of Cord | Temp. °C | Color Coding | AWG (Stranding) | Nominal OD (In.) | Rating @125V |      | Type Cordage | Jacket Color |
|------------|----------------|----------|--------------|-----------------|------------------|--------------|------|--------------|--------------|
|            |                |          |              |                 |                  | Watts        | Amps |              |              |
| 17725†     | 6'7"           | 105      | INT'L        | 18(42×34)       | .270             | 1250         | 10   | SVT          | Black        |
| 17742      | 6'7"           | 60       | INT'L        | 18(42×34)       | .270             | 1250         | 10   | SVT          | Black        |
| 17743      | 9'10"          | 60       | INT'L        | 18(42×34)       | .270             | 1250         | 10   | SVT          | Black        |
| 17729†     | 6'7"           | 105      | INT'L        | 18(42×34)       | .328             | 1250         | 10   | SJT          | Black        |
| 17600      | 6'7"           | 60       | INT'L        | 18(42×34)       | .328             | 1250         | 10   | SJT          | Black        |
| 17601      | 9'10"          | 60       | INT'L        | 18(42×34)       | .328             | 1250         | 10   | SJT          | Black        |
| 17602      | 6'7"           | 60       | INT'L        | 16(65×34)       | .353             | 1625         | 13   | SJT          | Black        |
| 17603      | 9'10"          | 60       | INT'L        | 16(65×34)       | .353             | 1625         | 13   | SJT          | Black        |
| 17604      | 6'7"           | 60       | INT'L        | 14(41×30)       | .388             | 1875         | 15   | SJT          | Black        |
| 17605      | 9'10"          | 60       | INT'L        | 14(41×30)       | .388             | 1875         | 15   | SJT          | Black        |

† Passes VW-1 Vertical Wire Flame Test.

(CONTINUED ON NEXT PAGE)