


Screw Mount Ties


22

Screw-Mount Cable Ties


Secure bundled harnesses to panels. They may also be pre-mounted to existing surfaces before final assembly.

- Specifications: Type 6/6 Nylon
- Self-extinguishing — UL 94 Flam. Class: V-2
- Designed in accordance with MIL-S-23190 and MS 3367.
- Meets ASTM D 4066-82.
- Stocked in natural, weather-resistant black, and heat stabilized black. Other colors upon request.

- Natural operating temperatures from -40°F (-40°C) to 185°F (85°C). Weather resistant from -40°F (-40°C) to 176°F (80°C). Heat stabilized from -40°F (-40°C) to 221°F (105°C).
- Recognized under the component program of Underwriters Laboratories, Inc.  File No. E 57800.


SCREW-MOUNT TIES-Standard Accepts #10 Screw

PART NO.	STYLE	LENGTH	BUNDLE DIA. MIN.-MAX.	MINIMUM LOOP TENSILE STRENGTH	PACKAGE QUANTITY
08415	NATURAL SCREW MOUNT	7.5" (194 mm)	1/16"-1-3/4" (1.5-45 mm)	50 LBS. (22.7 kg)	1000/BAG
08444	BLACK/WR/SCREW MOUNT				1000/BAG
08443	BLACK/HS/SCREW MOUNT				1000/BAG
08484	NATURAL SCREW MOUNT	11" (280 mm)	1/16"-3" (1.5-76 mm)	50 LBS. (22.7 kg)	100/BAG
08318	BLACK/WR/SCREW MOUNT				100/BAG
10350	NATURAL SCREW MOUNT				1000/BAG
10352	BLACK/WR/SCREW MOUNT	1000/BAG			
10351	BLACK/HS/SCREW MOUNT	1000/BAG			
10353	NATURAL SCREW MOUNT	100/BAG			100/BAG
10354	BLACK/WR/SCREW MOUNT				100/BAG


SCREW-MOUNT TIES—HEAVY DUTY Accepts 1/4" Screw

PART NO.	STYLE	LENGTH	BUNDLE DIA. MIN.-MAX.	MINIMUM LOOP TENSILE STRENGTH	PACKAGE QUANTITY
10035	NATURAL SCREW MOUNT	14.5" (373 mm)	3/16"-4" (4.5-102 mm)	120 LBS. (55 kg)	100/BAG
10040	BLACK/WR/SCREW MOUNT				100/BAG
08441	BLACK/HS/SCREW MOUNT				100/BAG
08426	NATURAL SCREW MOUNT	50/BAG			50/BAG
08442	BLACK/WR/SCREW MOUNT				50/BAG

**W I R E S
L I N E
C O R D S & A C C**