Mounts

 Constructed of durable, high tensile Type 6/6 Nylon, natural color. Special colors available on request. Cable Tie slips easily through slot.
 Tie is securely contained for easy assembly and tensioning.

 Recognized under the component program of Underwriters Laboratories, Inc.
 File No. E 57800.





10044 #4 screw; for miniature ties.



10045 #8 screw; for ties up to standard.



10046 #10 screw; for ties up to heavy duty.



1/4" screw; (6 mm Hole) for heat stabilized ties up to heavy duty.

Accommodate miniature, intermediate, standard and heavy duty sized cable ties.

Provide Stability in Wire Run.

PART NO.	STYLE	PACKAGE QUANTITY
10044	CRADLE MOUNT SMALL #4 SCREW	100/BAG
10045	CRADLE MOUNT MEDIUM #8 SCREW	100/BAG
10046	CRADLE MOUNT LARGE #10 SCREW	100/BAG
10079	CRADLE MOUNT LARGE 1/4" SCREW HEAT STABILIZED (6 mm Hole)	100/BAG

TIE ANCHOR BASE

Accommodate miniature, inter-

mediate, and standard sized

Allows four-way tie mounting



10027 #8 Screw

with low profile.

cable ties.



10028 #10 Screw

LOW PROFILE MOUNT



08458 #8 Screw

- Accommodate miniature, intermediate, and standard sized cable ties.
- Low height accommodates minimal space limitations.

PUSH-IN MOUNTS



- Accommodate miniature, intermediate, and standard sized cable ties.
- For use in .250" hole. (6 mm Hole)


PART NO.	STYLE	
10027 10028 08458 10056	TIE ANCHOR BASE #8 SCREW TIE ANCHOR BASE #10 SCREW LOW PROFILE MOUNT #8 SCREW PUSH-IN MOUNT 1/4" HOLE (6 mm Hole)	100/BAG 100/BAG 100/BAG 100/BAG

Cable Clip

- Available in acrylic-based adhesive
- Allows use of any width cable
- Accommodates stacked cable
- Made of Type 6/6 Nylon
- High quality, durable, non-conductive



Adhesive Mount



PART. NO.	STYLE	PACKAGE QUANTITY	
08406	ADHESIVE FLAT CABLE CLIP	100/BAG	







Adhesive Backed Mount Selection Chart

	Adhesive Selec	
Mount Application	Rubber	Acrylic
Paper/Cardboard	Х	
Steel/Aluminum	Х	Х
Glass/Ceramics		Х
Rubber	Х	
Painted Surfaces	Х	Х
Cloth	Х	
Rigid Vinyl	X	Х
Plasticized Vinyl		Х
Polypropylene/Polyethylene	Х	
ABS Acrylics	Х	
Polystyrene	Х	Х
Urethane	Х	

Relative Solvent Resistance		
Rubber	Medium	
Acrylic	High	

	Surface Selection	
Painted Surfaces	Rubber	Acrylic
Polene	Х	
Urethane	X	
Silicone	X	
Latex	X	
Enamel		Х
Acrylic		Х

Temperature	Low	High Temperature	
Performance	Temperature	Continuous	Intermittent
Rubber	-20°F	150°F	200°F
Acrylic	-20°F	180°F	375°F

Relative Shear Strength		
Rubber	High	
Acrylic	Very High	

Peel Strength	Initial	Ultimate	
Rubber	High	High	
Acrylic	Medium	High	

Cable Tie Mounts

Adhesive Backed and Screw Mount



3/4" (19 mm) 08461 Acrylic-based adhesive 10029 Rubber-based adhesive



1" (25 mm)

08462 Acrylic-based adhesive 10030 Rubber-based adhesive



1" (25 mm)

08463 For use with #6 screw

- Two mounts per peel-off strip provides faster separation from backing.
- Type 6 Nylon for high impact and tensile strength.
- Nylon operating temperatures from -40°F (-40°C) to 185°F (85°C)
- Four-way tie insertion speeds assembly. Ties slide easily into mounts from any of four sides.
- Adhesive-backed mounts (Acrylic or Rubber based) conform to minor surface irregularities.
- Load carrying capability for 1" (25 mm) adhesive-backed mounts is 0.5 lb. (.23 kg); 3/4" (19 mm) mounts is 0.25 lb. (.11 kg).
- Stocked in natural color. Other colors available on request.
- Recognized under the component program of Underwriters Laboratories, Inc. File No. E 57800.

PART NO.	STYLE	PACKAGE QUANTITY
08461 10029 08462 10030 08463	3/4" ACRYLIC ADHESIVE MOUNT FOR MINIATURE AND INTERMEDIATE TIES (19mm) 3/4" RUBBER BASED ADHESIVE MOUNT FOR MINIATURE AND INTERMEDIATE TIES (19mm) 1" ACRYLIC ADHESIVE MOUNT FOR INTERMEDIATE AND STANDARD TIES (25mm) 1" RUBBER BASED ADHESIVE MOUNT FOR INTERMEDIATE AND STANDARD TIES (25mm) 1" PLAIN BACKED MOUNT FOR INTERMEDIATE AND STANDARD TIES (25mm)	100/BAG 100/BAG 100/BAG 100/BAG 100/BAG