


## FERRULES

Insulated twin ferrules	Wire size		Color	Strip length	Dimensions (mm)*								P/N
	mm <sup>2</sup>	AWG			L1	L2	d1	S1	E2/d2	S2	D1	W/D2	
	2 x 0.5	2 x 22	White	5.2	15.0	8.0	1.50	0.15	2.5/4.7	0.25	1.80	3.0/5.2	0304 558.10
	2 x 0.75	2 x 20	Grey	5.5	15.0	8.0	1.80	0.15	2.8/5.0	0.25	2.10	3.3/5.5	0304 559.11
	2 x 0.75	2 x 20	Grey	5.5	17.0	10.0	1.80	0.15	2.8/5.0	0.25	2.10	3.3/5.5	0304 560.16
	2 x 1.0	2 x 18	Red	6.0	15.0	8.0	2.05	0.15	3.4/5.4	0.30	2.35	4.0/6.0	0304 561.03
	2 x 1.0	2 x 18	Red	6.0	17.0	10.0	2.05	0.15	3.4/5.4	0.30	2.35	4.0/6.0	0304 562.04
	2 x 1.5	2 x 16	Black	7.2	16.0	8.0	2.30	0.15	3.6/5.6	0.30	2.60	4.2/7.2	0304 563.05
	2 x 1.5	2 x 16	Black	7.2	20.0	12.0	2.30	0.15	3.6/5.6	0.30	2.60	4.2/7.2	0304 564.06
	2 x 2.5	2 x 14	Blue	8.4	18.5	10.0	2.90	0.20	4.2/7.8	0.30	3.30	4.8/8.4	0304 565.07
	2 x 2.5	2 x 14	Blue	8.4	21.5	13.0	2.90	0.20	4.2/7.8	0.30	3.30	4.8/8.4	0304 566.00
	2 x 4.0	2 x 12	Grey	9.4	23.0	12.0	3.80	0.20	4.9/8.8	0.30	4.20	5.5/9.4	0304 567.01
	2 x 6.0	2 x 10	Yellow	10.8	26.0	14.0	4.90	0.20	6.9/10.0	0.40	5.30	7.7/10.8	0304 568.12
	2 x 10.0	2 x 8	Red	13.8	26.0	14.0	6.50	0.20	7.2/13.0	0.40	6.90	8.0/13.8	0304 569.13
	2 x 16.0	2 x 6	Blue	19.2	30.0	14.0	8.30	0.20	9.6/18.4	0.40	8.70	10.4/19.2	0304 570.10



Uninsulated ferrules	Wire size		Strip length	Dimensions (mm)*			P/N
	mm <sup>2</sup>	AWG		L	d1	D2	
	0.5	22	5.5	6	1.0	2.1	0304 571.05
	0.75	20	5.5	6	1.4	2.5	0304 572.06
	1.0	18	5.5	6	1.6	2.7	0304 573.07
	1.0	18	8.5	10	1.6	2.7	0304 574.00
	1.5	16	6.0	7	1.8	2.9	0304 575.01
	1.5	16	9.0	10	1.8	2.9	0304 576.02
	2.5	14	6.0	7	2.3	3.5	0304 577.03
	2.5	14	11.0	12	2.3	3.5	0304 578.14
	4.0	12	8.0	9	2.8	4.0	0304 579.15
	4.0	12	11.0	12	2.8	4.0	0304 580.03
	6.0	10	9.0	10	3.7	4.8	0304 581.20
	6.0	10	11.0	12	3.7	4.8	0304 582.21
	6.0	10	14.0	15	3.7	4.8	0304 583.22
	10.0	8	11.0	12	4.6	5.8	0304 584.23
	10.0	8	14.0	15	4.6	5.8	0304 585.24
	10.0	8	17.0	18	4.6	5.8	0304 586.25
	16.0	6	10.5	12	5.9	7.5	0304 587.26
	16.0	6	13.5	15	5.9	7.5	0304 588.07
	16.0	6	16.5	18	5.9	7.5	0304 589.00

\*Dimensions may vary slightly from one shipment to the next. See page 1924 for ferrule crimping tools.