




---

 PRODUCT-DETAILS

# S804U-UCZ70

## S804U-UCZ70 High Performance MCB




---

**General Information**

Extended Product Type	S804U-UCZ70
Product ID	2CCS248364R0001
EAN	7612271420789
Catalog Description	S804U-UCZ70 High Performance MCB
Long Description	S804U-UCZ70 4 Pole Z Characteristic 70A 10kA 600VDC High Performance Circuit Breaker HPCB

---

**ABB EcoSolutions**

ABB EcoSolutions	Yes
EcoSolutions Profile	9AKK108471A1082
Recyclability Rate of the Product acc. to EN45555	Design for Closing Resource Loops - Standard EN45555 - 86.29 %
ABB Site Meeting Group Waste To Landfill Target	No non-hazardous waste is sent to a landfill
End Of Life Disassembling Instructions	9AKK108470A2575
Environmental Product	9AKK108470A1695,9AKK108470A1696

## Declaration - EPD

**Technical**

Rated Ultimate Short-Circuit Breaking Capacity ( $I_{cu}$ )	(415 V AC) 50 kA
Rated Service Short-Circuit Breaking Capacity ( $I_{cs}$ )	(415 V AC) 40 kA
Contact Position Indication	ON / OFF / TRIP
Energy Limiting Class	3
Number of Protected Poles	4
Number of Poles	4P
Release Type	Other
Actuator Marking	I / O
Options Provided	Universal current
Accessories Available	Yes
Connecting Capacity	Flexible 0 ... 50 mm <sup>2</sup> Rigid 0 ... 70 mm <sup>2</sup>

**Electrical**

Short-Circuit Current Rating (SCCR)	(600 V DC) 10 kA
Tripping Characteristic	Z
Rated Operational Voltage	UL489 600 V DC
Rated Insulation Voltage ( $U_i$ )	acc. to IEC/EN 60664-1 1500 V
Rated Impulse Withstand Voltage ( $U_{imp}$ )	8 kV
Input Voltage Type	DC
Rated Current ( $I_n$ )	70 A
Frequency (f)	0...0 Hz
Rated Frequency (f)	0 Hz
Power Loss	Total 6 W at Rated Operating Conditions per Pole 1.5 W
Overvoltage Category	III

**Technical UL/CSA**

Interrupting Rating acc. to UL489	(600 V DC) 10 kA
-----------------------------------	------------------

**Material Compliance**

RoHS Declaration	2CCC005116D0201
RoHS Information	Following EU Directive 2011/65/EU and Amendment 2015/863 July 22, 2019
RoHS Date	20250625
REACH Declaration	9AKK108470A9089
REACH Information	False - does not contain substances > 0.1 mass percentage

REACH Date	20250313
Conflict Minerals Reporting Template (CMRT)	9AKK108468A3363
WEEE Category	5. Small Equipment (No External Dimension More Than 50 cm)
WEEE B2C / B2B	Business To Business

## Environmental

Ambient Air Temperature	Operation -25 ... +60 °C Storage -40 ... +70 °C
Degree of Protection	IP20
Pollution Degree	3
Environmental Information	2CCY413207D0203

## Dimensions

Width in Number of Modular Spacings	6
Product Net Width	106 mm
Product Net Height	142 mm
Product Net Depth / Length	82.5 mm
Product Net Weight	980 g
Built-In Depth (t <sub>2</sub> )	82.5 mm

## Engineering

EPLAN Data	9AAF622589_EPLAN
------------	------------------

## Ordering

Package Level 1 Units	box 1 piece
Package Level 1 Gross Weight	1010 g

## Certificates and Declarations

CCC Certificate	CQC2007010307251328
CEBEC Certificate	9AKK108469A3550
Declaration of Conformity - CE	2CCC413009D0201
DNV GL Certificate	2CCC413018D0201
UL Certificate	9AKK108469A3551

## Installation

Instructions and Manuals	9AKK1074920410
--------------------------	----------------

---

## Popular Downloads

---

Data Sheet, Technical Information	9AKK108468A9560
	9AKK108468A9561
	9AKK108468A9562

---



---

## External Classifications and Standards

---

ETIM 9	EC000042 - Miniature circuit breaker (MCB)
ETIM 10	EC000042 - Miniature circuit breaker (MCB)
UNSPSC	39121603
eClass	V11.0 : 27141901
IDEA Granular Category Code (IGCC)	4899 >> Miniature circuit breaker (MCB) screw-in model
Object Classification Code	F
Standards	UL 489

---



---

## Categories

---

Low Voltage Products and Systems → Modular DIN Rail Products → High Performance Circuit Breakers HPCBs → High Performance Circuit Breakers HPCBs - S800

